

# LM124, LM124A, LM224, LM224A LM324, LM324A, LM2902 QUADRUPLE OPERATIONAL AMPLIFIERS

SLOS066F – SEPTEMBER 1975 – REVISED JANUARY 2002

- **Wide Range of Supply Voltages:**  
Single Supply . . . 3 V to 30 V  
(LM2902 3 V to 26 V) or Dual Supplies
- **Low Supply Current Drain Independent of Supply Voltage** . . . 0.8 mA Typ
- **Common-Mode Input Voltage Range**  
Includes Ground Allowing Direct Sensing Near Ground
- **Low Input Bias and Offset Parameters:**
  - Input Offset Voltage . . . 3 mV Typ  
A Versions . . . 2 mV Typ
  - Input Offset Current . . . 2 nA Typ
  - Input Bias Current . . . 20 nA Typ  
A Versions . . . 15 nA Typ
- **Differential Input Voltage Range Equal to Maximum-Rated Supply Voltage** . . . 32 V  
(26 V for LM2902)
- **Open-Loop Differential Voltage Amplification** . . . 100 V/mV Typ
- **Internal Frequency Compensation**


## description

These devices consist of four independent high-gain frequency-compensated operational amplifiers that are designed specifically to operate from a single supply over a wide range of voltages. Operation from split supplies is also possible when the difference between the two supplies is 3 V to 30 V (for the LM2902, 3 V to 26 V) and  $V_{CC}$  is at least 1.5 V more positive than the input common-mode voltage. The low supply current drain is independent of the magnitude of the supply voltage.


Applications include transducer amplifiers, dc amplification blocks, and all the conventional operational-amplifier circuits that now can be more easily implemented in single-supply-voltage systems. For example, the LM124 can be operated directly from the standard 5-V supply that is used in digital systems and easily provides the required interface electronics without requiring additional  $\pm 15$ -V supplies.

The LM124 and LM124A are characterized for operation over the full military temperature range of  $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ . The LM224 and LM224A are characterized for operation from  $-25^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ . The LM324 and LM324A are characterized for operation from  $0^{\circ}\text{C}$  to  $70^{\circ}\text{C}$ . The LM2902 is characterized for operation from  $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ .

LM124, LM124A . . . J OR W PACKAGE  
LM224, LM224A, LM324, LM324A,  
LM2902 . . . D, DB, N, OR PW PACKAGE  
(TOP VIEW)



LM124, LM124A . . . FK PACKAGE  
(TOP VIEW)



NC – No internal connection

LM124, LM124A, LM224, LM224A  
 LM324, LM324A, LM2902  
 QUADRUPLE OPERATIONAL AMPLIFIERS


SLOS066F – SEPTEMBER 1975 – REVISED JANUARY 2002

AVAILABLE OPTIONS


| T <sub>A</sub> | V <sub>IO</sub> MAX<br>AT 25°C | SMALL<br>OUTLINE<br>(D) | VERY SMALL<br>OUTLINE<br>(DB) | CHIP<br>CARRIER<br>(FK) | CERAMIC<br>DIP<br>(J) | PLASTIC<br>DIP<br>(N) | TSSOP<br>(PW) | FLAT<br>PACK<br>(W) |
|----------------|--------------------------------|-------------------------|-------------------------------|-------------------------|-----------------------|-----------------------|---------------|---------------------|
| 0°C to 70°C    | 7 mV                           | LM324D                  | LM324DB                       | —                       | —                     | LM324N                | LM324PW       | —                   |
|                | 3 mV                           | LM324AD                 | —                             | —                       | —                     | LM324AN               | LM324APW      | —                   |
| –25°C to 85°C  | 5 mV                           | LM224D                  | —                             | —                       | —                     | LM224N                | —             | —                   |
|                | 3 mV                           | LM224AD                 | —                             | —                       | —                     | LM224AN               | —             | —                   |
| –40°C to 125°C | 7 mV                           | LM2902D                 | LM2902DB                      | —                       | —                     | LM2902N               | LM2902PW      | —                   |
| –55°C to 125°C | 5 mV                           | LM124D                  | —                             | LM124FK                 | LM124J                | —                     | —             | LM124W              |
|                | 2 mV                           | —                       | —                             | LM124AFK                | LM124AJ               | —                     | —             | —                   |

The D package is available taped and reeled. Add the suffix R to the device type (e.g., LM324DR). The DB and PW packages are only available taped and reeled.

symbol (each amplifier)



schematic (each amplifier)



| COMPONENT COUNT<br>(total device) |    |
|-----------------------------------|----|
| Epi-FET                           | 1  |
| Transistors                       | 95 |
| Diodes                            | 4  |
| Resistors                         | 11 |
| Capacitors                        | 4  |

**LM124, LM124A, LM224, LM224A  
LM324, LM324A, LM2902  
QUADRUPLE OPERATIONAL AMPLIFIERS**

SLOS066F – SEPTEMBER 1975 – REVISED JANUARY 2002

**absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>†</sup>**

|                                                                                                                                               |                         | LM124, LM124A<br>LM224, LM224A<br>LM324, LM324A | LM2902     | UNIT               |
|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|-------------------------------------------------|------------|--------------------|
| Supply voltage, $V_{CC}$ (see Note 1)                                                                                                         |                         | 32                                              | 26         | V                  |
| Differential input voltage, $V_{ID}$ (see Note 2)                                                                                             |                         | $\pm 32$                                        | $\pm 26$   | V                  |
| Input voltage, $V_I$ (either input)                                                                                                           |                         | -0.3 to 32                                      | -0.3 to 26 | V                  |
| Duration of output short circuit (one amplifier) to ground at (or below) $T_A = 25^\circ\text{C}$ ,<br>$V_{CC} \leq 15\text{ V}$ (see Note 3) |                         | Unlimited                                       | Unlimited  |                    |
| Continuous total dissipation                                                                                                                  |                         | See Dissipation Rating Table                    |            |                    |
| Package thermal impedance, $\theta_{JA}$ (see Note 4)                                                                                         | D package               | 86                                              |            | $^\circ\text{C/W}$ |
|                                                                                                                                               | DB package              | 96                                              |            |                    |
|                                                                                                                                               | N package               | 80                                              |            |                    |
|                                                                                                                                               | PW package              | 113                                             |            |                    |
| Case temperature for 60 seconds                                                                                                               | FK package              | 260                                             |            | $^\circ\text{C}$   |
| Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds                                                                                  | J or W package          | 300                                             | 300        | $^\circ\text{C}$   |
| Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds                                                                                  | D, DB, N, or PW package | 260                                             | 260        | $^\circ\text{C}$   |
| Storage temperature range, $T_{stg}$                                                                                                          |                         | -65 to 150                                      | -65 to 150 | $^\circ\text{C}$   |

<sup>†</sup> Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltage values (except differential voltages and  $V_{CC}$  specified for the measurement of  $I_{OS}$ ) are with respect to the network GND.  
2. Differential voltages are at  $IN+$  with respect to  $IN-$ .  
3. Short circuits from outputs to  $V_{CC}$  can cause excessive heating and eventual destruction.  
4. The package thermal impedance is calculated in accordance with JESD 51-7.

**DISSIPATION RATING TABLE**

| PACKAGE        | $T_A \leq 25^\circ\text{C}$<br>POWER RATING | DERATING<br>FACTOR        | DERATE<br>ABOVE $T_A$ | $T_A = 70^\circ\text{C}$<br>POWER RATING | $T_A = 85^\circ\text{C}$<br>POWER RATING | $T_A = 125^\circ\text{C}$<br>POWER RATING |
|----------------|---------------------------------------------|---------------------------|-----------------------|------------------------------------------|------------------------------------------|-------------------------------------------|
| D              | 900 mW                                      | 7.6 mW/ $^\circ\text{C}$  | 32 $^\circ\text{C}$   | 611 mW                                   | 497 mW                                   | N/A                                       |
| FK             | 900 mW                                      | 11.0 mW/ $^\circ\text{C}$ | 68 $^\circ\text{C}$   | 878 mW                                   | 713 mW                                   | 273 mW                                    |
| J (LM124_)     | 900 mW                                      | 11.0 mW/ $^\circ\text{C}$ | 68 $^\circ\text{C}$   | 878 mW                                   | 713 mW                                   | 273 mW                                    |
| J (all others) | 900 mW                                      | 8.2 mW/ $^\circ\text{C}$  | 40 $^\circ\text{C}$   | 654 mW                                   | 531 mW                                   | N/A                                       |
| W              | 900 mW                                      | 8.0 mW/ $^\circ\text{C}$  | 37 $^\circ\text{C}$   | 636 mW                                   | 516 mW                                   | 196 mW                                    |

electrical characteristics at specified free-air temperature,  $V_{CC} = 5\text{ V}$  (unless otherwise noted)

| PARAMETER                        |                                                                      | TEST CONDITIONS†                                                                                | T <sub>A</sub> ‡ | LM124, LM224              |      |      | LM324                     |      |      | LM2902                    |      |      | UNIT |
|----------------------------------|----------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|------------------|---------------------------|------|------|---------------------------|------|------|---------------------------|------|------|------|
|                                  |                                                                      |                                                                                                 |                  | MIN                       | TYP§ | MAX  | MIN                       | TYP§ | MAX  | MIN                       | TYP§ | MAX  |      |
| V <sub>IO</sub>                  | Input offset voltage                                                 | V <sub>CC</sub> = 5 V to MAX,<br>V <sub>IC</sub> = V <sub>ICRmin</sub> , V <sub>O</sub> = 1.4 V | 25°C             |                           | 3    | 5    |                           | 3    | 7    |                           | 3    | 7    | mV   |
|                                  |                                                                      |                                                                                                 | Full range       |                           |      | 7    |                           |      | 9    |                           |      | 10   |      |
| I <sub>IO</sub>                  | Input offset current                                                 | V <sub>O</sub> = 1.4 V                                                                          | 25°C             |                           | 2    | 30   |                           | 2    | 50   |                           | 2    | 50   | nA   |
|                                  |                                                                      |                                                                                                 | Full range       |                           |      | 100  |                           |      | 150  |                           |      | 300  |      |
| I <sub>IB</sub>                  | Input bias current                                                   | V <sub>O</sub> = 1.4 V                                                                          | 25°C             |                           | –20  | –150 |                           | –20  | –250 |                           | –20  | –250 | nA   |
|                                  |                                                                      |                                                                                                 | Full range       |                           |      | –300 |                           |      | –500 |                           |      | –500 |      |
| V <sub>ICR</sub>                 | Common-mode input voltage range                                      | V <sub>CC</sub> = 5 V to MAX                                                                    | 25°C             | 0 to V <sub>CC</sub> –1.5 |      |      | 0 to V <sub>CC</sub> –1.5 |      |      | 0 to V <sub>CC</sub> –1.5 |      |      | V    |
|                                  |                                                                      |                                                                                                 | Full range       | 0 to V <sub>CC</sub> –2   |      |      | 0 to V <sub>CC</sub> –2   |      |      | 0 to V <sub>CC</sub> –2   |      |      |      |
| V <sub>OH</sub>                  | High-level output voltage                                            | R <sub>L</sub> = 2 kΩ                                                                           | 25°C             | V <sub>CC</sub> –1.5      |      |      | V <sub>CC</sub> –1.5      |      |      |                           |      |      | V    |
|                                  |                                                                      | R <sub>L</sub> = 10 kΩ                                                                          | 25°C             |                           |      |      |                           |      |      | V <sub>CC</sub> –1.5      |      |      |      |
|                                  |                                                                      | V <sub>CC</sub> = MAX, R <sub>L</sub> = 2 kΩ                                                    | Full range       | 26                        |      |      | 26                        |      |      | 22                        |      |      |      |
|                                  |                                                                      | V <sub>CC</sub> = MAX, R <sub>L</sub> ≥ 10 kΩ                                                   | Full range       | 27 28                     |      |      | 27 28                     |      |      | 23 24                     |      |      |      |
| V <sub>OL</sub>                  | Low-level output voltage                                             | R <sub>L</sub> ≤ 10 kΩ                                                                          | Full range       | 5 20                      |      |      | 5 20                      |      |      | 5 20                      |      |      | mV   |
| A <sub>VD</sub>                  | Large-signal differential voltage amplification                      | V <sub>CC</sub> = 15 V, V <sub>O</sub> = 1 V to 11 V,<br>R <sub>L</sub> = ≥ 2 kΩ                | 25°C             | 50 100                    |      |      | 25 100                    |      |      | 100                       |      |      | V/mV |
|                                  |                                                                      |                                                                                                 | Full range       | 25                        |      |      | 15                        |      |      | 15                        |      |      |      |
| CMRR                             | Common-mode rejection ratio                                          | V <sub>IC</sub> = V <sub>ICRmin</sub>                                                           | 25°C             | 70 80                     |      |      | 65 80                     |      |      | 50 80                     |      |      | dB   |
| k <sub>SVR</sub>                 | Supply-voltage rejection ratio (ΔV <sub>CC</sub> /ΔV <sub>IO</sub> ) |                                                                                                 | 25°C             | 65 100                    |      |      | 65 100                    |      |      | 50 100                    |      |      | dB   |
| V <sub>O1</sub> /V <sub>O2</sub> | Crosstalk attenuation                                                | f = 1 kHz to 20 kHz                                                                             | 25°C             | 120                       |      |      | 120                       |      |      | 120                       |      |      | dB   |
| I <sub>O</sub>                   | Output current                                                       | V <sub>CC</sub> = 15 V, V <sub>ID</sub> = 1 V,<br>V <sub>O</sub> = 0                            | 25°C             | –20 –30 –60               |      |      | –20 –30 –60               |      |      | –20 –30 –60               |      |      | mA   |
|                                  |                                                                      |                                                                                                 | Full range       | –10                       |      |      | –10                       |      |      | –10                       |      |      |      |
|                                  |                                                                      | V <sub>CC</sub> = 15 V, V <sub>O</sub> = 15 V                                                   | 25°C             | 10 20                     |      |      | 10 20                     |      |      | 10 20                     |      |      |      |
|                                  |                                                                      |                                                                                                 | Full range       | 5                         |      |      | 5                         |      |      | 5                         |      |      |      |
|                                  |                                                                      | V <sub>ID</sub> = –1 V, V <sub>O</sub> = 200 mV                                                 | 25°C             | 12 30                     |      |      | 12 30                     |      |      | 30                        |      |      | μA   |
| I <sub>OS</sub>                  | Short-circuit output current                                         | V <sub>CC</sub> at 5 V, GND at –5 V, V <sub>O</sub> = 0                                         | 25°C             | ±40 ±60                   |      |      | ±40 ±60                   |      |      | ±40 ±60                   |      |      | mA   |
| I <sub>CC</sub>                  | Supply current (four amplifiers)                                     | V <sub>O</sub> = 2.5 V, No load                                                                 | Full range       | 0.7 1.2                   |      |      | 0.7 1.2                   |      |      | 0.7 1.2                   |      |      | mA   |
|                                  |                                                                      | V <sub>CC</sub> = MAX, V <sub>O</sub> = 0.5 V <sub>CC</sub> , No load                           | Full range       | 1.4 3                     |      |      | 1.4 3                     |      |      | 1.4 3                     |      |      |      |

† All characteristics are measured under open-loop conditions with zero common-mode input voltage unless otherwise specified. MAX  $V_{CC}$  for testing purposes is 26 V for LM2902, 30 V for the others.

‡ Full range is –55°C to 125°C for LM124, –25°C to 85°C for LM224, 0°C to 70°C for LM324, and –40°C to 125°C for LM2902.

§ All typical values are at  $T_A = 25^\circ\text{C}$ .

## LM124, LM124A, LM224, LM224A

## LM324, LM324A, LM2902

## QUADRUPLER OPERATIONAL AMPLIFIERS

SLOS066 – SEPTEMBER 1975 – REVISED JANUARY 2002

electrical characteristics at specified free-air temperature,  $V_{CC} = 5\text{ V}$  (unless otherwise noted)

| PARAMETER                        |                                                                      | TEST CONDITIONS†                                                                                 | T <sub>A</sub> ‡ | LM124A                    |      |      | LM224A                    |      |      | LM324A                    |      |      | UNIT |
|----------------------------------|----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|------------------|---------------------------|------|------|---------------------------|------|------|---------------------------|------|------|------|
|                                  |                                                                      |                                                                                                  |                  | MIN                       | TYP§ | MAX  | MIN                       | TYP§ | MAX  | MIN                       | TYP§ | MAX  |      |
| V <sub>IO</sub>                  | Input offset voltage                                                 | V <sub>CC</sub> = 5 V to 30 V,<br>V <sub>IC</sub> = V <sub>ICRmin</sub> , V <sub>O</sub> = 1.4 V | 25°C             |                           |      | 2    |                           | 2    | 3    |                           | 2    | 3    | mV   |
|                                  |                                                                      |                                                                                                  | Full range       |                           |      | 4    |                           |      | 4    |                           |      | 5    |      |
| I <sub>IO</sub>                  | Input offset current                                                 | V <sub>O</sub> = 1.4 V                                                                           | 25°C             |                           |      | 10   |                           |      | 2    | 15                        | 2    | 30   | nA   |
|                                  |                                                                      |                                                                                                  | Full range       |                           |      | 30   |                           |      | 30   |                           |      | 75   |      |
| I <sub>IB</sub>                  | Input bias current                                                   | V <sub>O</sub> = 1.4 V                                                                           | 25°C             |                           |      | –50  |                           | –15  | –80  |                           | –15  | –100 | nA   |
|                                  |                                                                      |                                                                                                  | Full range       |                           |      | –100 |                           |      | –100 |                           |      | –200 |      |
| V <sub>ICR</sub>                 | Common-mode input voltage range                                      | V <sub>CC</sub> = 30 V                                                                           | 25°C             | 0 to V <sub>CC</sub> –1.5 |      |      | 0 to V <sub>CC</sub> –1.5 |      |      | 0 to V <sub>CC</sub> –1.5 |      |      | V    |
|                                  |                                                                      |                                                                                                  | Full range       | 0 to V <sub>CC</sub> –2   |      |      | 0 to V <sub>CC</sub> –2   |      |      | 0 to V <sub>CC</sub> –2   |      |      |      |
| V <sub>OH</sub>                  | High-level output voltage                                            | R <sub>L</sub> = 2 kΩ                                                                            | 25°C             | V <sub>CC</sub> –1.5      |      |      | V <sub>CC</sub> –1.5      |      |      | V <sub>CC</sub> –1.5      |      |      | V    |
|                                  |                                                                      | V <sub>CC</sub> = 30 V, R <sub>L</sub> = 2 kΩ                                                    | Full range       | 26                        |      |      | 26                        |      |      | 26                        |      |      |      |
|                                  |                                                                      | V <sub>CC</sub> = 30 V, R <sub>L</sub> ≥ 10 kΩ                                                   | Full range       | 27                        |      |      | 27                        | 28   |      | 27                        | 28   |      |      |
| V <sub>OL</sub>                  | Low-level output voltage                                             | R <sub>L</sub> ≤ 10 kΩ                                                                           | Full range       | 20                        |      |      | 5                         | 20   |      | 5                         | 20   | mV   |      |
| A <sub>VD</sub>                  | Large-signal differential voltage amplification                      | V <sub>CC</sub> = 15 V, V <sub>O</sub> = 1 V to 11 V, R <sub>L</sub> = ≥ 2 kΩ                    | Full range       | 25                        |      |      | 25                        |      |      | 15                        |      |      | V/mV |
| CMRR                             | Common-mode rejection ratio                                          | V <sub>IC</sub> = V <sub>ICRmin</sub>                                                            | 25°C             | 70                        |      |      | 70                        | 80   |      | 65                        | 80   | dB   |      |
| k <sub>SVR</sub>                 | Supply-voltage rejection ratio (ΔV <sub>CC</sub> /ΔV <sub>IO</sub> ) |                                                                                                  | 25°C             | 65                        |      |      | 65                        | 100  |      | 65                        | 100  | dB   |      |
| V <sub>O1</sub> /V <sub>O2</sub> | Crosstalk attenuation                                                | f = 1 kHz to 20 kHz                                                                              | 25°C             | 120                       |      |      | 120                       |      |      | 120                       |      |      | dB   |
| I <sub>O</sub>                   | Output current                                                       | V <sub>CC</sub> = 15 V, V <sub>ID</sub> = 1 V, V <sub>O</sub> = 0                                | 25°C             | –20                       |      |      | –20                       | –30  | –60  | –20                       | –30  | –60  | mA   |
|                                  |                                                                      |                                                                                                  | Full range       | –10                       |      |      | –10                       |      |      | –10                       |      |      |      |
|                                  |                                                                      | V <sub>CC</sub> = 15 V, V <sub>O</sub> = 15 V                                                    | 25°C             | 10                        |      |      | 10                        | 20   |      | 10                        | 20   |      |      |
|                                  |                                                                      |                                                                                                  | Full range       | 5                         |      |      | 5                         |      |      | 5                         |      |      |      |
|                                  |                                                                      | V <sub>ID</sub> = –1 V, V <sub>O</sub> = 200 mV                                                  | 25°C             | 12                        |      |      | 12                        | 30   |      | 12                        | 30   |      | μA   |
| I <sub>OS</sub>                  | Short-circuit output current                                         | V <sub>CC</sub> at 5 V, V <sub>O</sub> = 0 GND at –5 V,                                          | 25°C             | ±40 ±60                   |      |      | ±40 ±60                   |      |      | ±40 ±60                   |      |      | mA   |
| I <sub>CC</sub>                  | Supply current (four amplifiers)                                     | V <sub>O</sub> = 2.5 V, No load                                                                  | Full range       | 0.7 1.2                   |      |      | 0.7 1.2                   |      |      | 0.7 1.2                   |      |      | mA   |
|                                  |                                                                      | V <sub>CC</sub> = 30 V, V <sub>O</sub> = 15 V, No load                                           | Full range       | 1.4 3                     |      |      | 1.4 3                     |      |      | 1.4 3                     |      |      |      |

† All characteristics are measured under open-loop conditions with zero common-mode input voltage unless otherwise specified.

‡ Full range is –55°C to 125°C for LM124A, –25°C to 85°C for LM224A, and 0°C to 70°C for LM324A.

§ All typical values are at  $T_A = 25^\circ\text{C}$ .

## **IMPORTANT NOTICE**

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Mailing Address:

Texas Instruments  
Post Office Box 655303  
Dallas, Texas 75265