

## ADC088S022 8-Channel, 50 kps to 200 kps, 8-Bit A/D Converter

Check for Samples: [ADC088S022](#)

### FEATURES

- Eight Input Channels
- Variable Power Management
- Independent Analog and Digital Supplies
- SPI™/ QSPI™/MICROWIRE/DSP Compatible
- Packaged in 16-Lead TSSOP

### APPLICATIONS

- Automotive Navigation
- Portable Systems
- Medical Instruments
- Mobile Communications
- Instrumentation and Control Systems

### KEY SPECIFICATIONS

- Conversion Rate: 50 kps to 200 kps
- DNL ( $V_A = V_D = 2.7V$  to  $5.25V$ ):  $\pm 0.2$  LSB (Max)
- INL ( $V_A = V_D = 2.7V$  to  $5.25V$ ):  $\pm 0.2$  LSB (Max)
- Power Consumption
  - 3V Supply: 0.9 mW (Typ)
  - 5V Supply: 5.5 mW (Typ)

### DESCRIPTION


The ADC088S022 is a low-power, eight-channel CMOS 8-bit analog-to-digital converter specified for conversion throughput rates of 50 kps to 200 kps. The converter is based on a successive-approximation register architecture with an internal track-and-hold circuit. It can be configured to accept up to eight input signals at inputs IN0 through IN7.

The output serial data is straight binary and is compatible with several standards, such as SPI™, QSPI™, MICROWIRE, and many common DSP serial interfaces.

The ADC088S022 may be operated with independent analog and digital supplies. The analog supply ( $V_A$ ) can range from +2.7V to +5.25V, and the digital supply ( $V_D$ ) can range from +2.7V to  $V_A$ . Normal power consumption using a +3V or +5V supply is 0.9 mW and 5.5 mW, respectively. The power-down feature reduces the power consumption to 0.03  $\mu W$  using a +3V supply and 0.15  $\mu W$  using a +5V supply.

The ADC088S022 is packaged in a 16-lead TSSOP package. Operation over the extended industrial temperature range of  $-40^{\circ}C$  to  $+105^{\circ}C$  is ensured.

### Connection Diagram




Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

SPI, QSPI are trademarks of Motorola, Inc..

All other trademarks are the property of their respective owners.

## Block Diagram



## PIN DESCRIPTIONS

| Pin No.             | Symbol          | Description                                                                                                                                                                                                                                                           |
|---------------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>ANALOG I/O</b>   |                 |                                                                                                                                                                                                                                                                       |
| 4 - 11              | IN0 to IN7      | Analog inputs. These signals can range from 0V to V <sub>REF</sub> .                                                                                                                                                                                                  |
| <b>DIGITAL I/O</b>  |                 |                                                                                                                                                                                                                                                                       |
| 16                  | SCLK            | Digital clock input. The specified performance range of frequencies for this input is 0.8 MHz to 3.2 MHz. This clock directly controls the conversion and readout processes.                                                                                          |
| 15                  | DOUT            | Digital data output. The output samples are clocked out of this pin on the falling edges of the SCLK pin.                                                                                                                                                             |
| 14                  | DIN             | Digital data input. The ADC088S022's Control Register is loaded through this pin on rising edges of the SCLK pin.                                                                                                                                                     |
| 1                   | $\overline{CS}$ | Chip select. On the falling edge of $\overline{CS}$ , a conversion process begins. Conversions continue as long as $\overline{CS}$ is held low.                                                                                                                       |
| <b>POWER SUPPLY</b> |                 |                                                                                                                                                                                                                                                                       |
| 2                   | V <sub>A</sub>  | Positive analog supply pin. This voltage is also used as the reference voltage. This pin should be connected to a quiet +2.7V to +5.25V source and bypassed to GND with 1 $\mu$ F and 0.1 $\mu$ F monolithic ceramic capacitors located within 1 cm of the power pin. |
| 13                  | V <sub>D</sub>  | Positive digital supply pin. This pin should be connected to a +2.7V to V <sub>A</sub> supply, and bypassed to GND with a 0.1 $\mu$ F monolithic ceramic capacitor located within 1 cm of the power pin.                                                              |
| 3                   | AGND            | The ground return for the analog supply and signals.                                                                                                                                                                                                                  |
| 12                  | DGND            | The ground return for the digital supply and signals.                                                                                                                                                                                                                 |



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

## Absolute Maximum Ratings<sup>(1)(2)(3)</sup>

|                                               |                  |                                  |
|-----------------------------------------------|------------------|----------------------------------|
| Analog Supply Voltage $V_A$                   |                  | -0.3V to 6.5V                    |
| Digital Supply Voltage $V_D$                  |                  | -0.3V to $V_A + 0.3V$ , max 6.5V |
| Voltage on Any Pin to GND                     |                  | -0.3V to $V_A + 0.3V$            |
| Input Current at Any Pin <sup>(4)</sup>       |                  | ±10 mA                           |
| Package Input Current <sup>(4)</sup>          |                  | ±20 mA                           |
| Power Dissipation at $T_A = 25^\circ\text{C}$ |                  | See <sup>(5)</sup>               |
| ESD Susceptibility <sup>(6)</sup>             | Human Body Model | 2500V                            |
|                                               | Machine Model    | 250V                             |
| Junction Temperature                          |                  | +150°C                           |
| Storage Temperature                           |                  | -65°C to +150°C                  |

- (1) Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is functional, but do not ensure specific performance limits. For ensured specifications and test conditions, see the [Electrical Characteristics](#). The specified specifications apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed test conditions.
- (2) If Military/Aerospace specified devices are required, please contact the Texas Instruments Sales Office/Distributors for availability and specifications.
- (3) For soldering specifications, see <http://www.ti.com/lit/SNOA549>
- (4) When the input voltage at any pin exceeds the power supplies (that is,  $V_{IN} < \text{AGND}$  or  $V_{IN} > V_A$  or  $V_D$ ), the current at that pin should be limited to 10 mA. The 20 mA maximum package input current rating limits the number of pins that can safely exceed the power supplies with an input current of 10 mA to two.
- (5) The absolute maximum junction temperature ( $T_{Jmax}$ ) for this device is 150°C. The maximum allowable power dissipation is dictated by  $T_{Jmax}$ , the junction-to-ambient thermal resistance ( $\theta_{JA}$ ), and the ambient temperature ( $T_A$ ), and can be calculated using the formula  $P_{DMAX} = (T_{Jmax} - T_A)/\theta_{JA}$ . In the 16-pin TSSOP,  $\theta_{JA}$  is 96°C/W, so  $P_{DMAX} = 1,200$  mW at 25°C and 625 mW at the maximum operating ambient temperature of 105°C. Note that the power consumption of this device under normal operation is a maximum of 12 mW. The values for maximum power dissipation listed above will be reached only when the ADC088S022 is operated in a severe fault condition (e.g. when input or output pins are driven beyond the power supply voltages, or the power supply polarity is reversed). Obviously, such conditions should always be avoided.
- (6) Human body model is 100 pF capacitor discharged through a 1.5 kΩ resistor. Machine model is 220 pF discharged through ZERO ohms

## Operating Ratings<sup>(1)(2)</sup>

|                       |                        |
|-----------------------|------------------------|
| Operating Temperature | -40°C ≤ $T_A$ ≤ +105°C |
| $V_A$ Supply Voltage  | +2.7V to +5.25V        |
| $V_D$ Supply Voltage  | +2.7V to $V_A$         |
| Digital Input Voltage | 0V to $V_A$            |
| Analog Input Voltage  | 0V to $V_A$            |
| Clock Frequency       | 50 MHz to 16 MHz       |

- (1) Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is functional, but do not ensure specific performance limits. For ensured specifications and test conditions, see the [Electrical Characteristics](#). The specified specifications apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed test conditions.
- (2) All voltages are measured with respect to GND = 0V, unless otherwise specified.

## Package Thermal Resistance

| Package                             | $\theta_{JA}$ |
|-------------------------------------|---------------|
| 16-lead TSSOP on 4-layer, 2 oz. PCB | 96°C / W      |

## ADC088S022 Converter Electrical Characteristics<sup>(1)</sup>

The following specifications apply for  $V_A = V_D = +2.7V$  to  $+5.25V$ ,  $AGND = DGND = 0V$ ,  $f_{SCLK} = 0.8\text{ MHz}$  to  $3.2\text{ MHz}$ ,  $f_{SAMPLE} = 50\text{ kps}$  to  $200\text{ kps}$ , and  $C_L = 50\text{ pF}$ , unless otherwise noted. **Boldface limits apply for  $T_A = T_{MIN}$  to  $T_{MAX}$** ; all other limits  $T_A = 25^\circ\text{C}$ .

| Symbol                              | Parameter                                      | Conditions                                           | Typical                   | Limits <sup>(2)</sup> | Units      |
|-------------------------------------|------------------------------------------------|------------------------------------------------------|---------------------------|-----------------------|------------|
| STATIC CONVERTER CHARACTERISTICS    |                                                |                                                      |                           |                       |            |
|                                     | Resolution with No Missing Codes               |                                                      |                           | 8                     | Bits       |
| INL                                 | Integral Non-Linearity (End Point Method)      |                                                      | ±0.04                     | ±0.2                  | LSB (max)  |
| DNL                                 | Differential Non-Linearity                     |                                                      | ±0.04                     | ±0.2                  | LSB (max)  |
| V <sub>OFF</sub>                    | Offset Error                                   |                                                      | +0.6                      | ±0.7                  | LSB (max)  |
| OEM                                 | Offset Error Match                             |                                                      | ±0.02                     | ±0.2                  | LSB (max)  |
| FSE                                 | Full Scale Error                               |                                                      | +0.5                      | ±0.6                  | LSB (max)  |
| FSEM                                | Full Scale Error Match                         |                                                      | ±0.02                     | ±0.2                  | LSB (max)  |
| DYNAMIC CONVERTER CHARACTERISTICS   |                                                |                                                      |                           |                       |            |
| FPBW                                | Full Power Bandwidth (−3dB)                    |                                                      | 8                         |                       | MHz        |
| SINAD                               | Signal-to-Noise Plus Distortion Ratio          | f <sub>IN</sub> = 39.9 kHz, −0.02 dBFS               | 49.5                      | 49.2                  | dB (min)   |
| SNR                                 | Signal-to-Noise Ratio                          | f <sub>IN</sub> = 39.9 kHz, −0.02 dBFS               | 49.5                      | 49.2                  | dB (min)   |
| THD                                 | Total Harmonic Distortion                      | f <sub>IN</sub> = 39.9 kHz, −0.02 dBFS               | −70.1                     | −56.8                 | dB (max)   |
| SFDR                                | Spurious-Free Dynamic Range                    | f <sub>IN</sub> = 39.9 kHz, −0.02 dBFS               | 67.7                      | 64.2                  | dB (min)   |
| ENOB                                | Effective Number of Bits                       | f <sub>IN</sub> = 39.9 kHz                           | 7.93                      | 7.88                  | Bits (min) |
| ISO                                 | Channel-to-Channel Isolation                   | f <sub>IN</sub> = 20 kHz                             | 65.3                      |                       | dB         |
| IMD                                 | Intermodulation Distortion, Second Order Terms | f <sub>a</sub> = 19.5 kHz, f <sub>b</sub> = 20.5 kHz | −75.0                     |                       | dB         |
|                                     | Intermodulation Distortion, Third Order Terms  | f <sub>a</sub> = 19.5 kHz, f <sub>b</sub> = 20.5 kHz | −71.9                     |                       | dB         |
| ANALOG INPUT CHARACTERISTICS        |                                                |                                                      |                           |                       |            |
| V <sub>IN</sub>                     | Input Range                                    |                                                      | 0 to V <sub>A</sub>       |                       | V          |
| I <sub>DCL</sub>                    | DC Leakage Current                             |                                                      |                           | ±1                    | μA (max)   |
| C <sub>INA</sub>                    | Input Capacitance                              | Track Mode                                           | 33                        |                       | pF         |
|                                     |                                                | Hold Mode                                            | 3                         |                       | pF         |
| DIGITAL INPUT CHARACTERISTICS       |                                                |                                                      |                           |                       |            |
| V <sub>IH</sub>                     | Input High Voltage                             | V <sub>A</sub> = V <sub>D</sub> = +2.7V to +3.6V     |                           | 2.1                   | V (min)    |
|                                     |                                                | V <sub>A</sub> = V <sub>D</sub> = +4.75V to +5.25V   |                           | 2.4                   | V (min)    |
| V <sub>IL</sub>                     | Input Low Voltage                              |                                                      |                           | 0.8                   | V (max)    |
| I <sub>IN</sub>                     | Input Current                                  | V <sub>IN</sub> = 0V or V <sub>D</sub>               | ±0.01                     | ±1                    | μA (max)   |
| C <sub>IND</sub>                    | Digital Input Capacitance                      |                                                      | 2                         | 4                     | pF (max)   |
| DIGITAL OUTPUT CHARACTERISTICS      |                                                |                                                      |                           |                       |            |
| V <sub>OH</sub>                     | Output High Voltage                            | I <sub>SOURCE</sub> = 200 μA,                        |                           | V <sub>D</sub> − 0.5  | V (min)    |
| V <sub>OL</sub>                     | Output Low Voltage                             | I <sub>SINK</sub> = 200 μA to 1.0 mA,                |                           | 0.4                   | V (max)    |
| I <sub>OZH</sub> , I <sub>OZL</sub> | Hi-Impedance Output Leakage Current            |                                                      |                           | ±1                    | μA (max)   |
| C <sub>OUT</sub>                    | Hi-Impedance Output Capacitance <sup>(1)</sup> |                                                      | 2                         | 4                     | pF (max)   |
|                                     | Output Coding                                  |                                                      | Straight (Natural) Binary |                       |            |

(1) Data sheet min/max specification limits are ensured by design, test, or statistical analysis.

(2) Tested limits are ensured to AOQL (Average Outgoing Quality Level).

## ADC088S022 Converter Electrical Characteristics<sup>(1)</sup> (continued)

The following specifications apply for  $V_A = V_D = +2.7V$  to  $+5.25V$ ,  $AGND = DGND = 0V$ ,  $f_{SCLK} = 0.8$  MHz to  $3.2$  MHz,  $f_{SAMPLE} = 50$  kps to  $200$  kps, and  $C_L = 50pF$ , unless otherwise noted. **Boldface limits apply for  $T_A = T_{MIN}$  to  $T_{MAX}$** ; all other limits  $T_A = 25^\circ C$ .

| Symbol                                                | Parameter                                    | Conditions                                                                                                   | Typical | Limits <sup>(2)</sup> | Units       |
|-------------------------------------------------------|----------------------------------------------|--------------------------------------------------------------------------------------------------------------|---------|-----------------------|-------------|
| POWER SUPPLY CHARACTERISTICS (C <sub>L</sub> = 10 pF) |                                              |                                                                                                              |         |                       |             |
| V <sub>A</sub> , V <sub>D</sub>                       | Analog and Digital Supply Voltages           | V <sub>A</sub> ≥ V <sub>D</sub>                                                                              |         | 2.7                   | V (min)     |
|                                                       |                                              |                                                                                                              |         | 5.25                  | V (max)     |
| I <sub>A</sub> + I <sub>D</sub>                       | Total Supply Current Normal Mode (CS low)    | V <sub>A</sub> = V <sub>D</sub> = +2.7V to +3.6V, f <sub>SAMPLE</sub> = 200 kSPS, f <sub>IN</sub> = 40 kHz   | 0.3     | 0.74                  | mA (max)    |
|                                                       |                                              | V <sub>A</sub> = V <sub>D</sub> = +4.75V to +5.25V, f <sub>SAMPLE</sub> = 200 kSPS, f <sub>IN</sub> = 40 kHz | 1.1     | 1.55                  | mA (max)    |
|                                                       | Total Supply Current Shutdown Mode (CS high) | V <sub>A</sub> = V <sub>D</sub> = +2.7V to +3.6V, f <sub>SCLK</sub> = 0 ksp/s                                | 10      |                       | nA          |
|                                                       |                                              | V <sub>A</sub> = V <sub>D</sub> = +4.75V to +5.25V, f <sub>SCLK</sub> = 0 ksp/s                              | 30      |                       | nA          |
| P <sub>C</sub>                                        | Power Consumption Normal Mode (CS low)       | V <sub>A</sub> = V <sub>D</sub> = +3.0V, f <sub>SAMPLE</sub> = 200 kSPS, f <sub>IN</sub> = 40 kHz            | 0.9     | 2.2                   | mW (max)    |
|                                                       |                                              | V <sub>A</sub> = V <sub>D</sub> = +5.0V, f <sub>SAMPLE</sub> = 200 kSPS, f <sub>IN</sub> = 40 kHz            | 5.5     | 7.8                   | mW (max)    |
|                                                       | Power Consumption Shutdown Mode (CS high)    | V <sub>A</sub> = V <sub>D</sub> = +3.0V, f <sub>SCLK</sub> = 0 ksp/s                                         | 0.03    |                       | μW          |
|                                                       |                                              | V <sub>A</sub> = V <sub>D</sub> = +5.0V, f <sub>SCLK</sub> = 0 ksp/s                                         | 0.15    |                       | μW          |
| AC ELECTRICAL CHARACTERISTICS                         |                                              |                                                                                                              |         |                       |             |
| f <sub>SCLKMIN</sub>                                  | Minimum Clock Frequency                      |                                                                                                              |         | 0.8                   | MHz (min)   |
| f <sub>SCLK</sub>                                     | Maximum Clock Frequency                      |                                                                                                              | 16      | 3.2                   | MHz (max)   |
| f <sub>S</sub>                                        | Sample Rate Continuous Mode                  |                                                                                                              |         | 50                    | ksp/s (min) |
|                                                       |                                              | 1000                                                                                                         | 200     | ksp/s (max)           |             |
| t <sub>CONVERT</sub>                                  | Conversion (Hold) Time                       |                                                                                                              |         | 13                    | SCLK cycles |
| DC                                                    | SCLK Duty Cycle                              |                                                                                                              | 30      | 40                    | % (min)     |
|                                                       |                                              |                                                                                                              | 70      | 60                    | % (max)     |
| t <sub>ACQ</sub>                                      | Acquisition (Track) Time                     |                                                                                                              |         | 3                     | SCLK cycles |
|                                                       | Throughput Time                              | Acquisition Time + Conversion Time                                                                           |         | 16                    | SCLK cycles |
| t <sub>AD</sub>                                       | Aperture Delay                               |                                                                                                              | 4       |                       | ns          |

## ADC088S022 Timing Specifications

The following specifications apply for  $V_A = V_D = +2.7V$  to  $5.25V$ ,  $AGND = DGND = 0V$ ,  $f_{SCLK} = 0.8$  MHz to  $3.2$  MHz,  $f_{SAMPLE} = 50$  kps to  $200$  kps, and  $C_L = 50pF$ . **Boldface limits apply for  $T_A = T_{MIN}$  to  $T_{MAX}$** ; all other limits  $T_A = 25^\circ C$ .

| Symbol     | Parameter                                            | Conditions   | Typical | Limits <sup>(1)</sup>                   | Units    |
|------------|------------------------------------------------------|--------------|---------|-----------------------------------------|----------|
| $t_{CSH}$  | $\overline{CS}$ Hold Time after SCLK Rising Edge     |              | 0       | <b>10</b>                               | ns (min) |
| $t_{CSS}$  | $\overline{CS}$ Setup Time prior to SCLK Rising Edge |              | 5       | <b>10</b>                               | ns (min) |
| $t_{EN}$   | $\overline{CS}$ Falling Edge to DOUT enabled         |              | 5       | <b>30</b>                               | ns (max) |
| $t_{DACC}$ | DOUT Access Time after SCLK Falling Edge             |              | 17      | <b>27</b>                               | ns (max) |
| $t_{DHLD}$ | DOUT Hold Time after SCLK Falling Edge               |              | 4       |                                         | ns (typ) |
| $t_{DS}$   | DIN Setup Time prior to SCLK Rising Edge             |              | 3       | <b>10</b>                               | ns (min) |
| $t_{DH}$   | DIN Hold Time after SCLK Rising Edge                 |              | 3       | <b>10</b>                               | ns (min) |
| $t_{CH}$   | SCLK High Time                                       |              |         | <b><math>0.4 \times t_{SCLK}</math></b> | ns (min) |
| $t_{CL}$   | SCLK Low Time                                        |              |         | <b><math>0.4 \times t_{SCLK}</math></b> | ns (min) |
| $t_{DIS}$  | $\overline{CS}$ Rising Edge to DOUT High-Impedance   | DOUT falling | 2.4     | <b>20</b>                               | ns (max) |
|            |                                                      | DOUT rising  | 0.9     | <b>20</b>                               | ns (max) |

(1) Tested limits are ensured to AOQL (Average Outgoing Quality Level).

## Timing Diagrams




Figure 1. ADC088S022 Operational Timing Diagram




Figure 2. ADC088S022 Serial Timing Diagram




Figure 3. SCLK and  $\overline{CS}$  Timing Parameters

## Specification Definitions

**ACQUISITION TIME** is the time required for the ADC to acquire the input voltage. During this time, the hold capacitor is charged by the input voltage.

**APERTURE DELAY** is the time between the fourth falling edge of SCLK and the time when the input signal is internally acquired or held for conversion.

**CONVERSION TIME** is the time required, after the input voltage is acquired, for the ADC to convert the input voltage to a digital word.

**CHANNEL-TO-CHANNEL ISOLATION** is resistance to coupling of energy from one channel into another channel.

**CROSSTALK** is the coupling of energy from one channel into another channel. This is similar to Channel-to-Channel Isolation, except for the sign of the data.

**DIFFERENTIAL NON-LINEARITY (DNL)** is the measure of the maximum deviation from the ideal step size of 1 LSB.

**DUTY CYCLE** is the ratio of the time that a repetitive digital waveform is high to the total time of one period. The specification here refers to the SCLK.

**EFFECTIVE NUMBER OF BITS (ENOB, or EFFECTIVE BITS)** is another method of specifying Signal-to-Noise and Distortion or SINAD. ENOB is defined as  $(\text{SINAD} - 1.76) / 6.02$  and says that the converter is equivalent to a perfect ADC of this (ENOB) number of bits.

**FULL POWER BANDWIDTH** is a measure of the frequency at which the reconstructed output fundamental drops 3 dB below its low frequency value for a full scale input.

**FULL SCALE ERROR (FSE)** is a measure of how far the last code transition is from the ideal  $1\frac{1}{2}$  LSB below  $V_{\text{REF}}^+$  and is defined as:

$$V_{\text{FSE}} = V_{\text{max}} + 1.5 \text{ LSB} - V_{\text{REF}}^+ \quad (1)$$

where  $V_{\text{max}}$  is the voltage at which the transition to the maximum code occurs. FSE can be expressed in Volts, LSB or percent of full scale range.

**GAIN ERROR** is the deviation of the last code transition (111...110) to (111...111) from the ideal ( $V_{\text{REF}} - 1.5$  LSB), after adjusting for offset error.

**INTEGRAL NON-LINEARITY (INL)** is a measure of the deviation of each individual code from a line drawn from negative full scale ( $\frac{1}{2}$  LSB below the first code transition) through positive full scale ( $\frac{1}{2}$  LSB above the last code transition). The deviation of any given code from this straight line is measured from the center of that code value.

**INTERMODULATION DISTORTION (IMD)** is the creation of additional spectral components as a result of two sinusoidal frequencies being applied to an individual ADC input at the same time. It is defined as the ratio of the power in both the second or the third order intermodulation products to the power in one of the original frequencies. Second order products are  $f_a \pm f_b$ , where  $f_a$  and  $f_b$  are the two sine wave input frequencies. Third order products are  $(2f_a \pm f_b)$  and  $(f_a \pm 2f_b)$ . IMD is usually expressed in dB.

**MISSING CODES** are those output codes that will never appear at the ADC outputs. These codes cannot be reached with any input value. The ADC088S022 is ensured not to have any missing codes.

**OFFSET ERROR** is the deviation of the first code transition (000...000) to (000...001) from the ideal (i.e. GND + 0.5 LSB).

**SIGNAL TO NOISE RATIO (SNR)** is the ratio, expressed in dB, of the rms value of the input signal to the rms value of the sum of all other spectral components below one-half the sampling frequency, not including harmonics or d.c.

**SIGNAL TO NOISE PLUS DISTORTION (S/N+D or SINAD)** Is the ratio, expressed in dB, of the rms value of the input signal to the rms value of all of the other spectral components below half the clock frequency, including harmonics but excluding d.c.

**SPURIOUS FREE DYNAMIC RANGE (SFDR)** is the difference, expressed in dB, between the rms values of the input signal and the peak spurious signal where a spurious signal is any signal present in the output spectrum that is not present at the input, including harmonics but excluding d.c.

**TOTAL HARMONIC DISTORTION (THD)** is the ratio, expressed in dBc, of the rms total of the first five harmonic components at the output to the rms level of the input signal frequency as seen at the output. THD is calculated as

$$\text{THD} = 20 \cdot \log_{10} \sqrt{\frac{A_{f2}^2 + \dots + A_{f6}^2}{A_{f1}^2}} \quad (2)$$

where  $A_{f1}$  is the RMS power of the input frequency at the output and  $A_{f2}$  through  $A_{f6}$  are the RMS power in the first 5 harmonic frequencies.

**THROUGHPUT TIME** is the minimum time required between the start of two successive conversions. It is the acquisition time plus the conversion and read out times. In the case of the ADC088S022, this is 16 SCLK periods.

## Typical Performance Characteristics

$V_A = V_D = +5.0\text{V}$ ,  $T_A = +25^\circ\text{C}$ ,  $f_{\text{SAMPLE}} = 200\text{ kpsps}$ ,  $f_{\text{SCLK}} = 3.2\text{ MHz}$ ,  $f_{\text{IN}} = 39.9\text{ kHz}$  unless otherwise stated.




Figure 4.




Figure 5.




Figure 6.




Figure 7.




Figure 8.




Figure 9.

## Typical Performance Characteristics (continued)

$V_A = V_D = +5.0\text{V}$ ,  $T_A = +25^\circ\text{C}$ ,  $f_{\text{SAMPLE}} = 200\text{ kps}$ ,  $f_{\text{SCLK}} = 3.2\text{ MHz}$ ,  $f_{\text{IN}} = 39.9\text{ kHz}$  unless otherwise stated.




Figure 10.




Figure 11.




Figure 12.




Figure 13.




Figure 14.




Figure 15.

### Typical Performance Characteristics (continued)

$V_A = V_D = +5.0V$ ,  $T_A = +25^\circ C$ ,  $f_{SAMPLE} = 200$  ksp/s,  $f_{SCLK} = 3.2$  MHz,  $f_{IN} = 39.9$  kHz unless otherwise stated.




Figure 16.




Figure 17.




Figure 18.




Figure 19.




Figure 20.




Figure 21.

### Typical Performance Characteristics (continued)

$V_A = V_D = +5.0V$ ,  $T_A = +25^\circ C$ ,  $f_{SAMPLE} = 200$  kps,  $f_{SCLK} = 3.2$  MHz,  $f_{IN} = 39.9$  kHz unless otherwise stated.




Figure 22.




Figure 23.




Figure 24.




Figure 25.




Figure 26.




Figure 27.

### Typical Performance Characteristics (continued)

$V_A = V_D = +5.0V$ ,  $T_A = +25^\circ C$ ,  $f_{SAMPLE} = 200$  ksp/s,  $f_{SCLK} = 3.2$  MHz,  $f_{IN} = 39.9$  kHz unless otherwise stated.




Figure 28.




Figure 29.




Figure 30.




Figure 31.




Figure 32.




Figure 33.


## Functional Description

The ADC08S022 is a successive-approximation analog-to-digital converter designed around a charge-redistribution digital-to-analog converter.


## ADC088S022 OPERATION

Simplified schematics of the ADC088S022 in both track and hold operation are shown in [Figure 34](#) and [Figure 35](#) respectively. In [Figure 34](#), the ADC088S022 is in track mode: switch SW1 connects the sampling capacitor to one of eight analog input channels through the multiplexer, and SW2 balances the comparator inputs. The ADC088S022 is in this state for the first three SCLK cycles after  $\overline{\text{CS}}$  is brought low.

**Figure 35** shows the ADC088S022 in hold mode: switch SW1 connects the sampling capacitor to ground, maintaining the sampled voltage, and switch SW2 unbalances the comparator. The control logic then instructs the charge-redistribution DAC to add or subtract fixed amounts of charge to or from the sampling capacitor until the comparator is balanced. When the comparator is balanced, the digital word supplied to the DAC is the digital representation of the analog input voltage. The ADC088S022 is in this state for the last thirteen SCLK cycles after  $\overline{\text{CS}}$  is brought low.



### Figure 34. ADC088S022 in Track Mode



### Figure 35. ADC088S022 in Hold Mode

## SERIAL INTERFACE

An operational timing diagram and a serial interface timing diagram for the ADC088S022 are shown in [Timing Diagrams](#). CS, chip select, initiates conversions and frames the serial data transfers. SCLK (serial clock) controls both the conversion process and the timing of serial data. DOUT is the serial data output pin, where a conversion result is sent as a serial data stream, MSB first. Data to be written to the ADC088S022's Control Register is placed on DIN, the serial data input pin. New data is written to DIN with each conversion.

A serial frame is initiated on the falling edge of  $\overline{\text{CS}}$  and ends on the rising edge of  $\overline{\text{CS}}$ . Each frame must contain an integer multiple of 16 rising SCLK edges. The ADC's DOUT pin is in a high impedance state when  $\overline{\text{CS}}$  is high and is active when  $\overline{\text{CS}}$  is low. Thus,  $\overline{\text{CS}}$  acts as an output enable. Similarly, SCLK is internally gated off when  $\overline{\text{CS}}$  is brought high.

During the first 3 cycles of SCLK, the ADC is in the track mode, acquiring the input voltage. For the next 13 SCLK cycles the conversion is accomplished and the data is clocked out. SCLK falling edges 1 through 4 clock out leading zeros, falling edges 5 through 12 clock out the conversion result, MSB first, and falling edges 13 through 16 clock out trailing zeros. If there is more than one conversion in a frame (continuous conversion mode), the ADC will re-enter the track mode on the falling edge of SCLK after the N\*16th rising edge of SCLK and re-enter the hold/convert mode on the N\*16+4th falling edge of SCLK. "N" is an integer value.

The ADC088S022 enters track mode under three different conditions. In [Figure 1](#),  $\overline{CS}$  goes low with SCLK high and the ADC enters track mode on the first falling edge of SCLK. In the second condition,  $\overline{CS}$  goes low with SCLK low. Under this condition, the ADC automatically enters track mode and the falling edge of  $\overline{CS}$  is seen as the first falling edge of SCLK. In the third condition,  $\overline{CS}$  and SCLK go low simultaneously and the ADC enters track mode. While there is no timing restriction with respect to the rising edges of  $\overline{CS}$  and SCLK, see [Figure 3](#) for setup and hold time requirements for the falling edge of  $\overline{CS}$  with respect to the rising edge of SCLK.

While a conversion is in progress, the address of the next input for conversion is clocked into a control register through the DIN pin on the first 8 rising edges of SCLK after the fall of  $\overline{CS}$ . See [Table 1](#), [Table 2](#), and [Table 3](#).

There is no need to incorporate a power-up delay or dummy conversion as the ADC088S022 is able to acquire the input signal to full resolution in the first conversion immediately following power-up. The first conversion result after power-up will be that of IN0.

**Table 1. Control Register Bits**

| Bit 7 (MSB) | Bit 6 | Bit 5 | Bit 4 | Bit 3 | Bit 2 | Bit 1 | Bit 0 |
|-------------|-------|-------|-------|-------|-------|-------|-------|
| DONTC       | DONTC | ADD2  | ADD1  | ADD0  | DONTC | DONTC | DONTC |

**Table 2. Control Register Bit Descriptions**

| Bit #:        | Symbol: | Description                                                                                                                                                                             |
|---------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7, 6, 2, 1, 0 | DONTC   | Don't care. The values of these bits do not affect the device.                                                                                                                          |
| 5             | ADD2    | These three bits determine which input channel will be sampled and converted at the next conversion cycle. The mapping between codes and channels is shown in <a href="#">Table 3</a> . |
| 4             | ADD1    |                                                                                                                                                                                         |
| 3             | ADD0    |                                                                                                                                                                                         |

**Table 3. Input Channel Selection**

| ADD2 | ADD1 | ADD0 | Input Channel |
|------|------|------|---------------|
| 0    | 0    | 0    | IN0 (Default) |
| 0    | 0    | 1    | IN1           |
| 0    | 1    | 0    | IN2           |
| 0    | 1    | 1    | IN3           |
| 1    | 0    | 0    | IN4           |
| 1    | 0    | 1    | IN5           |
| 1    | 1    | 0    | IN6           |
| 1    | 1    | 1    | IN7           |

## ADC088S022 TRANSFER FUNCTION

The output format of the ADC088S022 is straight binary. Code transitions occur midway between successive integer LSB values. The LSB width for the ADC088S022 is  $V_A / 256$ . The ideal transfer characteristic is shown in Figure 36. The transition from an output code of 0000 0000 to a code of 0000 0001 is at  $1/2$  LSB, or a voltage of  $V_A / 512$ . Other code transitions occur at steps of one LSB.




Figure 36. Ideal Transfer Characteristic

## ANALOG INPUTS

An equivalent circuit for one of the ADC088S022's input channels is shown in Figure 37. Diodes D1 and D2 provide ESD protection for the analog inputs. The operating range for the analog inputs is 0V to  $V_A$ . Going beyond this range will cause the ESD diodes to conduct and result in erratic operation.

The capacitor C1 in Figure 37 has a typical value of 3 pF and is mainly the package pin capacitance. Resistor R1 is the on resistance of the multiplexer and track / hold switch and is typically 500 ohms. Capacitor C2 is the ADC088S022 sampling capacitor, and is typically 30 pF. The ADC088S022 will deliver best performance when driven by a low-impedance source (less than 100 ohms). This is especially important when using the ADC088S022 to sample dynamic signals. Also important when sampling dynamic signals is a band-pass or low-pass filter which reduces harmonics and noise in the input. These filters are often referred to as anti-aliasing filters.




Figure 37. Equivalent Input Circuit

## DIGITAL INPUTS AND OUTPUTS

The ADC088S022's digital inputs (SCLK,  $\overline{CS}$ , and DIN) have an operating range of 0V to  $V_A$ . They are not prone to latch-up and may be asserted before the digital supply ( $V_D$ ) without any risk. The digital output (DOUT) operating range is controlled by  $V_D$ . The output high voltage is  $V_D - 0.5V$  (min) while the output low voltage is 0.4V (max).

## APPLICATIONS INFORMATION

### TYPICAL APPLICATION CIRCUIT

A typical application is shown in [Figure 38](#). The split analog and digital supply pins are both powered in this example by the TI LP2950 low-dropout voltage regulator. The analog supply is bypassed with a capacitor network located close to the ADC088S022. The digital supply is separated from the analog supply by an isolation resistor and bypassed with additional capacitors. The ADC088S022 uses the analog supply ( $V_A$ ) as its reference voltage, so it is very important that  $V_A$  be kept as clean as possible. Due to the low power requirements of the ADC088S022, it is also possible to use a precision reference as a power supply.

To minimize the error caused by the changing input capacitance of the ADC088S022, a capacitor is connected from each input pin to ground. The capacitor, which is much larger than the input capacitance of the ADC088S022 when in track mode, provides the current to quickly charge the sampling capacitor of the ADC088S022. An isolation resistor is added to isolate the load capacitance from the input source.




Figure 38. Typical Application Circuit

### POWER SUPPLY CONSIDERATIONS

There are three major power supply concerns with this product: power supply sequencing, power management, and the effect of digital supply noise on the analog supply.

#### Power Supply Sequence

The ADC088S022 is a dual-supply device. The two supply pins share ESD resources, so care must be exercised to ensure that the power is applied in the correct sequence. To avoid turning on the ESD diodes, the digital supply ( $V_D$ ) cannot exceed the analog supply ( $V_A$ ) by more than 300 mV, not even on a transient basis. Therefore,  $V_A$  must ramp up before or concurrently with  $V_D$ .

#### Power Management

The ADC088S022 is fully powered-up whenever  $\overline{CS}$  is low and fully powered-down whenever  $\overline{CS}$  is high, with one exception. If operating in continuous conversion mode, the ADC088S022 automatically enters power-down mode between SCLK's 16th falling edge of a conversion and the SCLK's 1st falling edge of the subsequent conversion (see [Figure 1](#)).

In continuous conversion mode, the ADC088S022 can perform multiple conversions back to back. Each conversion requires 16 SCLK cycles and the ADC088S022 will perform conversions continuously as long as  $\overline{CS}$  is held low. Continuous mode offers maximum throughput.

In burst mode, the user may trade off throughput for power consumption by performing fewer conversions per unit time. This means spending more time in power-down mode and less time in normal mode. By utilizing this technique, the user can achieve very low sample rates while still utilizing an SCLK frequency within the electrical specifications. [Figure 33](#) in the [Typical Performance Characteristics](#) shows the typical power consumption of the ADC088S022. To calculate the power consumption ( $P_C$ ), simply multiply the fraction of time spent in the normal mode ( $t_N$ ) by the normal mode power consumption ( $P_N$ ), and add the fraction of time spent in shutdown mode ( $t_S$ ) multiplied by the shutdown mode power consumption ( $P_S$ ) as shown in [Equation 3](#).

$$P_C = \frac{t_N}{t_N + t_S} \times P_N + \frac{t_S}{t_N + t_S} \times P_S \quad (3)$$

### Power Supply Noise Considerations

The charging of any output load capacitance requires current from the digital supply,  $V_D$ . The current pulses required from the supply to charge the output capacitance will cause voltage variations on the digital supply. If these variations are large enough, they could degrade SNR and SINAD performance of the ADC. Furthermore, if the analog and digital supplies are tied directly together, the noise on the digital supply will be coupled directly into the analog supply, causing greater performance degradation than would noise on the digital supply alone. Similarly, discharging the output capacitance when the digital output goes from a logic high to a logic low will dump current into the die substrate, which is resistive. Load discharge currents will cause "ground bounce" noise in the substrate that will degrade noise performance if that current is large enough. The larger the output capacitance, the more current flows through the die substrate and the greater the noise coupled into the analog channel.

The first solution to keeping digital noise out of the analog supply is to decouple the analog and digital supplies from each other or use separate supplies for them. To keep noise out of the digital supply, keep the output load capacitance as small as practical. If the load capacitance is greater than 50 pF, use a 100  $\Omega$  series resistor at the ADC output, located as close to the ADC output pin as practical. This will limit the charge and discharge current of the output capacitance and improve noise performance. Since the series resistor and the load capacitance form a low frequency pole, verify signal integrity once the series resistor has been added.

### LAYOUT AND GROUNDING

Capacitive coupling between the noisy digital circuitry and the sensitive analog circuitry can lead to poor performance. The solution is to keep the analog circuitry separated from the digital circuitry and the clock line as short as possible.

Digital circuits create substantial supply and ground current transients. The logic noise generated could have significant impact upon system noise performance. To avoid performance degradation of the ADC088S022 due to supply noise, do not use the same supply for the ADC088S022 that is used for digital logic.

Generally, analog and digital lines should cross each other at 90° to avoid crosstalk. However, to maximize accuracy in high resolution systems, avoid crossing analog and digital lines altogether. It is important to keep clock lines as short as possible and isolated from ALL other lines, including other digital lines. In addition, the clock line should also be treated as a transmission line and be properly terminated.

The analog input should be isolated from noisy signal traces to avoid coupling of spurious signals into the input. Any external component (e.g., a filter capacitor) connected between the converter's input pins and ground or to the reference input pin and ground should be connected to a very clean point in the ground plane.

We recommend the use of a single, uniform ground plane and the use of split power planes. The power planes should be located within the same board layer. All analog circuitry (input amplifiers, filters, reference components, etc.) should be placed over the analog power plane. All digital circuitry and I/O lines should be placed over the digital power plane. Furthermore, all components in the reference circuitry and the input signal chain that are connected to ground should be connected together with short traces and enter the analog ground plane at a single, quiet point.

## REVISION HISTORY

### Changes from Revision E (March 2013) to Revision F

### Page

- Changed layout of National Data Sheet to TI format ..... [17](#)

## PACKAGING INFORMATION

| Orderable Device     | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2)            | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|----------------------|---------------|--------------|--------------------|------|----------------|----------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| ADC088S022CIMT       | NRND          | TSSOP        | PW                 | 16   | 92             | TBD                        | Call TI                 | Call TI              | -40 to 105   | 88S022<br>CIMT          |                         |
| ADC088S022CIMT/NOPB  | ACTIVE        | TSSOP        | PW                 | 16   | 92             | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-260C-UNLIM   | -40 to 105   | 88S022<br>CIMT          | <a href="#">Samples</a> |
| ADC088S022CIMTX      | NRND          | TSSOP        | PW                 | 16   |                | TBD                        | Call TI                 | Call TI              | -40 to 105   | 88S022<br>CIMT          |                         |
| ADC088S022CIMTX/NOPB | ACTIVE        | TSSOP        | PW                 | 16   | 2500           | Green (RoHS<br>& no Sb/Br) | CU SN                   | Level-1-260C-UNLIM   | -40 to 105   | 88S022<br>CIMT          | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.


(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and

---

continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**


\*All dimensions are nominal

| Device               | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|----------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| ADC088S022CIMTX/NOPB | TSSOP        | PW              | 16   | 2500 | 330.0              | 12.4               | 6.95    | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS




\*All dimensions are nominal

| Device                   | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|--------------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| ADC088S022CIMTX/NOP<br>B | TSSOP        | PW              | 16   | 2500 | 367.0       | 367.0      | 35.0        |

PW (R-PDSO-G16)

PLASTIC SMALL OUTLINE



4040064-4/G 02/11

- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
  - E. Falls within JEDEC MO-153

## IMPORTANT NOTICE

Texas Instruments Incorporated (TI) reserves the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

TI's published terms of sale for semiconductor products (<http://www.ti.com/sc/docs/stdterms.htm>) apply to the sale of packaged integrated circuit products that TI has qualified and released to market. Additional terms may apply to the use or sale of other types of TI products and services.

Reproduction of significant portions of TI information in TI data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such reproduced documentation. Information of third parties may be subject to additional restrictions. Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyers and others who are developing systems that incorporate TI products (collectively, "Designers") understand and agree that Designers remain responsible for using their independent analysis, evaluation and judgment in designing their applications and that Designers have full and exclusive responsibility to assure the safety of Designers' applications and compliance of their applications (and of all TI products used in or for Designers' applications) with all applicable regulations, laws and other applicable requirements. Designer represents that, with respect to their applications, Designer has all the necessary expertise to create and implement safeguards that (1) anticipate dangerous consequences of failures, (2) monitor failures and their consequences, and (3) lessen the likelihood of failures that might cause harm and take appropriate actions. Designer agrees that prior to using or distributing any applications that include TI products, Designer will thoroughly test such applications and the functionality of such TI products as used in such applications.

TI's provision of technical, application or other design advice, quality characterization, reliability data or other services or information, including, but not limited to, reference designs and materials relating to evaluation modules, (collectively, "TI Resources") are intended to assist designers who are developing applications that incorporate TI products; by downloading, accessing or using TI Resources in any way, Designer (individually or, if Designer is acting on behalf of a company, Designer's company) agrees to use any particular TI Resource solely for this purpose and subject to the terms of this Notice.

TI's provision of TI Resources does not expand or otherwise alter TI's applicable published warranties or warranty disclaimers for TI products, and no additional obligations or liabilities arise from TI providing such TI Resources. TI reserves the right to make corrections, enhancements, improvements and other changes to its TI Resources. TI has not conducted any testing other than that specifically described in the published documentation for a particular TI Resource.

Designer is authorized to use, copy and modify any individual TI Resource only in connection with the development of applications that include the TI product(s) identified in such TI Resource. NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT OF TI OR ANY THIRD PARTY IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information regarding or referencing third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of TI Resources may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI RESOURCES ARE PROVIDED "AS IS" AND WITH ALL FAULTS. TI DISCLAIMS ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, REGARDING RESOURCES OR USE THEREOF, INCLUDING BUT NOT LIMITED TO ACCURACY OR COMPLETENESS, TITLE, ANY EPIDEMIC FAILURE WARRANTY AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS. TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY DESIGNER AGAINST ANY CLAIM, INCLUDING BUT NOT LIMITED TO ANY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON ANY COMBINATION OF PRODUCTS EVEN IF DESCRIBED IN TI RESOURCES OR OTHERWISE. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, DIRECT, SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF TI RESOURCES OR USE THEREOF, AND REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Unless TI has explicitly designated an individual product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949 and ISO 26262), TI is not responsible for any failure to meet such industry standard requirements.

Where TI specifically promotes products as facilitating functional safety or as compliant with industry functional safety standards, such products are intended to help enable customers to design and create their own applications that meet applicable functional safety standards and requirements. Using products in an application does not by itself establish any safety features in the application. Designers must ensure compliance with safety-related requirements and standards applicable to their applications. Designer may not use any TI products in life-critical medical equipment unless authorized officers of the parties have executed a special contract specifically governing such use. Life-critical medical equipment is medical equipment where failure of such equipment would cause serious bodily injury or death (e.g., life support, pacemakers, defibrillators, heart pumps, neurostimulators, and implantables). Such equipment includes, without limitation, all medical devices identified by the U.S. Food and Drug Administration as Class III devices and equivalent classifications outside the U.S.

TI may expressly designate certain products as completing a particular qualification (e.g., Q100, Military Grade, or Enhanced Product). Designers agree that it has the necessary expertise to select the product with the appropriate qualification designation for their applications and that proper product selection is at Designers' own risk. Designers are solely responsible for compliance with all legal and regulatory requirements in connection with such selection.

Designer will fully indemnify TI and its representatives against any damages, costs, losses, and/or liabilities arising out of Designer's non-compliance with the terms and provisions of this Notice.