

1.1 Scope.

This specification covers the detail requirements for a high precision 10 volt IC reference.

1.2 Part Number.

The complete part number per Table 1 of this specification is as follows:

Device	Part Number
-1	AD587SQ/883B
-2	AD587TQ/883B
-3	AD587UQ/883B

1.2.3 Case Outline.

See Appendix 1 of General Specification ADI-M-1000: package outline: Q-8A.

1.3 Absolute Maximum Ratings. ($T_A = +25^\circ\text{C}$ unless otherwise noted)

Input Voltage V_{IN} to Ground	+36V
Power Dissipation	500mW
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering 10secs)	+300°C

1.5 Thermal Characteristics.

Thermal Resistance $\theta_{JC} = 22^\circ\text{C/W}$
 $\theta_{JA} = 110^\circ\text{C/W}$

AD587—SPECIFICATIONS


Table 1.

Test	Symbol	Device	Design Limit @ +25°C	Sub Group 1	Sub Group 2, 3	Sub Group 4	Test Condition ¹	Units
Quiescent Current	I _{CC}	- 1, 2, 3	4	4				+ mA max
Output Voltage Error	V _{OUT}	- 1	10	10				± mV max
		- 2	5	10		5		
		- 3	5	10		5		
Output Voltage Temperature Coefficient	V _{OUT} /dT	- 1	20		20		T _A = - 55°C to + 125°C	± ppm/°C max
		- 2	10		10			
		- 3	5		5			
Gain Adjustment	V _{ADJ}	- 1, 2, 3	+ 300	+ 300				mV min
			- 100	- 100				
Line Regulation	VR _{LINE}	- 1, 2, 3	100	100	100		13.5V ≤ V _{IN} ≤ 36V	± μV/V max
Load Regulation, Sourcing	VR _{LOAD}	- 1, 2, 3	100	100	100		I _L = 0 to 10mA	± μV/mA max
Load Regulation, Sinking	I _{OUT}	- 1, 2, 3	100	100	100		I _L = - 10 to 0mA	± μV/mA max
Output Short-Circuit Current	I _{OS}	- 1, 2, 3	50	50			To Ground	+ mA max
Output Short-Circuit Current	I _{OS}	- 1, 2, 3	50	50			To V _{IN}	- mA max


NOTE

¹T_A = + 25°C; V_{CC} = + 15V unless otherwise stated.

3.2.1 Functional Block Diagram and Terminal Assignments.



NOTE: MAKE NO CONNECTIONS TO PINS 1, 3, AND 7.




3.2.4 Microcircuit Technology Group.

This microcircuit is covered by technology group (59).

4.2.1 Life Test/Burn-In Circuit.

Steady state life test is per MIL-STD-883 Method 1005. Burn-in is per MIL-STD-883 Method 1015 test condition (B).



NOTE: D1 = MR-820
C1 = 0.1 μ F
C2 = 47 μ F
R1 = 1k Ω 1/2 WATT AT 25°C