



Automotive Product Selector Guide



Automotive Product Selector Guide

Microsemi® offers a broad range of automotive-grade FPGAs and ARM®-enabled SoC FPGAs for designers to choose from which best fits their requirements. This product selector guide covers primary parameters; be it logic elements density, package size, on-chip peripherals etc. that are used to select an FPGA or SoC FPGA for a given application. All the products recommended in this guide are AEC-Q100 qualified and offer extended temperature support. Microsemi's automotive-grade FPGAs and SoCs offers the advantages of best-in-class security, high-reliability and low-power flash FPGAs for automotive designers.

The following device families offer Microsemi automotive-grade FPGAs:

- ProASIC3®
- IGLOO®2
- SmartFusion®2

Family	Part Number	Package Size(mm)	Temperature Range(°C)	LEs	Mathblocks (18x18)	RAM Memory (Kbits)	Transceivers (Lanes)	Transceiver Speed	User I/Os	Status
ProASIC3	A3P060-1FG144T	13x13	-40 to 135	~700	-	18	-	-	96	Production
ProASIC3	A3P060-FG144T	13x13	-40 to 135	~700	-	18	-	-	96	Production
ProASIC3	A3P060-1FGG144T	13x13	-40 to 135	~700	-	18	-	-	96	Production
ProASIC3	A3P060-FGG144T	13x13	-40 to 135	~700	-	18	-	-	96	Production
ProASIC3	A3P060-1VQ100T	14x14	-40 to 135	~700	-	18	-	-	71	Production
ProASIC3	A3P060-VQ100T	14x14	-40 to 135	~700	-	18	-	-	71	Production
ProASIC3	A3P060-1VQG100T	14x14	-40 to 135	~700	-	18	-	-	71	Production
ProASIC3	A3P060-VQG100T	14x14	-40 to 135	~700	-	18	-	-	71	Production
ProASIC3	A3P125-1FG144T	13x13	-40 to 135	~1500	-	36	-	-	97	Production
ProASIC3	A3P125-FG144T	13x13	-40 to 135	~1500	-	36	-	-	97	Production
ProASIC3	A3P125-1FGG144T	13x13	-40 to 135	~1500	-	36	-	-	97	Production
ProASIC3	A3P125-FGG144T	13x13	-40 to 135	~1500	-	36	-	-	97	Production
ProASIC3	A3P125-1VQ100T	14x14	-40 to 135	~1500	-	36	-	-	71	Production
ProASIC3	A3P125-VQ100T	14x14	-40 to 135	~1500	-	36	-	-	71	Production
ProASIC3	A3P125-1VQG100T	14x14	-40 to 135	~1500	-	36	-	-	71	Production
ProASIC3	A3P125-VQG100T	14x14	-40 to 135	~1500	-	36	-	-	71	Production
ProASIC3	A3P250-FG144T	13x13	-40 to 135	~3,000	-	36	-	-	97	Production
ProASIC3	A3P250-1FGG144T	13x13	-40 to 135	~3,000	-	36	-	-	97	Production

Automotive Product Selector Guide



Table continuation...

Family	Part Number	Package Size(mm)	Temperature Range(°C)	LEs	Mathblocks (18x18)	RAM Memory (Kbits)	Transceivers (Lanes)	Transceiver Speed	User I/Os	Status
ProASIC3	A3P250-FGG144T	13x13	-40 to 135	~3,000	-	36	-	-	97	Production
ProASIC3	A3P250-1FG144T	13x13	-40 to 135	~3,000	-	36	-	-	97	Production
ProASIC3	A3P250-VQ100T	14x14	-40 to 135	~3,000	-	36	-	-	68	Production
ProASIC3	A3P250-1VQ100T	14x14	-40 to 135	~3,000	-	36	-	-	68	Production
ProASIC3	A3P250-1VQG100T	14x14	-40 to 135	~3,000	-	36	-	-	68	Production
ProASIC3	A3P250-VQG100T	14x14	-40 to 135	~3,000	-	36	-	-	68	Production
ProASIC3	A3P250-1FG256T	17x17	-40 to 135	~3,000	-	36	-	-	157	Production
ProASIC3	A3P250-FG256T	17x17	-40 to 135	~3,000	-	36	-	-	157	Production
ProASIC3	A3P250-1FGG256T	17x17	-40 to 135	~3,000	-	36	-	-	157	Production
ProASIC3	A3P250-FGG256T	17x17	-40 to 135	~3,000	-	36	-	-	157	Production
ProASIC3	A3P1000-1FG144T	13x13	-40 to 135	~11,000	-	144	-	-	97	Production
ProASIC3	A3P1000-1FGG144T	13x13	-40 to 135	~11,000	-	144	-	-	97	Production
ProASIC3	A3P1000-FGG144T	13x13	-40 to 135	~11,000	-	144	-	-	97	Production
ProASIC3	A3P1000-FG144T	13x13	-40 to 135	~11,000	-	144	-	-	97	Production
ProASIC3	A3P1000-1FG256T	17x17	-40 to 135	~11,000	-	144	-	-	177	Production
ProASIC3	A3P1000-FG256T	17x17	-40 to 135	~11,000	-	144	-	-	177	Production
ProASIC3	A3P1000-1FGG256T	17x17	-40 to 135	~11,000	-	144	-	-	177	Production
ProASIC3	A3P1000-FGG256T	17x17	-40 to 135	~11,000	-	144	-	-	177	Production
ProASIC3	A3P1000-1FG484T	23x23	-40 to 135	~11,000	-	144	-	-	300	Production
ProASIC3	A3P1000-FG484T	23x23	-40 to 135	~11,000	-	144	-	-	300	Production
ProASIC3	A3P1000-1FGG484T	23x23	-40 to 135	~11,000	-	144	-	-	300	Production
ProASIC3	A3P1000-FGG484T	23x23	-40 to 135	~11,000	-	144	-	-	300	Production
SmartFusion2	M2S005S-1VFG256T2	14x14	-40 to 125	6,060	11	703	-	-	161	Production
SmartFusion2	M2S005S-1VFG400T2	17x17	-40 to 125	6,060	11	703	-	-	171	Production
SmartFusion2	M2S005S-1FGG484T2	23x23	-40 to 125	6,060	11	703	-	-	209	Production
SmartFusion2	M2S010TS-1VFG256T2	14x14	-40 to 125	12,084	22	912	2	3.125 Gbps	138	Production

Automotive Product Selector Guide

Table continuation...

Family	Part Number	Package Size(mm)	Temperature Range(°C)	LEs	Mathblocks (18x18)	RAM Memory (Kbits)	Transceivers (Lanes)	Transceiver Speed	User I/Os	Status
SmartFusion2	M2S010TS-1VFG400T2	17x17	-40 to 125	12,084	22	912	4	3.125 Gbps	195	Production
SmartFusion2	M2S010TS-1FGG484T2	23x23	-40 to 125	12,084	22	912	4	3.125 Gbps	233	Production
SmartFusion2	M2S025TS-1VFG256T2	14x14	-40 to 125	27,696	34	1104	2	3.125 Gbps	138	Production
SmartFusion2	M2S025TS-1VFG400T2	17x17	-40 to 125	27,696	34	1104	4	3.125 Gbps	207	Production
SmartFusion2	M2S025TS-1FGG484T2	23x23	-40 to 125	27,696	34	1104	4	3.125 Gbps	267	Production
SmartFusion2	M2S060TS-1VFG400T2	17x17	-40 to 125	56,520	72	1826	4	3.125 Gbps	207	Preliminary
SmartFusion2	M2S060TS-1FGG484T2	23x23	-40 to 125	56,520	72	1826	4	3.125 Gbps	267	Preliminary
SmartFusion2	M2S060TS-1FGG676T2	27x27	-40 to 125	56,520	72	1826	4	3.125 Gbps	387	Preliminary
SmartFusion2	M2S090TS-1FGG484T2	23x23	-40 to 125	86,184	84	2586	4	3.125 Gbps	425	Production
SmartFusion2	M2S090TS-1FGG676T2	27x27	-40 to 125	86,184	84	2586	4	3.125 Gbps	425	Production
IGLOO2	M2GL005S-1VFG256T2	14x14	-40 to 125	6,060	11	703	-	-	161	Production
IGLOO2	M2GL005S-1VFG400T2	17x17	-40 to 125	6,060	11	703	-	-	171	Production
IGLOO2	M2GL005S-1FGG484T2	23x23	-40 to 125	6,060	11	703	-	-	209	Production
IGLOO2	M2GL010TS-1VFG256T2	14x14	-40 to 125	12,084	22	912	2	3.125 Gbps	138	Production
IGLOO2	M2GL010TS-1VFG400T2	17x17	-40 to 125	12,084	22	912	4	3.125 Gbps	195	Production
IGLOO2	M2GL010TS-1FGG484T2	23x23	-40 to 125	12,084	22	912	4	3.125 Gbps	233	Production
IGLOO2	M2GL025TS-1VFG256T2	14x14	-40 to 125	27,696	34	1104	2	3.125 Gbps	138	Production
IGLOO2	M2GL025TS-1VFG400T2	17x17	-40 to 125	27,696	34	1104	4	3.125 Gbps	207	Production
IGLOO2	M2GL025TS-1FGG484T2	23x23	-40 to 125	27,696	34	1104	4	3.125 Gbps	267	Production
IGLOO2	M2GL060TS-1VFG400T2	17x17	-40 to 125	56,520	72	1826	4	3.125 Gbps	207	Preliminary
IGLOO2	M2GL060TS-1FGG484T2	23x23	-40 to 125	56,520	72	1826	4	3.125 Gbps	267	Preliminary
IGLOO2	M2GL060TS-1FGG676T2	27x27	-40 to 125	56,520	72	1826	4	3.125 Gbps	387	Preliminary
IGLOO2	M2GL090TS-1FGG484T2	23x23	-40 to 125	86,184	84	2586	4	3.125 Gbps	267	Production
IGLOO2	M2GL090TS-1FGG676T2	27x27	-40 to 125	86,184	84	2586	4	3.125 Gbps	425	Production
IGLOO2	M2GL005-1FGG484T1	23x23	-40 to 135	6,060	11	703	-	-	209	Planned
IGLOO2	M2GL010-1FGG484T1	23x23	-40 to 135	12,084	22	912	-	-	233	Planned

Table continuation...

Family	Part Number	Package Size(mm)	Temperature Range(°C)	LEs	Mathblocks (18x18)	RAM Memory (Kbits)	Transceivers (Lanes)	Transceiver Speed	User I/Os	Status
IGLOO2	M2GL025-1FGG484T1	23x23	-40 to 135	27,696	34	1104	-	-	267	Planned
IGLOO2	M2GL060-1FGG484T1	23x23	-40 to 135	56,520	72	1826	-	-	267	Planned
IGLOO2	M2GL090-1FGG484T1	23x23	-40 to 135	86,184	84	2586	-	-	267	Planned

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.



Microsemi®

Microsemi Corporate Headquarters
 One Enterprise, Aliso Viejo, CA 92656 USA
 Within the USA: +1 (800) 713-4113
 Outside the USA: +1 (949) 380-6100
 Sales: +1 (949) 380-6136
 Fax: +1 (949) 215-4996
 email: sales.support@microsemi.com
 www.microsemi.com

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense & security, aerospace and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif, and has approximately 3,600 employees globally. Learn more at www.microsemi.com.