



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE74HCT174 Integrated Circuit TTL – High Speed CMOS, Hex D–Type Flip–Flop with Clear

Description:

The NTE74HCT174 is a positive edge–triggered flip–flop in a 16–Lead DIP type package that has a common clock and clear and independent Q outputs. Data on a D input, having the specified set–up and hold time, is transferred to the corresponding Q output on the positive–going transition of the clock pulse. The asynchronous clear forces all outputs low when it is low.

All inputs to this device are protected from damage due to electrostatic discharge by diodes to V_{CC} and GND.

Features:

- Typical Propagation Delay: 20ns
- Low Quiescent Current: 80 μ A (max)
- Fanout of 10 LS–TTL Loads

Absolute Maximum Ratings: (Note 1, Note 2)

Supply Voltage, V_{CC}	–0.5 to +7.0V
DC Input Voltage, V_{IN}	–1.5 to $V_{CC} + 1.5V$
DC Output Voltage, V_{OUT}	–0.5 to $V_{CC} + 0.5V$
Clamp Diode Current, I_{IK}, I_{OK}	$\pm 20mA$
DC Output Current (Per Pin), I_{OUT}	$\pm 25mA$
DC V_{CC} or GND Current (Per Pin), I_{CC}	$\pm 50mA$
Power Dissipation (Note 3), P_D	500mW
Storage Temperature Range, T_{stg}	–65°C to +150°C
Lead Temperature (During Soldering, 10sec), T_L	+260°C

Note 1. Absolute Maximum Ratings are those values beyond which damage to the device may occur.

Note 2. Unless otherwise specified, all voltages are referenced to GND.

Note 3. Power Dissipation temperature derating: 12mW/°C from +65°C to +85°C.

Recommended Operating Conditions:

Parameter	Symbol	Min	Typ	Max	Unit
Supply Voltage	V_{CC}	4.5	–	5.5	V
DC Input or Output Voltage	V_{IN}, V_{OUT}	0	–	V_{CC}	V
Operating Temperature Range	T_A	–40	–	+85	°C
Input Rise or Fall Times	t_r, t_f	–	–	500	ns

DC Electrical Characteristics: ($V_{CC} = 5V \pm 10\%$ unless otherwise specified)

Parameter	Symbol	Test Conditions		T _A = +25°C		T _A = −40° to +85°C	Unit
				Typ	Guaranteed Limits		
Minimum High Level Input Voltage	V _{IH}			–	2.0	2.0	V
Maximum Low Level Input Voltage	V _{IL}			–	0.8	0.8	V
Minimum High Level Output Voltage	V _{OH}	V _{IN} = V _{IH} or V _{IL}	I _{OUT} = 20μA	V _{CC}	V _{CC} ^{−0.1}	V _{CC} ^{−0.1}	V
			I _{OUT} = 4.0mA, V _{CC} = 4.5V	4.2	3.98	3.84	V
			I _{OUT} = 4.8mA, V _{CC} = 5.5V	5.7	4.98	4.84	V
Maximum Low Level Output Voltage	V _{OL}	V _{IN} = V _{IH}	I _{OUT} = 20μA	0	0.1	0.1	V
			I _{OUT} = 4.0mA, V _{CC} = 4.5V	0.2	0.26	0.33	V
			I _{OUT} = 4.8mA, V _{CC} = 5.5V	0.2	0.26	0.33	V
Maximum Input Current	I _{IN}	V _{IN} = V _{CC} or GND, V _{IH} or V _{IL}		–	±0.1	±1.0	μA
Maximum Quiescent Supply Current	I _{CC}	V _{IN} = V _{CC} or GND, I _{OUT} = 0μA		–	8	80	μA
		V _{IN} = 2.4V or 0.5V, Note 4		–	–	–	μA

Note 4. This is measured per input with all other inputs held at V_{CC} or GND.

AC Electrical Characteristics: ($V_{CC} = 5V$, $t_r = t_f = 6\text{ns}$, $C_L = 15\text{pF}$, $T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Typ	Guaranteed Limits	Unit
Maximum Operating Frequency	f_{MAX}		50	30	MHz
Maximum Propagation Delay (Clock to Q)	t_{PHL} , t_{PLH}		18	30	ns
Maximum Propagation Delay (Clear to Q)	t_{PHL} , t_{PLH}		18	30	ns
Maximum Removal Time (Clear to Clock)	t_{REM}		–	20	ns
Minimum Set Up Time (D to Clock)	t_S		10	30	ns
Minimum Hold Time (Clock to Q)	t_H		–3	0	ns
Minimum Pulse Width (Clock or Clear)	t_W		8	16	ns

AC Electrical Characteristics: ($V_{CC} = 5V \pm 10\%$, $t_r = t_f = 6\text{ns}$, $C_L = 50\text{pF}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	T _A = +25°C		T _A = −40° to +85°C	Unit
			Typ	Guaranteed Limits		
Maximum Operating Frequency	f _{MAX}		40	22	18	MHz
Maximum Propagation Delay (Clock to Q)	t _{PHL} , t _{PLH}		22	35	44	ns
Maximum Propagation Delay (Clear to Q)	t _{PHL} , t _{PLH}		22	35	44	ns
Minimum Removal Time (Clear to Clock)	t _{REM}		–	20	25	ns
Minimum Setup Time (D to Clock)	t _S		10	20	25	ns
Minimum Hold Time (D to Clock)	t _H		−3	0	0	ns
Minimum Pulse Width (Clock or Clear)	t _W		–	16	20	ns
Maximum Input Rise and Fall Time	t _r , t _f		–	500	500	ns
Maximum Output Rise and Fall Time	t _{THL} , t _{TLH}		–	15	19	ns
Power Dissipation Capacitance	C _{PD}	Per Flip-Flop, Note 5	–	–	–	pF
Maximum Input Capacitance	C _{IN}		5	10	10	pF

Note 5. C_{PD} determines the no load dynamic power consumption, $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$, and the no load dynamic current consumption, $I_S = C_{PD} V_{CC} f + I_{CC}$.



Pin Connection Diagram

