



SANYO Semiconductors

DATA SHEET

LA47503

Monolithic Linear IC
For Car Audio
BTL 4ch (50W×4) Power IC

Overview

The LA47503 is a BTL 4ch (50W×4) power IC for car audio.

Functions

- Maximum output display 48W×4 ($V_{CC} = 14.4V$, 4Ω , 1kHz, average measurement)
- 43W×4 ($V_{CC} = 14.4V$, 4Ω , 1kHz)
- Equipped an electric mirror noise control pin.
- Built-in mute function.
- Built-in stand-by SW.
- Various types of built-in protection circuits (Air fault, ground fault, load short, over voltage and heat protections)
- GND open ground fault resistance amount 16V.

Specifications

Maximum Ratings at $T_a = 25^\circ C$

Parameter	Symbol	Conditions	Ratings	Unit
Maximum power supply voltage	$V_{CC\ max1}$	When signal is ON	18	V
	$V_{CC\ max2}$	When signal is OFF	26	V
Maximum output current	$I_O\ peak$		4.5/ch	A
Allowable power dissipation	$P_d\ max$	Infinite heatsink	50	W
Operating ambient temperature	T_{opr}		-40 to +85	$^\circ C$
Storage ambient temperature	T_{stg}		-40 to +150	$^\circ C$
Heat resistance between junction part and case	θ_{j-c}		1	$^\circ C/W$

Operating Conditions at $T_a = 25^\circ C$

Parameter	Symbol	Conditions	Ratings	Unit
Recommended supply voltage	V_{CC}		14.4	V
Recommended load resistance	R_L		4	Ω
Operating supply voltage range	$V_{CC\ op}$		9 to 18	V

- Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.
- SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO products described or contained herein.

LA47503


Electrical Characteristics at $T_a = 25^\circ\text{C}$, $V_{CC} = 14.4\text{V}$, $f = 1\text{kHz}$, $R_L = 4\Omega$, $R_g = 600\Omega$

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Current when signal is OFF	I _{CCO}	R _L = ∞, R _g = 0		200	350	mA
Stand-by current	I _{st}	V _{st} = 0V			10	μA
Output offset voltage	V _{noffset}	R _g = 0	-150		+150	mV
Voltage gain	V _G	V _O = 0dBm	31	32	33	dB
Voltage gain difference	ΔV _G		-1		+1	dB
Output electric power	P _{O1}	THD = 10%	24	29		W
	P _{O max1}	V _{CC} = 13.7V, V _{IN} = 5Vrms		43		W
	P _{O max2}	V _{IN} = 2.5Vrms		48		W
All higher harmonics distortion factor	THD	P _O = 4W		0.1	0.4	%
Channel separation	Chsep	V _O = 0dBm, R _g = 10kΩ	55	70		dB
Ripple rejection ratio	SVRR	f _r = 100Hz, V _r = 0dBm, R _g = 0	50	70		dB
Output noise voltage	V _{no}	R _g = 0 B.P.F. = 20Hz to 20kHz		80	200	μVrms
Mute attenuation	Ma	V _O = 20dBm	70	90		dB

Package Dimensions

unit : mm

3236A



- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of May, 2004. Specifications and information herein are subject to change without notice.