

CR16HCS5/CR16HCS9/CR16MAR5/CR16MAS5/ CR16MAS9/CR16MBR5/CR16MCS5/CR16MCS9

Family of 16-bit CAN-enabled CompactRISC Microcontrollers

General Description

The family of 16-bit CompactRISC™ microcontroller is based on a Reduced Instruction Set Computer (RISC) architecture. The device operates as a complete microcomputer with all system timing, interrupt logic, flash program memory or ROM memory, RAM, EEPROM data memory, and I/O ports included on-chip. It is ideally suited to a wide range of embedded controller applications because of its high performance, on-chip integrated features and low power consumption resulting in decreased system cost.

The device offers the high performance of a RISC architecture while retaining the advantages of a traditional Complex Instruction Set Computer (CISC): compact code, on-chip memory and I/O, and reduced cost. The CPU uses a three-stage instruction pipeline that allows execution of up to one instruction per clock cycle, or up to 25 million instructions per second (MIPS) at a clock rate of 24 MHz.

The device contains a FullCAN class, CAN serial interface for low/high speed applications with 15 orthogonal message buffers, each supporting standard as well as extended message identifiers.

The device has up to 64K bytes of reprogrammable flash EEPROM program memory or ROM memory, 1.5K bytes of flash EEPROM In-System-Programming memory, 3K bytes of static RAM, 2K bytes of non-volatile EEPROM data memory and 128 bytes with high endurance, two USARTs, two 16-bit multi-function timers, one SPI/MICROWIRE-PLUS™ serial interface, a 12-channel A/D converter, two analog comparators, WATCHDOG™ protection mechanism, and up to 56 general-purpose I/O pins.

The device operates with a high-frequency crystal as the main clock source and either the prescaled main clock source or with a low frequency (32.768 kHz) oscillator in Power Save mode. The device supports several Power Save modes which are combined with multi-source interrupt and wake-up capabilities. This device also has a Versatile Timer Unit (VTU) with four timer sub-systems, a CAN interface, and ACCESS.bus synchronous serial bus interface.

Powerful cross-development tools are available from National Semiconductor and third party suppliers to support the development and debugging of application software for the device. These tools let you program the application software in C and are designed to take full advantage of the CompactRISC architecture.

In the following text, device is always referred to the family of 16-bit CAN-enabled CompactRISC Microcontroller.

Please check the web for the latest update to this datasheet.

Features


- CPU Features
 - Fully static core, capable of operating at any rate from 0 to 24 MHz (4 MHz minimum in active mode)
 - Multi-source vectored interrupts (internal, external, and on-chip peripheral)
 - Dual clock and reset
- On-chip power-on reset
- On-Chip Memory
 - Up to 64 kbytes flash EEPROM program memory; can be programmed, erased, and reprogrammed by software (100 kcycles)
 - 3 kbytes of static RAM data memory
 - For flash program memory devices, 1.5 kbytes flash EEPROM memory is available to store boot loader code (100 kcycles)
 - 2 kbytes of non-volatile EEPROM data memory with low endurance (25 kcycles) and 128 bytes with high endurance (100 kcycles)
- On-Chip Peripherals
 - Two Universal Synchronous/Asynchronous Receiver/Transmitter (USART) devices
 - Programmable Idle Timer and real-time clock (T0)
 - Two dual 16-bit multi-function timers (MFT1 and MFT2)
 - 8/16-bit SPI/MICROWIRE-PLUS serial interface
 - 12-channel, 8-bit Analog-to-Digital (A/D) converter with external voltage reference, programmable sample-and-hold delay, and programmable conversion frequency
 - ACCESS.bus synchronous serial bus
 - FullCAN interface with 15 message buffers compliant to CAN specification 2.0B active
 - Versatile Timer Unit with four subsystems (VTU)
 - Two analog comparators
 - Integrated WATCHDOG logic
- I/O Features
 - Up to 56 general-purpose I/O pins (shared with on-chip peripheral I/O pins)
 - Programmable I/O pin characteristics: TRI-STATE output, push-pull output, weak pull-up input, high-impedance input
 - Schmitt triggers on general purpose inputs
- Power Supply
 - 4.5V to 5.5V single-supply operation
- Temperature Range
 - -40°C to +85°C
 - -40°C to +125°C

Features (Continued)

- Development Support
 - Real-time emulation and full program debug capabilities available

— CompactRISC tools provide C programming and debugging support

Block Diagram



20032001

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
 Americas
 Email: support@nsc.com

www.national.com

National Semiconductor Europe
 Fax: +49 (0) 180-530 85 86
 Email: europe.support@nsc.com
 Deutsch Tel: +49 (0) 69 9508 6208
 English Tel: +44 (0) 870 24 0 2171
 Français Tel: +33 (0) 1 41 91 8790

National Semiconductor Asia Pacific Customer Response Group
 Tel: 65-2544466
 Fax: 65-2504466
 Email: ap.support@nsc.com

National Semiconductor Japan Ltd.
 Tel: 81-3-5639-7560
 Fax: 81-3-5639-7507

CR16MAS9 Product Folder

Family of 16-bit CAN-enabled CompactRISC Microcontrollers

General Description	Features	Datasheet	Package & Models	Samples & Pricing
-------------------------------------	--------------------------	---------------------------	--------------------------------------	---------------------------------------

Parametric Table

Operating Frequency (MHz)	25
Code Memory (in K Bytes) (Bytes)	64
Code Memory Type	Flash
SRAM (in K Bytes) (Bytes)	3
EEPROM Data Memory	-
CAN	Yes
ACCESS.Bus/I2C	Yes
Operating Voltage	5.0V
General Purpose I/O	56
SCI/SPI	2 / 1

Parametric Table

Halt/Idle	Yes
MIWU	Yes
Timers	MFT, VTU
Interrupts	32 + 1NMI
Power on Reset	Yes
Watchdog	Yes
A/D Converter # Ch	none
Comparators	No
Microwire Plus	Yes
USART Interface	Yes

Datasheet

Title	Size in Kbytes	Date	 View Online	 Download	 Receive via Email
CR16HCS5 CR16HCS9 CR16MAR5 CR16MAS5 CR16MAS9 CR16MBR5 CR16MCS5 CR16MCS9 Family of 16-bit CAN-enabled CompactRISC Microcontrollers	50 Kbytes	2-Jan-02	View Online	Download	Receive via Email

If you have trouble printing or viewing PDF file(s), see [Printing Problems](#).

Package Availability, Models, Samples & Pricing

Part Number	Package			Status	Models		Samples & Electronic Orders	Budgetary Pricing		Std Pack Size	Package Marking
	Type	Pins	MSL		SPICE	IBIS		Qty	\$US each		
CR16MAS9VJE7	PQFP	80	MSL	Full production	N/A	N/A	Buy Now	1K+	\$10.8000	tray of 84	[logo]2¢Z¢3¢T¢P CR16MAS9VJE7
CR16MAS9VJE8	PQFP	80	MSL	Full production	N/A	N/A	Buy Now	1K+	\$10.7000	tray of 84	[logo]2¢Z¢3¢T¢P CR16MAS9VJE8

CR16MAS9VJE9	PQFP	80	MSL	Full production	N/A	N/A	Samples Buy Now	1K+	\$10.4000	tray of 84	[logo]2¢Z¢3¢T¢P CR16MAS9VJE9
--------------	----------------------	----	---------------------	-----------------	-----	-----	---------------------------------------	-----	-----------	------------	---------------------------------

General Description

The family of 16-bit CompactRISC™ microcontroller is based on a Reduced Instruction Set Computer (RISC) architecture. The device operates as a complete microcomputer with all system timing, interrupt logic, flash program memory or ROM memory, RAM, EEPROM data memory, and I/O ports included on-chip. It is ideally suited to a wide range of embedded controller applications because of its high performance, on-chip integrated features and low power consumption resulting in decreased system cost.

The device offers the high performance of a RISC architecture while retaining the advantages of a traditional Complex Instruction Set Computer (CISC): compact code, on-chip memory and I/O, and reduced cost. The CPU uses a three-stage instruction pipeline that allows execution of up to one instruction per clock cycle, or up to 25 million instructions per second (MIPS) at a clock rate of 24 MHz.

The device contains a FullCAN class, CAN serial interface for low/high speed applications with 15 orthogonal message buffers, each supporting standard as well as extended message identifiers.

The device has up to 64K bytes of reprogrammable flash EEPROM program memory or ROM memory, 1.5K bytes of flash EEPROM In-System-Programming memory, 3K bytes of static RAM, 2K bytes of non-volatile EEPROM data memory and 128 bytes with high endurance, two USARTs, two 16-bit multi-function timers, one SPI/MICROWIRE-PLUS™ serial interface, a 12-channel A/D converter, two analog comparators, WATCHDOG™ protection mechanism, and up to 56 general-purpose I/O pins.

The device operates with a high-frequency crystal as the main clock source and either the prescaled main clock source or with a low frequency (32.768 kHz) oscillator in Power Save mode. The device supports several Power Save modes which are combined with multi-source interrupt and wake-up capabilities. This device also has a Versatile Timer Unit (VTU) with four timer sub-systems, a CAN interface, and ACCESS.bus synchronous serial bus interface.

Powerful cross-development tools are available from National Semiconductor and third party suppliers to support the development and debugging of application software for the device. These tools let you program the application software in C and are designed to take full advantage of the CompactRISC architecture.

In the following text, device is always referred to the family of 16-bit CAN-enabled CompactRISC Microcontroller.

Please check the web for the latest update to this datasheet.

Features

- CPU Features
 - Fully static core, capable of operating at any rate from 0 to 24 MHz (4 MHz minimum in active mode)
 - Multi-source vectored interrupts (internal, external, and on-chip peripheral)
 - Dual clock and reset
- On-chip power-on reset
- On-Chip Memory
 - Up to 64 kbytes flash EEPROM program memory; can be programmed, erased, and reprogrammed by software (100 kcycles)
 - 3 kbytes of static RAM data memory
 - For flash program memory devices, 1.5 kbytes flash EEPROM memory is available to store boot loader code (100 kcycles)
 - 2 kbytes of non-volatile EEPROM data memory with low endurance (25 kcycles) and 128 bytes with high endurance (100 kcycles)

- On-Chip Peripherals
 - Two Universal Synchronous/Asynchronous Receiver/Transmitter (USART) devices
 - Programmable Idle Timer and real-time clock (T0)
 - Two dual 16-bit multi-function timers (MFT1 and MFT2)
 - 8/16-bit SPI/MICROWIRE-PLUS serial interface
 - 12-channel, 8-bit Analog-to-Digital (A/D) converter with external voltage reference, programmable sample-and-hold delay, and programmable conversion frequency
 - ACCESS.bus synchronous serial bus
 - FullCAN interface with 15 message buffers compliant to CAN specification 2.0B active
 - Versatile Timer Unit with four subsystems (VTU)
 - Two analog comparators
 - Integrated WATCHDOG logic
- I/O Features
 - Up to 56 general-purpose I/O pins (shared with on-chip peripheral I/O pins)
 - Programmable I/O pin characteristics: TRI-STATE output, push-pull output, weak pull-up input, high-impedance input
 - Schmitt triggers on general purpose inputs
- Power Supply
 - 4.5V to 5.5V single-supply operation
- Temperature Range
 - -40°C to +85°C
 - -40°C to +125°C
- Development Support
 - Real-time emulation and full program debug capabilities available
 - CompactRISC tools provide C programming and debugging support

[Information as of 5-Aug-2002]

Search	<u>Design</u>	<u>Purchasing</u>	<u>Quality</u>	<u>Company</u>	<u>Home</u>
---------------	-------------------------------	-----------------------------------	--------------------------------	--------------------------------	-----------------------------

[About Languages](#) .
 [Website Guide](#) .
 [About "Cookies"](#) .
 National is [QS 9000 Certified](#) .
 [Privacy/Security Statement](#) .
[Contact Us](#) .
 [Site Terms & Conditions of Use](#) .
 Copyright 2002 © National Semiconductor Corporation .
 [My Preferences](#) .
[**Feedback**](#)

CR16MCS9 Product Folder

CompactRISC 16-Bit Reprogrammable/ROM Microcontroller

General Description	Features	Datasheet	Package & Models	Samples & Pricing
-------------------------------------	--------------------------	---------------------------	--------------------------------------	---------------------------------------

Parametric Table

Operating Frequency (MHz)	25
Code Memory (in K Bytes) (Bytes)	64
Code Memory Type	Flash
SRAM (in K Bytes) (Bytes)	3
EEPROM Data Memory	2176
CAN	Yes
ACCESS.Bus/I2C	Yes
Operating Voltage	5.0V
General Purpose I/O	56
SCI/SPI	2 / 1

Parametric Table

Halt/Idle	Yes
MIWU	Yes
Timers	MFT, VTU
Interrupts	32 + 1NMI
Power on Reset	Yes
Watchdog	Yes
A/D Converter # Ch	8 bit, 12 channel
Comparators	Yes
Microwire Plus	Yes
USART Interface	Yes

Datasheet

Title	Size in Kbytes	Date	 View Online	 Download	 Receive via Email
CR16MCS9 CR16MCS5 CR16HCS9 CR16HCS5 CompactRISC 16-Bit Reprogrammable ROM Microcontroller	50 Kbytes	23-Apr-02	View Online	Download	Receive via Email

If you have trouble printing or viewing PDF file(s), see [Printing Problems](#).

Package Availability, Models, Samples & Pricing

Part Number	Package			Status	Models		Samples & Electronic Orders	Budgetary Pricing		Std Pack Size	Package Marking
	Type	Pins	MSL		SPICE	IBIS		Qty	\$US each		
CR16MCS9VJE8XXX	PQFP	80	MSL	Preliminary	N/A	N/A		1K+	\$11.3000	tray of 84	[logo]2¢Z¢3¢T¢P CR16MCS9 VJE8XXX
CR16MCS9VJE9XXX	PQFP	80	MSL	Preliminary	N/A	N/A		1K+	\$11.0000	tray of 84	[logo]2¢Z¢3¢T¢P CR16MCS9 VJE9XXX

CR16MCS9VJE8	PQFP	80	MSL	Custom	N/A	N/A	Buy Now	1K+	\$11.3000	tray of 84	[logo]2¢Z¢3¢T¢P CR16MCS9 VJE8
CR16MCS9VJE7XXX	PQFP	80	MSL	Preliminary	N/A	N/A		1K+	\$11.3000	tray of 84	[logo]2¢Z¢3¢T¢P CR16MCS9 VJE7XXX
CR16MCS9VJE7	PQFP	80	MSL	Full production	N/A	N/A	Samples	1K+	\$11.4000	tray of 84	[logo]2¢Z¢3¢T¢P CR16MCS9 VJE7
CR16MCS9VJE9	PQFP	80	MSL	Full production	N/A	N/A	Samples Buy Now	1K+	\$11.0000	tray of 84	[logo]2¢Z¢3¢T¢P CR16MCS9VJE9

General Description

The CR16MCS9/CR16MCS5/CR16HCS9/CR16HCS5 CompactRISC™ microcontrollers are general-purpose 16-bit microcontrollers based on a Reduced Instruction Set Computer (RISC) architecture. The device operates as a complete microcomputer with all system timing, interrupt logic, flash program memory or ROM memory, RAM, EEPROM data memory, and I/O ports included on-chip. It is ideally suited to a wide range of embedded controller applications because of its high performance, on-chip integrated features and low power consumption resulting in decreased system cost. The CR16MCS9/CR16MCS5/CR16HCS9/CR16HCS5 devices contains a Full-CAN class, CAN serial interface for low/high speed applications with 15 orthogonal message buffers, each supporting standard as well as extended message identifiers.

Features

- CPU Features include: up to 24MHz operating frequency, 41.67 ns instruction cycle, Multi-source vectored interrupts, Dual clock and reset.
- On-chip power on reset
- On-Chip Memory
- On-Chip Peripherals including: USARTs, Multi Function Timers, SPI/Microwire-Plus, A/D, ACCESS.bus, Full CAN interface, Versatile timer units, Analog comparators, Integrated watchdog logic
- I/O Features include: up to 56 general purpose I/O pins with TRI-STATE output
- 4.5V to 5.5V Single supply operation
- Full temperature range options
- Competitive Development support

[Information as of 5-Aug-2002]