

Single/Dual/Quad Ultra-Low Power Operational Amplifiers

Features

- Low Supply Current.....45 μ A/Amp
- Wide Supply Voltage Range Single 3V to 30V
or Dual \pm 1.5V to \pm 15V
- High Slew Rate 1.5V/ μ s
- High Gain 100kV/V
- Unity Gain Stable
- Available in Singles, Duals and Quads

Applications

- Portable Instruments
- Meter Amplifiers
- Telephone Headsets
- Microphone Amplifiers
- Instrumentation
- For Further Design Ideas See App. Note 544

Description

The HA-5141/42/44 ultra-low power operational amplifiers provided AC and DC performance characteristics similar to or better than most general purpose amplifiers while only drawing 1/30 of the supply current of most general purpose amplifiers. In applications which require low power dissipation and good A.C. electrical characteristics, this family offers the industry's best speed/power ratio.


The HA-5141/42/44 provides accurate signal processing by virtue of their low input offset voltage (0.5mV), low input bias current (45nA), high open loop gain (100kV/V) and low noise, for low power operational amplifiers (20nV/ \sqrt Hz). These characteristics coupled with a 1.5/ μ s slew rate and a 400kHz bandwidth make the HA-5141/42/44 ideal for use

in low power instrumentation, audio amplifier and active filter designs. The wide range of supply voltages (3V to 30V) also allow these amplifiers to be very useful in low voltage battery powered equipment. These parts are also tested and guaranteed at both \pm 15V and single ended +5V supplies.


These amplifiers are available in singles (HA-5141, Can or Mini-DIP), duals (HA-5142, Can, Mini-DIP or 20 pin LCC) or quads (HA-5144, 14 pin DIP or 20 pin LCC) with industry standards pinouts which allow the HA-5141/5142/5144's to be interchangeable with most other operational amplifiers. For military grade product refer to the 5141, 5142, 5144/883 data sheet.

Pinouts

HA1-5141 (CERAMIC MINI-DIP)
HA3-5141 (PLASTIC MINI-DIP)




HA2-5141 (TO-99 METAL CAN)




TOP VIEWS


HA3-5142 (PLASTIC MINI-DIP)
HA7-5142 (CERAMIC MINI-DIP)



HA2-5142 (TO-99 METAL CAN)



HA1-5144 (CERAMIC DIP)
HA3-5144 (PLASTIC DIP)



Specifications HA-5141/42/44

Absolute Maximum Ratings (Note 1)

Voltage Between V+ and V- Terminals..... 35V
 Differential Input Voltage..... $\pm 7V$
 Output Current..... S/C Protected
 Internal Power Dissipation..... 500mW

Operating Temperature Range

HA-5141/42/44-5 $0^{\circ}C \leq T_A \leq +75^{\circ}C$
 HA-5141/42/44-2 $-55^{\circ}C \leq T_A \leq +125^{\circ}C$
 Storage Temperature Range $-65^{\circ}C \leq T_A \leq +150^{\circ}C$

Electrical Specifications $R_S = 100\Omega$, $C_L \leq 10pF$ Unless Otherwise Specified.

PARAMETER	TEMP	V+ = +5V, V- = 0V			V+ = +15V, V- = -15V			UNITS
		MIN	TYP	MAX	MIN	TYP	MAX	
INPUT CHARACTERISTICS								
Offset Voltage (Note 11)	+25°C		2	6		2	6	mV
	Full			8			8	mV
Average Offset Voltage Drift	Full		3			3		$\mu V/^{\circ}C$
Bias Current (Note 11)	+25°C		45	100		45	100	nA
	Full			125			125	nA
Offset Current (Note 11)	+25°C		0.3	10		0.3	10	nA
	Full			20			20	nA
Common Mode Range	Full	0 to 3			± 10			V
Differential Input Resistance	+25°C		0.6			0.6		M Ω
Input Noise Voltage (f = 1kHz)	+25°C		20			20		nV/\sqrt{Hz}
Input Noise Current (f = 1kHz)	+25°C		0.25			0.25		pA/\sqrt{Hz}
TRANSFER CHARACTERISTICS								
Large Signal Voltage Gain (Notes 2, 4)	+25°C	20k	100k		20k	100k		V/V
	Full	15k			15k			V/V
Common Mode Rejection Ratio (Note 7)	Full	77	105		77	105		dB
Bandwidth (Notes 2, 3)	+25°C		0.4			0.4		MHz
OUTPUT CHARACTERISTICS								
Output Voltage Swing (Notes 2, 10)	+25°C	1.0 to 3.8	0.7 to 4.2		± 10	± 13		V
	Full	1.2 to 3.5	0.9 to 4.0		± 10	± 13		V
Full Power Bandwidth (Notes 2, 4, 8)	+25°C		240			24		kHz
TRANSIENT RESPONSE (Notes 2, 3)								
Rise Time	+25°C		600			600		ns
Slew Rate (Note 6)	+25°C	0.8	1.5		0.8	1.5		V/ μs
Settling Time (Note 5)	+25°C		10			10		μs
POWER SUPPLY CHARACTERISTICS								
Supply Current	+25°C		45	80		100	150	$\mu A/Amp$
	Full			100			200	$\mu A/Amp$
Power Supply Rejection Ratio (Note 9)	Full	77	105		77	105		dB


NOTES:

- Absolute maximum ratings are limiting values, applied individually beyond which the serviceability of the circuit may be impaired. Functional operability under any of these conditions is not necessarily implied.
- $R_L = 50k\Omega$
- $C_L = 50pF$
- $V_O = 1.4$ to $2.5V$ for $V_{CC} = +5, 0V$; $V_O = \pm 10V$ for $V_{CC} = \pm 15V$.
- Settling Time is specified to 0.1% of final value for a 3V output step and $\Delta V = -1$ for $V_{CC} = +5V, 0V$. Output step = $10V$ for $V_{CC} = \pm 15V$.
- Maximum input slew rate = $10V/\mu s$.
- $V_{CM} = 0$ to $3V$ for $V_{CC} = +5, 0V$; $V_{CM} = \pm 10V$ for $V_{CC} = \pm 15V$
- Full Power Bandwidth is guaranteed by equation:

$$\text{Full Power Bandwidth} = \frac{\text{Slew Rate}}{2\pi V_{\text{Peak}}}$$
- $\Delta V_S = +10V$ for $V_{CC} = +5, 0V$; $\Delta V_S = \pm 5V$ for $V_{CC} = \pm 15V$.
- For $V_{CC} = +5, 0V$ terminate R_L at $+2.5V$. Typical output current is $\pm 3mA$.
- $V_O = 1.4V$ for $V_{CC} = +5V, 0V$.


Test Circuits

SLEW RATE AND TRANSIENT RESPONSE TEST CIRCUIT



LARGE SIGNAL RESPONSE


Vertical Scale: (Volts: Input = 5V/Div.; Output = 2V/Div.)
Horizontal Scale: (Time: 2μs/Div.)



+VSUPPLY = +15V, -VSUPPLY = -15V

SMALL SIGNAL RESPONSE


Vertical Scale: (Volts: Input = 100mV/Div.; Output = 50mV/Div.)
Horizontal Scale: (Time: 2μs/Div.)



+VSUPPLY = +15V, -VSUPPLY = -15V

LARGE SIGNAL RESPONSE


Vertical Scale: (Volts: Input = 2V/Div.; Output = 1V/Div.)
Horizontal Scale: (Time: 5μs/Div.)



+VSUPPLY = +5V, -VSUPPLY = 0V

SMALL SIGNAL RESPONSE


Vertical Scale: (Volts: Input = 100mV/Div.; Output = 50mV/Div.)
Horizontal Scale: (Time: 5μs/Div.)




+VSUPPLY = +5V, -VSUPPLY = 0V

Performance Curves $V_S = \pm 2.5V$, $T_A = +25^\circ C$ Unless Otherwise Specified


OPEN LOOP FREQUENCY RESPONSE




INPUT OFFSET CURRENT AND BIAS CURRENT vs. TEMPERATURE




BANDWIDTH AND PHASE MARGIN vs. LOAD CAPACITANCE




NORMALIZED AC PARAMETERS vs. SUPPLY VOLTAGE



OUTPUT VOLTAGE SWING vs. FREQUENCY AND SINGLE SUPPLY VOLTAGE




NORMALIZED AC PARAMETERS vs. TEMPERATURE




Performance Curves Continued $V_S = \pm 2.5V$, $T_A = +25^\circ C$ Unless Otherwise Specified


INPUT NOISE vs. FREQUENCY




MAXIMUM OUTPUT VOLTAGE SWING vs. LOAD RESISTANCE AND SINGLE SUPPLY VOLTAGE




PSRR AND CMRR vs. FREQUENCY




POWER SUPPLY CURRENT vs. TEMPERATURE AND SINGLE SUPPLY VOLTAGE



CHANNEL SEPARATION vs. FREQUENCY



Schematic



Die Characteristics

Transistor Count		
HA-5141	33
HA-5142	66
HA-5144	132
Substrate Potential*	V-
Process	Bipolar-DI
Thermal Constants (°C/W)		
	θ_{ja}	θ_{jc}
HA1-5144 (-2, -5, -7)	101	33
HA1-5144 (/883)	75	22
HA2-5141 (-2, -5, -7)	206	56
HA2-5141 (/883)	168	50
HA2-5142 (-2, -5, -7)	184	50
HA2-5142 (/883)	143	43
HA3-5141 (-5)	90	40
HA3-5142 (-5)	80	20
HA3-5144 (-5)	75	20
HA7-5141 (-2, -5, -7)	210	117
HA7-5141 (/883)	90	40
HA7-5142 (-2, -5, -7)	177	92
HA7-5142 (/883)	80	20

*The substrate may be left floating (Insulating Die Mount) or it may be mounted on a conductor at V- potential.

NOTE: Consult Harris for LCC/PLCC information.