

FEATURES

Low voltage noise density: 1.15 nV/ $\sqrt{\text{Hz}}$ at 1 kHz
Low distortion: –120 dB total harmonic distortion plus noise (THD + N) at 1 kHz
Peak-to-peak noise: 76 nV p-p at 0.1 Hz to 10 Hz
Slew rate: 15 V/ μs at $V_{\text{SY}} = \pm 15 \text{ V}$
Wide gain bandwidth product: 10 MHz
Supply current per amplifier: 5.0 mA typical at $V_{\text{SY}} = \pm 15 \text{ V}$
Low offset voltage: 10 μV typical at $V_{\text{SY}} = \pm 15 \text{ V}$
Common-mode rejection ratio (CMRR): 120 dB minimum
Unity-gain stable
Dual-supply operation: $\pm 15 \text{ V}$

ENHANCED PRODUCT FEATURES

Supports defense and aerospace applications (AQEC standard)
Extended temperature range: -55°C to $+125^{\circ}\text{C}$
Controlled manufacturing baseline
One assembly/test site
One fabrication site
Enhanced product change notification
Qualification data available on request

APPLICATIONS

Professional audio preamplifiers
ATE/precision testers
Imaging systems
Medical/physiological measurements
Precision detectors/instruments
Precision data conversions

GENERAL DESCRIPTION

The [AD8599-EP](#) is a very low noise, low distortion op amp ideal for use as a preamplifier. The low noise of 1.15 nV/ $\sqrt{\text{Hz}}$ and low harmonic distortion of –120 dB (or better) at audio bandwidths give the [AD8599-EP](#) the wide dynamic range necessary for preamplifiers in audio, medical, and instrumentation applications. The excellent slew rate of 15 V/ μs and 10 MHz gain bandwidth product make the [AD8599-EP](#) highly suitable for medical applications. The low distortion and fast settling time make the [AD8599-EP](#) ideal for buffering high resolution data converters.

PIN CONFIGURATION




Figure 1.

130065-001

The [AD8599-EP](#) is available in an 8-lead SOIC package. It is specified over a -55°C to $+125^{\circ}\text{C}$ temperature range.

Additional application and technical information can be found in the [AD8599](#) data sheet.

TABLE OF CONTENTS

Features	1	Absolute Maximum Ratings	4
Enhanced Product Features	1	Thermal Resistance	4
Applications	1	Power Sequencing	4
Pin Configuration	1	ESD Caution	4
General Description	1	Typical Performance Characteristics	5
Revision History	2	Outline Dimensions	8
Specifications	3	Ordering Guide	8

REVISION HISTORY

8/15—Revision 0: Initial Version

SPECIFICATIONS

$V_{SY} = \pm 15\text{ V}$, $V_{CM} = 0\text{ V}$, $V_O = 0\text{ V}$, $T_A = 25^\circ\text{C}$, unless otherwise specified.

Table 1.

Parameter	Symbol	Test Conditions/Comments	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Offset Voltage	V_{OS}	$-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$		10	120	μV
Offset Voltage Drift	$\Delta V_{OS}/\Delta T$	$-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$		0.8	300	$\mu\text{V}/^\circ\text{C}$
Input Bias Current	I_B	$-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$		25	200	nA
Input Offset Current	I_{OS}	$-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$		50	350	nA
Input Voltage Range	IVR	$-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	-12.5		350	nA
Common-Mode Rejection Ratio	CMRR	$-12.5\text{ V} \leq V_{CM} \leq +12.5\text{ V}$ $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	120	135	+12.5	V
Large Signal Voltage Gain	A_{VO}	$R_L \geq 600\ \Omega$, $V_O = -11\text{ V to } +11\text{ V}$ $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	115	116		dB
Input Capacitance						
Differential Capacitance	C_{DIFF}			12.1		pF
Common-Mode Capacitance	C_{CM}			5.1		pF
OUTPUT CHARACTERISTICS						
Output Voltage						
High	V_{OH}	$R_L = 600\ \Omega$ $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	13.1	13.4		V
		$R_L = 2\text{ k}\Omega$ $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	12.8	13.7		V
Low	V_{OL}	$R_L = 600\ \Omega$ $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	13.5			V
		$R_L = 2\text{ k}\Omega$ $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	13.2			V
Output Short-Circuit Current	I_{SC}			-13.2	-12.9	V
Closed-Loop Output Impedance	Z_{OUT}				-12.8	V
				-13.5	-13.4	V
					-13.3	V
				± 52		mA
				5		Ω
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	$V_{SY} = \pm 18\text{ V to } \pm 4.5\text{ V}$ $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	120	140		dB
Supply Current per Amplifier	I_{SY}	$-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$	118	5.0	5.7	dB
					6.75	mA
DYNAMIC PERFORMANCE						
Slew Rate	SR	$A_{VO} = -1$, $R_L = 2\text{ k}\Omega$ $A_{VO} = 1$, $R_L = 2\text{ k}\Omega$		16		V/ μs
Settling Time	t_S	To 0.01%, step = 10 V		15		V/ μs
Gain Bandwidth Product	GBP			2		μs
Phase Margin	Φ_M			10		MHz
				65		Degrees
NOISE PERFORMANCE						
Peak-to-Peak Noise	$e_n\text{ p-p}$	0.1 Hz to 10 Hz		76		nV p-p
Voltage Noise Density	e_n	$f = 1\text{ kHz}$		1.07	1.15	nV/ $\sqrt{\text{Hz}}$
		$f = 10\text{ Hz}$			1.5	nV/ $\sqrt{\text{Hz}}$
Correlated Current Noise		$f = 1\text{ kHz}$		1.9		pA/ $\sqrt{\text{Hz}}$
		$f = 10\text{ Hz}$		4.3		pA/ $\sqrt{\text{Hz}}$
Uncorrelated Current Noise		$f = 1\text{ kHz}$		2.3		pA/ $\sqrt{\text{Hz}}$
		$f = 10\text{ Hz}$		5.3		pA/ $\sqrt{\text{Hz}}$
Total Harmonic Distortion + Noise	THD + N	$G = 1$, $R_L \geq 1\text{ k}\Omega$, $f = 1\text{ kHz}$, $V_{RMS} = 3\text{ V}$		-120		dB
Channel Separation	CS	$f = 10\text{ kHz}$		-120		dB

ABSOLUTE MAXIMUM RATINGS

Table 2.

Parameter	Rating
Supply Voltage	$\pm 18\text{ V}$
Input Voltage	$-V \leq V_{\text{IN}} \leq +V$
Differential Input Voltage ¹	$\pm 1\text{ V}$
Output Short-Circuit to GND	Indefinite
Storage Temperature Range	-65°C to $+150^{\circ}\text{C}$
Operating Temperature Range	-55°C to $+125^{\circ}\text{C}$
Lead Temperature (Soldering 60 sec)	300°C
Junction Temperature	150°C

¹ If the differential input voltage exceeds 1 V, limit the current to 5 mA.

Stresses at or above those listed under Absolute Maximum Ratings may cause permanent damage to the product. This is a stress rating only; functional operation of the product at these or any other conditions above those indicated in the operational section of this specification is not implied. Operation beyond the maximum operating conditions for extended periods may affect product reliability.

THERMAL RESISTANCE

θ_{JA} is specified with the device soldered on a circuit board with its exposed paddle soldered to a pad (if applicable) on a 4-layer JEDEC standard PCB with zero air flow.

Table 3.

Package Type	θ_{JA}	θ_{JC}	Unit
8-Lead SOIC (R-8)	120	36	$^{\circ}\text{C}/\text{W}$

POWER SEQUENCING







Apply the op amp supplies simultaneously. The op amp supplies must be stable before any input signals are applied. In any case, the input current must be limited to 5 mA.







ESD CAUTION









ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.


TYPICAL PERFORMANCE CHARACTERISTICS

Figure 2. Input Offset Voltage (V_{OS}) Distribution, $V_{SY} = \pm 5V$ Figure 5. Input Offset Voltage (V_{OS}) Distribution, $V_{SY} = \pm 15V$ Figure 3. Input Offset Voltage Drift (TCV_{OS}) Distribution, $V_{SY} = \pm 5V$ Figure 6. Input Offset Voltage Drift (TCV_{OS}) Distribution, $V_{SY} = \pm 15V$ Figure 4. Supply Current (I_{SY}) vs. TemperatureFigure 7. Supply Current (I_{SY}) vs. Supply Voltage (V_{SY})

Figure 8. Input Bias Current (I_B) vs. Temperature, $V_{SY} = \pm 5 V$ Figure 11. Input Bias Current (I_B) vs. Temperature, $V_{SY} = \pm 15 V$ Figure 9. Input Bias Current (I_B) vs. Common-Mode Voltage (V_{CM})Figure 12. Input Offset Current (I_{OS}) vs. TemperatureFigure 10. Large Signal Voltage Gain (A_{VO}) vs. Temperature, $V_{SY} = \pm 5 V$ Figure 13. Large Signal Voltage Gain (A_{VO}) vs. Temperature

Figure 14. Output Short-Circuit Current (I_{SC}) vs. Temperature, $V_{SY} = \pm 5 V$ Figure 17. Output Short-Circuit Current (I_{SC}) vs. Temperature, $V_{SY} = \pm 15 V$ Figure 15. Output Saturation Voltage ($V_{CC} - V_{OH}$) vs. Temperature, $V_{SY} = \pm 5 V$ Figure 18. Output Saturation Voltage ($V_{CC} - V_{OH}$) vs. Temperature, $V_{SY} = \pm 15 V$ Figure 16. Output Saturation Voltage ($V_{EE} - V_{OL}$) vs. Temperature, $V_{SY} = \pm 5 V$ Figure 19. Output Saturation Voltage ($V_{EE} - V_{OL}$) vs. Temperature, $V_{SY} = \pm 15 V$

OUTLINE DIMENSIONS



COMPLIANT TO JEDEC STANDARDS MS-012-AA
CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS
(IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR
REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

Figure 20. 8-Lead Standard Small Outline Package [SOIC_N]
Narrow Body
(R-8)

Dimensions shown in millimeters and (inches)

012407-A

ORDERING GUIDE

Model ¹	Temperature Range	Package Description	Package Option
AD8599TRZ-EP	–55°C to +125°C	8-Lead Standard Small Outline Package [SOIC_N]	R-8
AD8599TRZ-EP-R7	–55°C to +125°C	8-Lead Standard Small Outline Package [SOIC_N]	R-8

¹ Z = RoHS Complaint Part.