

SN54ALS651 THRU SN54ALS654, SN54AS651, SN54AS652 SN74ALS651 THRU SN74ALS654, SN74AS651, SN74AS652 OCTAL BUS TRANSCEIVERS AND REGISTERS

D2661, DECEMBER 1983 - REVISED NOVEMBER 1985

- Bus Transceivers/Registers
- Independent Registers and Enables for A and B Buses
- Multiplexed Real-Time and Stored Data
- Choice of True and Inverting Data Paths
- Choice of 3-State or Open-Collector Outputs to A Bus
- Included Among the Package Options Are Compact 24-Pin 300-mil-Wide DIPs and Both 28-Pin Plastic and Ceramic Chip Carriers
- Dependable Texas Instruments Quality and Reliability

DEVICE	A OUTPUT	B OUTPUT	LOGIC
'ALS651, 'AS651	3 State	3 State	Inverting
'ALS652, 'AS652	3 State	3 State	True
'ALS653	Open Collector	3 State	Inverting
'ALS654	Open Collector	3 State	True

description

These devices consist of bus transceiver circuits, D-type flip-flops, and control circuitry arranged for multiplexed transmission of data directly from the data bus or from the internal storage registers. Enable GAB and $\bar{G}BA$ are provided to control the transceiver functions. SAB and SBA control pins are provided to select whether real-time or stored data is transferred. The circuitry used for select control will eliminate the typical decoding glitch which occurs in a multiplexer during the transition between stored and real-time data. A low input level selects real-time data, and a high selects stored data. The following examples demonstrate the four fundamental bus-management functions that can be performed with the octal bus transceivers and registers.


Data on the A or B data bus, or both, can be stored in the internal D flip-flops by low-to-high transitions at the appropriate clock pins (CAB or CBA) regardless of the select or enable control pins. When SAB and SBA are in the real-time transfer mode, it is also possible to store data without using the internal D-type flip-flops by simultaneously enabling GAB and $\bar{G}BA$. In this configuration each output reinforces its input. Thus, when all other data sources to the two sets of bus lines are at high impedance, each set of bus lines will remain at its last state.

The -1 versions of the SN74ALS651 through SN74ALS654 are identical to the standard versions except that the recommended maximum I_{OL} is increased to 48 milliamperes. There are no -1 versions of the SN54ALS651 through SN54ALS654.

The SN54' family is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74' family is characterized for operation from 0°C to 70°C .


SN54ALS', SN54AS' . . . JT PACKAGE
SN74ALS', SN74AS' . . . DW OR NT PACKAGE

(TOP VIEW)



SN54ALS', SN54AS' . . . FK PACKAGE
SN74ALS', SN74AS' . . . FN PACKAGE

(TOP VIEW)




NC No internal connection


2

LSI Devices

**SN54ALS651 THRU SN54ALS654, SN54AS651, SN54AS652
SN74ALS651 THRU SN74ALS654, SN74AS651, SN74AS652
OCTAL BUS TRANSCEIVERS AND REGISTERS**




**REAL-TIME TRANSFER
BUS B TO BUS A**




**REAL-TIME TRANSFER
BUS A TO BUS B**

2

LSI Devices



**STORAGE FROM
A AND/OR B**



**TRANSFER
STORED DATA
TO A AND/OR B**

SN54ALS651 THRU SN54ALS654, SN54AS651, SN54AS652 SN74ALS651 THRU SN74ALS654, SN74AS651, SN74AS652 OCTAL BUS TRANSCEIVERS AND REGISTERS

FUNCTION TABLE



INPUTS						DATA I/O		OPERATION OR FUNCTION	
GAB	G̅BA	CAB	CBA	SAB	SBA	A1 THRU A8	B1 THRU B8	'ALS651, 'ALS653 'AS651	'ALS652, 'ALS654 'AS652
L	H	H or L	H or L	X	X	Input	Input	Isolation	Isolation
L	H	.	.	X	X	Input	Input	Store A and B Data	Store A and B Data
X	H	.	H or L	X	X	Input	Unspecified [†]	Store A, Hold B	Store A, Hold B
H	H	.	.	X [‡]	X	Input	Output	Store A in both registers	Store A in both registers
L	X	H or L	.	X	X	Unspecified [†]	Input	Hold A, Store B	Hold A, Store B
L	L	.	.	X	X [‡]	Output	Input	Store B in both registers	Store B in both registers
L	L	X	X	X	L	Output	Input	Real-Time B̅ Data to A Bus	Real-Time B̅ Data to A Bus
L	L	X	H or L	X	H	Output	Input	Stored B̅ Data to A Bus	Stored B̅ Data to A Bus
H	H	X	X	L	X	Input	Output	Real-Time A̅ Data to B Bus	Real-Time A̅ Data to B Bus
H	H	H or L	X	H	X	Input	Output	Stored A̅ Data to B Bus	Stored A̅ Data to B Bus
H	L	H or L	H or L	H	H	Output	Output	Stored A̅ Data to B Bus and Stored B̅ Data to A Bus	Stored A̅ Data to B Bus and Stored B̅ Data to A Bus

[†]The data output functions may be enabled or disabled by various signals at the GAB or G̅BA inputs. Data input functions are always enabled, i.e., data at the bus pins will be stored on every low-to-high transition on the clock inputs.

[‡]Select control - L: clocks can occur simultaneously.

Select control - H: clocks must be staggered in order to load both registers.

logic diagrams (positive logic)







Pin numbers shown are for DW, JT, and NT packages.

2
LSI Devices

**SN54ALS651 THRU SN54ALS654, SN54AS651, SN54AS652
SN74ALS651 THRU SN74ALS654, SN74AS651, SN74AS652
OCTAL BUS TRANSCEIVERS AND REGISTERS**

logic symbols†

2
LSI Devices



†These symbols are in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.
Pin numbers shown are for DW, JT, and NT packages.

SN54ALS651, SN54ALS652, SN74ALS651, SN74ALS652

OCTAL BUS TRANSCEIVERS AND REGISTERS

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage: Control inputs	7 V
I/O ports	5.5 V
Operating free-air temperature range: SN54ALS651, SN54ALS652	–55 °C to 125 °C
SN74ALS651, SN74ALS652	0 °C to 70 °C
Storage temperature range	–65 °C to 150 °C

recommended operating conditions

		SN54ALS651 SN54ALS652			SN74ALS651 SN74ALS652			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage			0.8			0.8	V
I_{OH}	High-level output current			–12			–15	mA
I_{OL}	Low-level output current			12			24	mA
							48†	
f_{clock}	Clock frequency	0		35	0		40	MHz
t_w	Pulse duration	CBA or CAB high		14.5	12.5			ns
		CBA or CAB low		14.5	12.5			
t_{su}	Setup time before CAB† or CBA†	A or B		15	10			ns
t_h	Hold time after CAB† or CBA†	A or B		5	0			ns
T_A	Operating free-air temperature	–55		125	0		70	°C

† The extended condition applies if V_{CC} is maintained between 4.75 V and 5.25 V. The 48-mA limit applies for the SN74ALS651 – 1 and SN74ALS652 – 1 only.

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS		SN54ALS651 SN54ALS652			SN74ALS651 SN74ALS652			UNIT	
				MIN	TYP [‡]	MAX	MIN	TYP [‡]	MAX		
V _{IK}		V _{CC} = 4.5 V, I _I = –18 mA		–1.2			–1.2			V	
V _{OH}		V _{CC} = 4.5 V to 5.5 V, I _{OH} = –0.4 mA		V _{CC} – 2			V _{CC} – 2			V	
		V _{CC} = 4.5 V, I _{OH} = –3 mA		2.4 3.2			2.4 3.2				
		V _{CC} = 4.5 V, I _{OH} = –12 mA		2							
		V _{CC} = 4.5 V, I _{OH} = –15 mA					2				
V _{OL}		V _{CC} = 4.5 V, I _{OL} = 12 mA		0.25 0.4			0.25 0.4			V	
		V _{CC} = 4.5 V, I _{OL} = 24 mA					0.35 0.5				
		(I _{OL} = 48 mA for –1 versions)									
I _I	Control inputs	V _{CC} = 5.5 V, V _I = 7 V		0.1			0.1			mA	
	A or B ports	V _{CC} = 5.5 V, V _I = 5.5 V		0.1			0.1				
I _{IH}	Control inputs	V _{CC} = 5.5 V, V _I = 2.7 V		20			20			μA	
	A or B ports [§]			20			20				
I _{IL}	Control inputs	V _{CC} = 5.5 V, V _I = 0.4 V		–0.2			–0.2			mA	
	A or B ports [§]			–0.2			–0.2				
I _O [¶]		V _{CC} = 5.5 V, V _O = 2.25 V		–30 –112			–30 –112			mA	
I _{CC}	‘ALS651	V _{CC} = 5.5 V		Outputs high		42 68		42 68		mA	
				Outputs low		52 82		52 82			
				Outputs disabled		52 82		52 82			
	‘ALS652			Outputs high		47 76		47 76			
				Outputs low		55 88		55 88			
				Outputs disabled		55 88		55 88			

‡ All typical values are at $V_{CC} = 5$ V, $T_A = 25$ °C.

§ For I/O ports, the parameters I_{IH} and I_{IL} include the off-state output current.

¶ The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS} .

PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

TEXAS
INSTRUMENTS

POST OFFICE BOX 225012 • DALLAS, TEXAS 75265

SN54ALS651, SN54ALS652, SN74ALS651, SN74ALS652 **OCTAL BUS TRANSCEIVERS AND REGISTERS**

***ALS651 switching characteristics (see Note 1)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	VCC = 5 V, CL = 50 pF, R1 = 500 Ω, R2 = 500 Ω, TA = 25°C			VCC = 4.5 V to 5.5 V, CL = 50 pF, R1 = 500 Ω, R2 = 500 Ω, TA = MIN to MAX			UNIT	
			*ALS651			SN54ALS651		SN74ALS651		
			MIN	TYP	MAX	MIN	MAX	MIN		MAX
fmax			50			35		40		MHz
tPLH	CBA or CAB	A or B	20 27			10 38		10 32		ns
tPHL			11 15			5 21		5 17		
tPLH	A or B	B or A	9 13			4 20		4 18		ns
tPHL			5 8			2 12		2 10		
tPLH	SBA or SAB† (with A or B high)	A or B	24 31			13 45		13 38		ns
tPHL			13 18			7 25		7 21		
tPLH	SBA or SAB† (with A or B low)	A or B	15 20			8 30		8 25		ns
tPHL			13 18			7 25		7 21		
tPZH	G̅BA	A	12 16			5 22		5 20		ns
tPZL			11 15			5 21		5 18		
tPHZ	G̅BA	A	4 7			2 10		2 9		ns
tPLZ			7 10			3 16		3 12		
tPZH	GAB	B	14 19			7 25		7 22		ns
tPZL			13 18			7 25		7 21		
tPHZ	GAB	B	5 10			2 14		2 12		ns
tPLZ			7 10			2 20		2 14		

***ALS652 switching characteristics (see Note 1)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 5 V, C _L = 50 pF, R ₁ = 500 Ω, R ₂ = 500 Ω, T _A = 25°C			V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R ₁ = 500 Ω, R ₂ = 500 Ω, T _A = MIN to MAX				UNIT
			ALS652			SN54ALS652		SN74ALS652		
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
f _{max}			50			35		40		MHz
t _{PLH}	CBA or CAB	A or B	20 25			10 35		10 30		ns
t _{PHL}			11 15			5 20		5 17		
t _{PLH}	A or B	B or A	11 15			5 20		5 18		ns
t _{PHL}			8 10			3 15		3 12		
t _{PLH}	SBA or SAB [†] (with A or B high)	A or B	24 32			15 40		15 35		ns
t _{PHL}			13 17			6 23		6 20		
t _{PLH}	SBA or SAB [†] (with A or B low)	A or B	17 22			8 30		8 25		ns
t _{PHL}			13 17			5 24		5 20		
t _{PZH}	G̅BA	A	10 15			3 20		3 17		ns
t _{PZL}			10 14			5 22		5 18		
t _{PHZ}	G̅BA	A	6 8			1 12		1 10		ns
t _{PLZ}			10 13			2 20		2 16		
t _{PZH}	GAB	B	15 20			8 25		8 22		ns
t _{PZL}			12 16			6 21		6 18		
t _{PHZ}	GAB	B	6 8			1 12		1 10		ns
t _{PLZ}			10 13			2 21		2 16		

[†] These parameters are measured with the internal output state of the storage register opposite to that of the bus input.

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

PRODUCTION DATA documents contain information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage: All inputs and A I/O ports	7 V
B I/O ports	5.5 V
Operating free-air temperature range: SN54ALS653, SN54ALS654	– 55 °C to 125 °C
SN74ALS653, SN74ALS654	0 °C to 70 °C
Storage temperature range	– 65 °C to 150 °C

recommended operating conditions

		SN54ALS653 SN54ALS654			SN74ALS653 SN74ALS654			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage			0.8			0.8	V
V_{OH}	High-level output voltage	A ports		5.5	5.5		5.5	V
I_{OH}	High-level output current	B ports		– 12	– 15		– 15	mA
I_{OL}	Low-level output current			12	24		24	mA
					48 [†]		48 [†]	
f_{clock}	Clock frequency							MHz
t_w	Pulse duration	CBA or CAB high						ns
		CBA or CAB low						
t_{su}	Setup time before CAB [†] or CBA [†]	A or B						ns
t_h	Hold time after CAB [†] or CBA [†]	A or B						ns
T_A	Operating free-air temperature	– 55		125	0		70	°C

[†] The extended condition applies if V_{CC} is maintained between 4.75 V and 5.25 V. The 48-mA limit applies for the SN74ALS653 – 1 and SN74ALS654 – 1 only.



electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS		SN54ALS653 SN54ALS654			SN74ALS653 SN74ALS654			UNIT	
				MIN	TYP†	MAX	MIN	TYP†	MAX		
V _{IK}		V _{CC} = 4.5 V,	I _I = -18 mA	-1.5			-1.5			V	
V _{OH}	B ports	V _{CC} = 4.5 V to 5.5 V,	I _{OH} = -0.4 mA	V _{CC} -2			V _{CC} -2			V	
		V _{CC} = 4.5 V,	I _{OH} = -3 mA	2.4	3.2		2.4	3.2			
		V _{CC} = 4.5 V,	I _{OH} = -12 mA	2							
		V _{CC} = 4.5 V,	I _{OH} = -15 mA				2				
I _{OH}	A ports	V _{CC} = 4.5 V,	V _{OH} = 5.5 V	0.1			0.1			mA	
V _{OL}		V _{CC} = 4.5 V,	I _{OL} = 12 mA	0.25			0.4	0.25		0.4	V
		V _{CC} = 4.75 V,	I _{OL} = 24 mA					0.35		0.5	
		(I _{OL} = 48 mA for -1 versions)									
I _I	Control inputs	V _{CC} = 5.5 V,	V _I = 7 V	0.1			0.1			mA	
	A or B ports	V _{CC} = 5.5 V,	V _I = 5.5 V	0.1			0.1				
I _{IH}	Control inputs	V _{CC} = 5.5 V,	V _I = 2.7 V	20			20			μA	
	A or B ports‡			20			20				
I _{IL}	Control inputs	V _{CC} = 5.5 V,	V _I = 0.4 V	-0.1			-0.1			mA	
	A or B ports‡			-0.2			-0.2				
I _O †	B ports	V _{CC} = 5.5 V,	V _O = 2.25 V	-30	-112		-30	-112		mA	
I _{CC}	'ALS653	V _{CC} = 5.5 V	Outputs high	52			52			mA	
			Outputs low	57			57				
			Outputs disabled	58			58				
	'ALS654		Outputs high	60			60				
			Outputs low	68			68				
			Outputs disabled	68			68				

† All typical values are at $V_{CC} = 5 \text{ V}$, $T_A = 25^\circ\text{C}$.

‡ For I/P ports, the parameters I_{IH} and I_{IL} include the off-state output current.

§ The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS} .

2

LSI Devices

ALS653 switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 680 Ω, (A outputs) R ₁ = R ₂ = 500 Ω, (B outputs) T _A = MIN to MAX						UNIT
			SN54ALS653			SN74ALS653			
			MIN	TYP†	MAX	MIN	TYP†	MAX	
f _{max}									MHz
t _{PLH}	CBA	A	24			24			ns
t _{PHL}			15			15			
t _{PLH}	CAB	B	11			11			ns
t _{PHL}			13			13			
t _{PLH}	A	B	10			10			ns
t _{PHL}			12			12			
t _{PLH}	B	A	24			24			ns
t _{PHL}			10			10			
t _{PLH}	SBA [†] (with B high)	A	26			26			ns
t _{PHL}			15			15			
t _{PLH}	SBA [†] (with B low)	A	26			26			ns
t _{PHL}			15			15			
t _{PLH}	SAB [†] (with A high)	B	16			16			ns
t _{PHL}			16			16			
t _{PLH}	SAB [†] (with A low)	B	15			15			ns
t _{PHL}			15			15			
t _{PLH}	GBA	A	24			24			ns
t _{PHL}			17			17			
t _{PZH}	GAB	B	19			19			ns
t _{PZL}			22			22			
t _{PHZ}	GAB	B	12			12			ns
t _{PLZ}			14			14			

† All typical values are at V_{CC} = 5 V, T_A = 25°C.

‡ These parameters are measured with the internal output state of the storage register opposite to that of the bus input.

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

Additional information on these products can be obtained from the factory as it becomes available.

2

LSI Devices

'ALS654 switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 680 Ω, (A outputs) R ₁ = R ₂ = 500 Ω, (B outputs) T _A = MIN to MAX						UNIT
			SN54ALS654			SN74ALS654			
			MIN	TYP†	MAX	MIN	TYP†	MAX	
f _{max}									MHz
t _{PLH}	CBA	A	24			24			ns
t _{PHL}			15			15			
t _{PLH}	CAB	B	11			11			ns
t _{PHL}			13			13			
t _{PLH}	A	B	8			8			ns
t _{PHL}			8			8			
t _{PLH}	B	A	24			24			ns
t _{PHL}			10			10			
t _{PLH}	SBA‡ (with B high)	A	26			26			ns
t _{PHL}			15			15			
t _{PLH}	SBA‡ (with B low)	A	26			26			ns
t _{PHL}			15			15			
t _{PLH}	SBA‡ (with A high)	B	16			16			ns
t _{PHL}			16			16			
t _{PLH}	SAB‡ (with A low)	B	15			15			ns
t _{PHL}			12			12			
t _{PLH}	G̅BA	A	24			24			ns
t _{PHL}			17			17			
t _{PZH}	GAB	B	19			19			ns
t _{PZL}			22			22			
t _{PHZ}	GAB	B	12			12			ns
t _{PLZ}			14			14			

† All typical values are at V_{CC} = 5 V, T_A = 25°C.

‡ These parameters are measured with the internal output state of the storage register opposite to that of the bus input.

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

Additional information on these products can be obtained from the factory as it becomes available.

SN54AS651, SN54AS652, SN74AS651, SN74AS652

OCTAL BUS TRANSCEIVERS AND REGISTERS

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage: Control inputs	7 V
I/O ports	5.5 V
Operating free-air temperature range: SN54AS651, SN54AS652	-55 °C to 125 °C
SN74AS651, SN74AS652	0 °C to 70 °C
Storage temperature range	-65 °C to 150 °C

recommended operating conditions

			SN54AS651 SN54AS652			SN74AS651 SN74AS652			UNIT
			MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage		4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage		2			2			V
V_{IL}	Low-level input voltage				0.8			0.8	V
I_{OH}	High-level output current				-12			-15	mA
I_{OL}	Low-level output current				32			48	mA
f_{clock}			0		75	0		90	MHz
t_w	Pulse duration	CBA or CAB high	6			5			ns
		CBA or CAB low	7			6			
t_{su}	Setup time before CAB [†] or CBA [†]	A or B	7			6			ns
t_h	Hold time after CAB [†] or CBA [†]	A or B	0			0			ns
T_A	Operating free-air temperature		-55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS		SN54AS651 SN54AS652			SN74AS651 SN74AS652			UNIT
				MIN	TYP†	MAX	MIN	TYP†	MAX	
V _{IK}		V _{CC} = 4.5 V,	I _I = -18 mA			-1.2			-1.2	V
V _{OH}		V _{CC} = 4.5 V to 5.5 V,	I _{OH} = -2 mA	V _{CC} -2			V _{CC} -2			V
		V _{CC} = 4.5 V,	I _{OH} = -3 mA	2.4	3.2		2.4	3.2		
		V _{CC} = 4.5 V,	I _{OH} = -12 mA	2						
		V _{CC} = 4.5 V,	I _{OH} = -15 mA				2			
V _{OL}		V _{CC} = 4.5 V,	I _{OL} = 32 mA		0.25	0.50				V
		V _{CC} = 4.5 V,	I _{OL} = 48 mA					0.35	0.50	
I _I	Control inputs	V _{CC} = 5.5 V,	V _I = 7 V			0.1			0.1	mA
	A or B ports	V _{CC} = 5.5 V,	V _I = 5.5 V			0.1			0.1	
I _{IH}	Control inputs	V _{CC} = 5.5 V,	V _I = 2.7 V			20			20	μA
	A or B ports‡					70		70		
I _{IL}	Control inputs	V _{CC} = 5.5 V,	V _I = 0.4 V			-0.5			-0.5	mA
	A or B ports‡					-0.75		-0.75		
I _O §		V _{CC} = 5.5 V,	V _O = 2.25 V	-30		-112	-30		-112	mA
I _{CC}	'AS651	V _{CC} = 5.5 V	Outputs high		110	185		110	185	mA
			Outputs low		120	195		120	195	
			Outputs disabled		130	195		130	195	
	'AS652		Outputs high		120	195		120	195	
			Outputs low		130	211		130	211	
			Outputs disabled		130	211		130	211	

[†]All typical values are at $V_{CC} = 5 \text{ V}$, $T_A = 25^\circ\text{C}$.

[‡]For I/O ports, the parameters I_{IH} and I_{IL} include the off-state output current.

^{\S}The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS} .

PRODUCTION DATA documents contain information current as of publication date. Products conform to these specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.



POST OFFICE BOX 225012 • DALLAS, TEXAS 75265

SN54AS651, SN54AS654, SN74AS651, SN74AS652 **OCTAL BUS TRANSCEIVERS AND REGISTERS**

***AS651 switching characteristics (see Note 1)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R ₁ = 500 Ω, R ₂ = 500 Ω, T _A = MIN to MAX				UNIT
			SN54AS651		SN74AS651		
			MIN	MAX	MIN	MAX	
f _{max}			75		90		MHz
t _{PLH}	CBA or CAB	A or B	2	9.5	2	8.5	ns
t _{PHL}			2	10	2	9	
t _{PLH}	A or B	B or A	2	9	2	8	ns
t _{PHL}			1	8	1	7	
t _{PLH}	SBA or SAB [†]	A or B	2	12	2	11	ns
t _{PHL}			2	10	2	9	
t _{PZH}	$\bar{G}$ BA	A	2	11	2	10	ns
t _{PZL}			3	18	3	16	
t _{PHZ}	$\bar{G}$ BA	A	2	10	2	9	ns
t _{PLZ}			2	10	2	9	
t _{PZH}	GAB	B	3	12	3	11	ns
t _{PZL}			3	20	3	16	
t _{PHZ}	GAB	B	2	11	2	10	ns
t _{PLZ}			2	12	2	11	

***AS652 switching characteristics (see Note 1)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R ₁ = 500 Ω, R ₂ = 500 Ω, T _A = MIN to MAX				UNIT
			SN54AS652		SN74AS652		
			MIN	MAX	MIN	MAX	
f _{max}			75		90		MHz
t _{PLH}	CBA or CAB	A or B	2	9.5	2	8.5	ns
t _{PHL}			2	10	2	9	
t _{PLH}	A or B	B or A	2	11	2	9	ns
t _{PHL}			1	8	1	7	
t _{PLH}	SBA or SAB†	A or B	2	12	2	11	ns
t _{PHL}			2	10	2	9	
t _{PZH}	G̅BA	A	2	11	2	10	ns
t _{PZL}			3	18	3	16	
t _{PHZ}	G̅BA	A	2	10	2	9	ns
t _{PLZ}			2	10	2	9	
t _{PZH}	GAB	B	3	12	3	11	ns
t _{PZL}			3	20	3	16	
t _{PHZ}	GAB	B	2	11	2	10	ns
t _{PLZ}			2	12	2	11	

† These parameters are measured with the internal output state of the storage register opposite to that of the bus input.

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.