

Section 14 Electrical Specifications

14.1 Absolute Maximum Ratings

Table 14-1 lists the absolute maximum ratings.

Table 14-1. Absolute Maximum Ratings (Preliminary)

Item	Symbol	Rating	Unit
Supply voltage	V_{CC}	-0.3 to +7.0	V
Programming voltage	V_{PP}	-0.3 to +13.5	V
Input voltage	Ports 1-6	V_{IN}	-0.3 to $V_{CC} + 0.3$
	Port 7	V_{IN}	-0.3 to $AV_{CC} + 0.3$
Analog supply voltage	AV_{CC}	-0.3 to +7.0	V
Analog input voltage	V_{AN}	-0.3 to $AV_{CC} + 0.3$	V
Operating temperature	T_{opr}	Regular specifications:	-20 to +75 °C
		Wide-range specifications:	-40 to +85 °C
Storage temperature	T_{stg}	-55 to +125	°C

Note: Exceeding the absolute maximum ratings shown in table 14-1 can permanently destroy the chip.

14.2 Electrical Characteristics

14.2.1 DC Characteristics

Table 14-2 lists the DC characteristics of the 5V versions of the H8/329 Series. Table 14-3 lists the DC characteristics of the 3V versions. Table 14-4 gives the allowable current output values of the 5V versions. Table 14-5 gives the allowable current output values of the 3V versions.

Table 14-2. DC Characteristics (5V Versions) (Preliminary)

Conditions: $V_{CC} = 5.0V \pm 10\%$, $AV_{CC} = 5.0V \pm 10\%$ *, $V_{SS} = AV_{SS} = 0V$,
 $T_A = -20$ to $75^\circ C$ (regular specifications), $T_A = -40$ to $85^\circ C$ (wide-range specifications)

Item		Symbol	Min	Typ	Max	Unit	Measurement conditions
Schmitt trigger input voltage (1)	P67-P62, P60, P47, P44-P40	V_{T-}	1.0	—	—	V	
		V_{T+}	—	—	$V_{CC} \times 0.7$	V	
		$V_{T+} - V_{T-}$	0.4	—	—	V	
Input High voltage (2)	<u>RES, STBY, NMI</u> MD1, MD0 EXTAL	V_{IH}	$V_{CC} - 0.7$	—	$V_{CC} + 0.3$	V	
	P77-P70		2.0	—	$AV_{CC} + 0.3$	V	
Input High voltage	Input pins other than (1) and (2) above	V_{IH}	2.0	—	$V_{CC} + 0.3$	V	
Input Low voltage (3)	<u>RES, STBY</u> MD1, MD0	V_{IL}	-0.3	—	0.5	V	
Input Low voltage	Input pins other than (1) and (3) above	V_{IL}	-0.3	—	0.8	V	
Output High voltage	All output pins	V_{OH}	$V_{CC} - 0.5$	—	—	V	$I_{OH} = -200 \mu A$
			3.5	—	—	V	$I_{OH} = -1.0 \text{ mA}$
Output Low voltage	All output pins	V_{OL}	—	—	0.4	V	$I_{OL} = 1.6 \text{ mA}$
	Ports 1 and 2		—	—	1.0	V	$I_{OL} = 10.0 \text{ mA}$
Input leakage current	<u>RES</u>	$ I_{in} $	—	—	10.0	μA	$V_{IN} = 0.5V$ to $V_{CC} - 0.5V$
	<u>STBY, NMI, MD1, MD0</u>		—	—	1.0	μA	
	P77-P70		—	—	1.0	μA	$V_{IN} = 0.5V$ to $AV_{CC} - 0.5V$
Leakage current in 3-state (off state)	Ports 1, 2, 3 4, 5, 6	$ I_{TSI} $	—	—	1.0	μA	$V_{IN} = 0.5V$ to $V_{CC} - 0.5V$
Input pull-up MOS current	Ports 1, 2, 3	$-I_p$	30	—	250	μA	$V_{IN} = 0V$

Note: * Connect AV_{CC} to the power supply (+5V) even when the A/D converter is not used.

Table 14-2. DC Characteristics (5V Versions) (Preliminary) (cont.)

Conditions: $V_{CC} = 5.0V \pm 10\%$, $AV_{CC} = 5.0V \pm 10\%$ *1, $V_{SS} = AV_{SS} = 0V$, $T_A = -20$ to $75^\circ C$ (regular specifications), $T_A = -40$ to $85^\circ C$ (wide-range specifications)

Item		Symbol	Min	Typ	Max	Unit	Measurement conditions
Input capacitance	RES	C _{IN}	—	—	60	pF	V _{IN} = 0V
	NMI		—	—	30	pF	f = 1 MHz
	All input pins except RES and NMI		—	—	15	pF	T _A = 25°C
Current dissipation*2	Normal operation	I _{CC}	—	12	25	mA	f = 6 MHz
			—	16	30	mA	f = 8 MHz
			—	20	40	mA	f = 10 MHz
	Sleep mode		—	8	15	mA	f = 6 MHz
			—	10	20	mA	f = 8 MHz
			—	12	25	mA	f = 10 MHz
	Standby modes*3		—	0.01	5.0	μA	
Analog supply current	During A/D conversion	A _I CC	—	0.6	1.5	mA	
	Waiting		—	0.01	5.0	μA	
RAM standby voltage		V _{RAM}	2.0	—	—	V	

Notes: *1 Connect AV_{CC} to the power supply (+5V) even when the A/D converter is not used.

*2 Current dissipation values assume that $V_{IH\text{ min}} = V_{CC} - 0.5V$, $V_{IL\text{ max}} = 0.5V$, all output pins are in the no-load state, and all input pull-up transistors are off.

*3 For these values it is assumed that $V_{RAM} \leq V_{CC} < 4.5V$ and $V_{IH\text{ min}} = V_{CC} \times 0.9$, $V_{IL\text{ max}} = 0.3V$.

Table 14-3. DC Characteristics (3V Versions) (Preliminary)

Conditions: $V_{CC} = 3.0V \pm 10\%$, $AV_{CC} = 5.0V \pm 10\%$ *1, $V_{SS} = AV_{SS} = 0V$, $T_A = -20$ to $75^\circ C$

Item		Symbol	Min	Typ	Max	Unit	Measurement conditions
Schmitt trigger input voltage*2 (1)	P67-P62, P60,	V_{T-}	$V_{CC} \times 0.15$	—	—	V	
	P47, P44-P40	V_{T+}	—	—	$V_{CC} \times 0.7$	V	
		$V_{T+} - V_{T-}$	0.2	—	—	V	
Input High voltage*2 (2)	RES, STBY MD1, MD0 EXTAL, NMI	V_{IH}	$V_{CC} \times 0.9$	—	$V_{CC} + 0.3$	V	
	P77-P70		$V_{CC} \times 0.7$	—	$AV_{CC} + 0.3$	V	
	Input pins other than (1) and (2) above		$V_{CC} \times 0.7$	—	$V_{CC} + 0.3$	V	
Input Low voltage*2 (3)	RES, STBY MD1, MD0	V_{IL}	-0.3	—	$V_{CC} \times 0.1$	V	
	Input pins other than (1) and (3) above		-0.3	—	$V_{CC} \times 0.15$	V	
Output High voltage	All output pins	V_{OH}	$V_{CC} - 0.4$	—	—	V	$I_{OH} = -200 \mu A$
			$V_{CC} - 0.9$	—	—	V	$I_{OH} = -1 \text{ mA}$
Output Low voltage	All output pins	V_{OL}	—	—	0.4	V	$I_{OL} = 0.8 \text{ mA}$
	Ports 1 and 2		—	—	0.4	V	$I_{OL} = 1.6 \text{ mA}$
Input leakage current	RES	$ I_{IN} $	—	—	10.0	μA	$V_{IN} = 0.5$ to $V_{CC} - 0.5V$
	STBY, NMI, MD1, MD0		—	—	1.0	μA	
	P77-P70		—	—	1.0	μA	$V_{IN} = 0.5$ to $AV_{CC} - 0.5V$
Leakage current in 3-state (off state)	Ports 1, 2, 3 4, 5, 6	$ I_{TSI} $	—	—	1.0	μA	$V_{IN} = 0.5$ to $V_{CC} - 0.5V$
Input pull-upMOS current	Ports 1, 2, 3	$-I_P$	3	—	120	μA	$V_{IN} = 0V$

Notes: *1 Connect AV_{CC} to the power supply (+3V) even when the A/D converter is not used.

*2 In the range $3.3V < V_{CC} < 4.5V$, for the input levels of V_{IH} and V_T , apply the higher of the values given for the 5V and 3V versions. For V_{IL} and V_{T-} , apply the lower of the values given for the 5V and 3V versions.

Table 14-3. DC Characteristics (3V Versions) (Preliminary) (cont.)

Conditions: $V_{CC} = 3.0V \pm 10\%$, $AV_{CC} = 5.0V \pm 10\%$ *1, $V_{SS} = AV_{SS} = 0V$, $T_A = -20$ to $70^\circ C$

Item		Symbol	Min	Typ	Max	Unit	Measurement conditions
Input capacitance	RES	C_{IN}	—		60	pF	$V_{IN} = 0V$
	NMI		—	—	30	pF	$f = 1\text{ MHz}$
	All input pins except RES and NMI		—	—	15	pF	$T_A = 25^\circ C$
Current dissipation*2	Normal operation	I_{CC}	—	4	—	mA	$f = 3\text{ MHz}$
			—	6	12	mA	$f = 5\text{ MHz}$
	Sleep mode		—	3	—	mA	$f = 3\text{ MHz}$
			—	4	8	mA	$f = 5\text{ MHz}$
	Standby modes*3		—	0.01	5.0	μA	
Analog supply current	During A/D conversion	AI_{CC}	—	0.6	1.5	mA	
	Waiting		—	0.01	5.0	μA	
RAM backup voltage (in standby modes)		V_{RAM}	2.0	—	—	V	

Notes: *1 Connect AV_{CC} to the power supply (+3V) even when the A/D converter is not used.

*2 Current dissipation values assume that $V_{IH\text{ min.}} = V_{CC} - 0.5V$, $V_{IL\text{ max.}} = 0.5V$, all output pins are in the no-load state, and all input pull-up transistors are off.

*3 For these values it is assumed that $V_{RAM} \leq V_{CC} < 2.7V$ and $V_{IH\text{ min.}} = V_{CC} \times 0.9$, $V_{IL\text{ max.}} = 0.3V$.

Table 14-4. Allowable Output Current Sink Values (5V Versions) (Preliminary)

Conditions: $V_{CC} = 5.0V \pm 10\%$, $AV_{CC} = 5.0V \pm 10\%$, $V_{SS} = AV_{SS} = 0V$, $T_A = -20$ to $75^\circ C$ (regular specifications), $T_A = -40$ to $85^\circ C$ (wide-range specifications)

Item		Symbol	Min	Typ	Max	Unit
Allowable output Low current sink (per pin)	Ports 1 and 2	I_{OL}	—	—	10	mA
	Other output pins		—	—	2.0	mA
Allowable output Low current sink (total)	Ports 1 and 2, total	ΣI_{OL}	—	—	80	mA
	Total of all output		—	—	120	mA
Allowable output High current sink (per pin)	All output pins	$-I_{OH}$	—	—	2.0	mA
Allowable output High current sink (total)	Total of all output pins	$\Sigma -I_{OH}$	—	—	40	mA

Table 14-5. Allowable Output Current Sink Values (3V Versions) (Preliminary)

Conditions: $V_{CC} = 3.0V \pm 10\%$, $AV_{CC} = 5.0V \pm 10\%$, $V_{SS} = AV_{SS} = 0V$, $T_A = -20$ to $75^\circ C$

Item		Symbol	Min	Typ	Max	Unit
Allowable output Low current sink (per pin)	Ports 1 and 2	I_{OL}	—	—	2	mA
	Other output pins		—	—	1	mA
Allowable output Low current sink (total)	Ports 1 and 2, total	ΣI_{OL}	—	—	40	mA
	All output pins		—	—	60	mA
Allowable output High current sink (per pin)	All output pins	$-I_{OH}$	—	—	2	mA
Allowable output High current sink (total)	Total of all output pins	$\Sigma -I_{OH}$	—	—	30	mA

Note: To avoid degrading the reliability of the chip, be careful not to exceed the output current sink values in tables 14-4 and 14-5. In particular, when driving a Darlington transistor pair or LED directly, be sure to insert a current-limiting resistor in the output path. See figures 14-1 and 14-2.




Figure 14-1. Example of Circuit for Driving a Darlington Pair (5V Versions)




Figure 14-2. Example of Circuit for Driving an LED (5V Versions)

14.2.2 AC Characteristics

The AC characteristics of the H8/329 Series are listed in three tables. Bus timing parameters are given in table 14-6, control signal timing parameters in table 14-7, and timing parameters of the on-chip supporting modules in table 14-8.

Table 14-6. Bus Timing (Preliminary)

Condition A: $V_{CC} = 5.0V \pm 10\%$, $V_{SS} = 0V$, $\phi = 0.5$ MHz to maximum operating frequency,

$T_A = -20$ to $75^\circ C$ (regular specifications),

$T_A = -40$ to $85^\circ C$ (wide-range specifications)

Condition B: $V_{CC} = 3.0V \pm 10\%$, $V_{SS} = 0V$, $\phi = 0.5$ MHz to maximum operating frequency,

$T_A = -20$ to $75^\circ C$

Item	Symbol	Condition B		Condition A								Unit	Measurement conditions
		5 MHz		6 MHz		8 MHz		10 MHz					
		Min	Max	Min	Max	Min	Max	Min	Max				
Clock cycle time	t _{cyc}	200	2000	166.7	2000	125	2000	100	2000	ns	Fig. 14-4		
Clock pulse width Low	t _{CL}	70	—	65	—	45	—	35	—	ns	Fig. 14-4		
Clock pulse width High	t _{CH}	70	—	65	—	45	—	35	—	ns	Fig. 14-4		
Clock rise time	t _{Cr}	—	25	—	15	—	15	—	15	ns	Fig. 14-4		
Clock fall time	t _{Cf}	—	25	—	15	—	15	—	15	ns	Fig. 14-4		
Address delay time	t _{AD}	—	90	—	70	—	60	—	50	ns	Fig. 14-4		
Address hold time	t _{AH}	30	—	30	—	25	—	20	—	ns	Fig. 14-4		
Address strobe delay time	t _{ASD}	—	80	—	70	—	60	—	40	ns	Fig. 14-4		
Write strobe delay time	t _{WSD}	—	80	—	70	—	60	—	50	ns	Fig. 14-4		
Strobe delay time	t _{SD}	—	90	—	70	—	60	—	50	ns	Fig. 14-4		
Write strobe pulse width*	t _{WSW}	200	—	200	—	150	—	120	—	ns	Fig. 14-4		
Address setup time 1*	t _{AS1}	25	—	25	—	20	—	15	—	ns	Fig. 14-4		
Address setup time 2*	t _{AS2}	105	—	105	—	80	—	65	—	ns	Fig. 14-4		
Read data setup time	t _{RDS}	90	—	70	—	50	—	35	—	ns	Fig. 14-4		
Read data hold time	t _{RDH}	0	—	0	—	0	—	0	—	ns	Fig. 14-4		
Read data access time*	t _{ACC}	—	300	—	270	—	210	—	170	ns	Fig. 14-4		
Write data delay time	t _{WDD}	—	125	—	85	—	75	—	75	ns	Fig. 14-4		
Write data setup time	t _{WDS}	10	—	20	—	10	—	5	—	ns	Fig. 14-4		
Write data hold time	t _{WDH}	30	—	30	—	25	—	20	—	ns	Fig. 14-4		
Wait setup time	t _{WTS}	60	—	40	—	40	—	40	—	ns	Fig. 14-5		
Wait hold time	t _{WTH}	20	—	10	—	10	—	10	—	ns	Fig. 14-5		

Note: * Values at maximum operating frequency

Table 14-7. Control Signal Timing (Preliminary)

Condition A: $V_{CC} = 5.0V \pm 10\%$, $V_{SS} = 0V$, $\phi = 0.5$ MHz to maximum operating frequency,

$T_A = -20$ to 75°C (regular specifications),

$T_A = -40$ to 85°C (wide-range specifications)

Condition B: $V_{CC} = 3.0V \pm 10\%$, $V_{SS} = 0V$, $\phi = 0.5$ MHz to maximum operating frequency,

$T_A = -20$ to 75°C

Item	Symbol	Condition B		Condition A								Unit	Measurement conditions
		5 MHz		6 MHz		8 MHz		10 MHz					
		Min	Max	Min	Max	Min	Max	Min	Max				
RES setup time	t _{RESS}	300	—	200	—	200	—	200	—	ns	Fig. 14-6		
RES pulse width	t _{RESW}	10	—	10	—	10	—	10	—	t _{CYC}	Fig. 14-6		
NMI setup time (NMI, IRQ ₀ to IRQ ₂)	t _{NMIS}	300	—	150	—	150	—	150	—	ns	Fig. 14-7		
NMI hold time (NMI, IRQ ₀ to IRQ ₂)	t _{NMIH}	10	—	10	—	10	—	10	—	ns	Fig. 14-7		
Interrupt pulse width for recovery from soft- ware standby mode (NMI, IRQ ₀ to IRQ ₂)	t _{NMIW}	300	—	200	—	200	—	200	—	ns	Fig. 14-7		
Crystal oscillator settling time (reset)	t _{osc1}	20	—	20	—	20	—	20	—	ms	Fig. 14-8		
Crystal oscillator settling time (software standby)	t _{OSC2}	10	—	10	—	10	—	10	—	ms	Fig. 14-9		

Table 14-8. Timing Conditions of On-Chip Supporting Modules (Preliminary)Condition A: $V_{CC} = 5.0V \pm 10\%$, $V_{SS} = 0V$, $\phi = 0.5$ MHz to maximum operating frequency, $T_A = -20$ to 75°C (regular specifications), $T_A = -40$ to 85°C (wide-range specifications)Condition B: $V_{CC} = 3.0V \pm 10\%$, $V_{SS} = 0V$, $\phi = 0.5$ MHz to maximum operating frequency,

Item		Symbol	Condition B		Condition A								Unit	Measurement conditions
			Min	Max	5 MHz		6 MHz		8 MHz		10 MHz			
FRT	Timer output delay time	t _{FOD}	—	150	—	100	—	100	—	100	—	100	ns	Fig. 14-10
	Timer input setup time	t _{FIS}	80	—	50	—	50	—	50	—	50	—	ns	Fig. 14-10
	Timer clock input setup time	t _{FTCS}	80	—	50	—	50	—	50	—	50	—	ns	Fig. 4-11
	Timer clock pulse width	t _{FTWCH} t _{FTCWL}	1.5	—	1.5	—	1.5	—	1.5	—	1.5	—	t _{CYC}	Fig. 4-11
TMR	Timer output delay time	t _{TMOD}	—	150	—	100	—	100	—	100	—	100	ns	Fig. 14-12
	Timer reset input setup time	t _{TMRS}	80	—	50	—	50	—	50	—	50	—	ns	Fig. 14-14
	Timer clock input setup time	t _{TMCS}	80	—	50	—	50	—	50	—	50	—	ns	Fig. 14-13
	Timer clock pulse width (single edge)	t _{TMCHW}	1.5	—	1.5	—	1.5	—	1.5	—	1.5	—	t _{CYC}	Fig. 14-13
	Timer clock pulse width (both edges)	t _{TMCLW}	2.5	—	2.5	—	2.5	—	2.5	—	2.5	—	t _{CYC}	Fig. 14-13
SCI	Input clock cycle	(Async) t _{SCYC}	2	—	2	—	2	—	2	—	2	—	t _{CYC}	Fig. 14-15
		(Sync) t _{SCYC}	6	—	6	—	6	—	6	—	6	—	t _{CYC}	Fig. 14-15
	Transmit data delay time (Sync)	t _{TXD}	—	200	—	100	—	100	—	100	—	100	ns	Fig. 14-15
	Receive data setup time (Sync)	t _{RXS}	150	—	100	—	100	—	100	—	100	—	ns	Fig. 14-15
	Receive data hold time (Sync)	t _{RXH}	150	—	100	—	100	—	100	—	100	—	ns	Fig. 14-15
	Input clock pulse width	t _{SCKW}	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	t _{SCYC}	Fig. 14-16
Ports	Output data delay time	t _{PWD}	—	150	—	100	—	100	—	100	—	100	ns	Fig. 14-17
	Input data setup time	t _{PRS}	80	—	50	—	50	—	50	—	50	—	ns	Fig. 14-17
	Input data hold time	t _{PRH}	80	—	50	—	50	—	50	—	50	—	ns	Fig. 14-17

• Measurement Conditions for AC Characteristics




Figure 14-3. Output Load Circuit

14.2.3 A/D Converter Characteristics

Table 14-9 lists the characteristics of the on-chip A/D converter.

Table 14-9. A/D Converter Characteristics (Preliminary)

Condition A: $V_{CC} = AV_{CC} = 5.0\text{V} \pm 10\%$, $V_{SS} = AV_{SS} = 0\text{V}$, $\phi = 0.5 \text{ MHz}$ to maximum operating frequency, $T_A = -20$ to 75°C (regular specifications),

$T_A = -40$ to 85°C (wide-range specifications)

Condition B: $V_{CC} = 3.0\text{V} \pm 10\%$, $AV_{CC} = 5.0\text{V} \pm 10\%$, $V_{SS} = AV_{SS} = 0\text{V}$, $\phi = 0.5 \text{ MHz}$ to maximum operating frequency, $T_A = -20$ to 75°C

Item	Condition B						Condition A						Measurement Unit
	5 MHz			6 MHz			8 MHz			10 MHz			
	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
Resolution	8	8	8	8	8	8	8	8	8	8	8	8	Bits
Conversion time (single mode)*	—	—	24.4	—	—	20.4	—	—	15.25	—	—	12.2	μs
Analog input capacitance	—	—	20	—	—	20	—	—	20	—	—	20	pF
Allowable signal source impedance	—	—	10	—	—	10	—	—	10	—	—	10	kΩ
Nonlinearity error	—	—	±1	—	—	±1	—	—	±1	—	—	±1	LSB
Offset error	—	—	±1	—	—	±1	—	—	11	—	—	±1	LSB
Full-scale error	—	—	±1	—	—	±1	—	—	±1	—	—	±1	LSB
Quantizing error	—	—	±0.5	—	—	±0.5	—	—	±0.5	—	—	±0.5	LSB
Absolute accuracy	—	—	±1.5	—	—	±1.5	—	—	±1.5	—	—	±1.5	LSB

Note: * At maximum operating frequency

14.3 MCU Operational Timing

This section provides the following timing charts:

14.3.1 Bus Timing	Figures 14-4 to 14-5
14.3.2 Control Signal Timing	Figures 14-6 to 14-9
14.3.3 16-Bit Free-Running Timer Timing	Figures 14-10 to 14-11
14.3.4 8-Bit Timer Timing	Figures 14-12 to 14-14
14.3.5 SCI Timing	Figures 14-15 to 14-16
14.3.6 I/O Port Timing	Figure 14-17

14.3.1 Bus Timing

(1) Basic Bus Cycle (without Wait States) in Expanded Modes




Figure 14-4. Basic Bus Cycle (without Wait States) in Expanded Modes

(2) Basic Bus Cycle (with 1 Wait State) in Expanded Modes




Figure 14-5. Basic Bus Cycle (with 1 Wait State) in Expanded Modes (Modes 1 and 2)

14.3.2 Control Signal Timing

(1) Reset Input Timing




Figure 14-6. Reset Input Timing

(2) Interrupt Input Timing




Figure 14-7. Interrupt Input Timing

(3) Clock Settling Timing




Figure 14-8. Clock Settling Timing

(4) Clock Settling Timing for Recovery from Software Standby Mode




Figure 14-9. Clock Settling Timing for Recovery from Software Standby Mode

14.3.3 16-Bit Free-Running Timer Timing

(1) Free-Running Timer Input/Output Timing




Figure 14-10. Free-Running Timer Input/Output Timing

(2) External Clock Input Timing for Free-Running Timer




Figure 14-11. External Clock Input Timing for Free-Running Timer

14.3.4 8-Bit Timer Timing

(1) 8-Bit Timer Output Timing




Figure 14-12. 8-Bit Timer Output Timing

(2) 8-Bit Timer Clock Input Timing




Figure 14-13. 8-Bit Timer Clock Input Timing

(3) 8-Bit Timer Reset Input Timing




Figure 14-14. 8-Bit Timer Reset Input Timing

14.3.5 Serial Communication Interface Timing

(1) SCI Input/Output Timing




Figure 14-15. SCI Input/Output Timing (Synchronous Mode)

(2) SCI Input Clock Timing




Figure 14-16. SCI Input Clock Timing

14.3.6 I/O Port Timing




Figure 14-17. I/O Port Input/Output Timing