


SN54ABTE16246, SN74ABTE16246 11-BIT INCIDENT-WAVE SWITCHING BUS TRANSCEIVERS WITH 3-STATE AND OPEN-COLLECTOR OUTPUTS

SCBS227F – JULY 1993 – REVISED JUNE 1999

- Members of the Texas Instruments *Widebus™* Family
- State-of-the-Art *EPIC-II B™* BiCMOS Design Significantly Reduces Power Dissipation
- Support the VME64 ETL Specification
- Reduced TTL-Compatible Input Threshold Range
- High-Drive Outputs ($I_{OH} = -60$ mA, $I_{OL} = 90$ mA) Support Equivalent 25- Ω Incident-Wave Switching
- V_{CCBIAS} Pin Minimizes Signal Distortion During Live Insertion
- Internal Pullup Resistor on $\overline{OE}$ Keeps Outputs in High-Impedance State During Power Up or Power Down
- Distributed V_{CC} and GND Pin Configuration Minimizes High-Speed Switching Noise
- Equivalent 25- Ω Series Damping Resistor on B Port
- Bus Hold on Data Inputs Eliminates the Need for External Pullup/Pulldown Resistors
- Package Options Include Plastic Shrink Small-Outline (DL) and Thin-Shrink Small-Outline (DGG) Packages and 380-mil Fine-Pitch Ceramic Flat (WD) Package Using 25-mil Center-to-Center Spacings

SN54ABTE16246 . . . WD PACKAGE
SN74ABTE16246 . . . DGG OR DL PACKAGE
(TOP VIEW)



description

The 'ABTE16246 devices are 11-bit noninverting transceivers designed for asynchronous two-way communication between buses. These devices have open-collector and 3-state outputs. They allow data transmission from the A bus to the B bus or from the B bus to the A bus, depending on the logic level at the direction-control (DIR) input. The output-enable ($\overline{OE}$) input can be used to disable the device so that the buses are effectively isolated. When $\overline{OE}$ is low, the device is active.

The B port has an equivalent 25- Ω series output resistor to reduce ringing. Active bus-hold inputs on the B port hold unused or floating inputs at a valid logic level.

The A port provides for the precharging of the outputs via V_{CCBIAS} , which establishes a voltage between 1.3 V and 1.7 V when V_{CC} is not connected.

The SN54ABTE16246 is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74ABTE16246 is characterized for operation from -40°C to 85°C .



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

Widebus and EPICII-B are trademarks of Texas Instruments Incorporated.

UNLESS OTHERWISE NOTED this document contains PRODUCTION DATA information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1999, Texas Instruments Incorporated

SN54ABTE16246, SN74ABTE16246
11-BIT INCIDENT-WAVE SWITCHING BUS TRANSCEIVERS
WITH 3-STATE AND OPEN-COLLECTOR OUTPUTS

SCBS227F – JULY 1993 – REVISED JUNE 1999

FUNCTION TABLE


INPUTS					OPERATION
$\overline{\text{OE}}$	9DIR	10DIR	11DIR	$\overline{\text{11OE}}$	
H	X	X	X	X	Isolation
L	X	X	X	X	1BI–8BI data to 1A–8A bus (OC [†]), 1A–8A data to 1BO–8BO bus
L	L	X	X	X	9A data to 9B bus
L	H	X	X	X	9B data to 9A bus
L	X	L	X	X	10A data to 10B bus
L	X	H	X	X	10B data to 10A bus
L	X	X	L	L	11A data to 11B bus
L	X	X	L	H	11A, 11B isolation
L	X	X	H	X	11B data to 11A bus

[†] OC = Open-collector outputs

SN54ABTE16246, SN74ABTE16246
11-BIT INCIDENT-WAVE SWITCHING BUS TRANSCEIVERS
WITH 3-STATE AND OPEN-COLLECTOR OUTPUTS

SCBS227F – JULY 1993 – REVISED JUNE 1999

logic diagram (positive logic)



SN54ABTE16246, SN74ABTE16246

11-BIT INCIDENT-WAVE SWITCHING BUS TRANSCEIVERS

WITH 3-STATE AND OPEN-COLLECTOR OUTPUTS

SCBS227F – JULY 1993 – REVISED JUNE 1999

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)[†]

Supply voltage range, V_{CC}	–0.5 V to 7 V
Input voltage range, V_I (except I/O ports) (see Note 1)	–0.5 V to 7 V
Voltage range applied to any output in the high or power-off state, V_O	–0.5 V to 5.5 V
Current into any output in the low state, I_O	128 mA
Input clamp current, I_{IK} ($V_I < 0$)	–18 mA
Output clamp current, I_{OK} ($V_O < 0$)	–50 mA
Package thermal impedance, θ_{JA} (see Note 2): DGG package	89°C/W
DL package	94°C/W
Storage temperature range, T_{stg}	–65°C to 150°C

[†] Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. The input and output negative-voltage ratings may be exceeded if the input and output clamp-current ratings are observed.
2. The package thermal impedance is calculated in accordance with JESD 51.

recommended operating conditions (see Note 3)

			SN54ABTE16246			SN74ABTE16246			UNIT
			MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage		4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage	$\overline{OE}$	2			2			V
		Except $\overline{OE}$	1.6			1.6			
V_{IL}	Low-level input voltage	$\overline{OE}$			0.8			0.8	V
		Except $\overline{OE}$			1.4			1.4	
V_{OH}	High-level output voltage	1A–8A			5.5	0		5.5	V
V_I	Input voltage		0		V_{CC}	0		V_{CC}	V
I_{OH}	High-level output current	B bus			–12			–12	mA
		9A–11A			–24			–64	
I_{OL}	Low-level output current	B bus			12			12	mA
		A bus			64			90	
$\Delta t/\Delta v$	Input transition rise or fall rate	Outputs enabled			10			10	ns/V
T_A	Operating free-air temperature		–55		125	–40		85	°C

NOTE 3: All unused control inputs of the device must be held at V_{CC} or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.

SN54ABTE16246, SN74ABTE16246
11-BIT INCIDENT-WAVE SWITCHING BUS TRANSCEIVERS
WITH 3-STATE AND OPEN-COLLECTOR OUTPUTS

SCBS227F – JULY 1993 – REVISED JUNE 1999

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS		SN54ABTE16246			SN74ABTE16246			UNIT
				MIN	TYP [†]	MAX	MIN	TYP [†]	MAX	
V _{IK}		V _{CC} = 4.5 V, I _I = –18 mA				–1.2			–1.2	V
V _{OH}	B port	V _{CC} = 5.5 V, I _{OH} = –100 µA				V _{CC} –0.2			V _{CC} –0.2	V
		V _{CC} = 4.5 V, I _{OH} = –1 mA		2.4			2.4			
		I _{OH} = –12 mA		2			2			
	9A–11A	V _{CC} = 5.5 V, I _{OH} = –1 mA				4.5			4.5	
		V _{CC} = 4.5 V, I _{OH} = –32 mA		2.4			2.4			
		I _{OH} = –64 mA					2			
I _{OH}	1A–8A	V _{CC} = 4.5 V, V _{OH} = 5.5 V				20			20	µA
V _{OL}	B port	V _{CC} = 4.5 V	I _{OL} = 1 mA			0.4			0.4	V
			I _{OL} = 12 mA						0.8	
	A port	V _{CC} = 4.5 V	I _{OL} = 64 mA			0.55			0.55	
			I _{OL} = 90 mA						0.9	
V _{hys}					100			100		mV
I _I (hold)	B port	V _{CC} = 4.5 V	V _I = 0.8 V		100			100		µA
			V _I = 2 V		–100			–100		
		V _{CC} = 5.5 V, V _I = 0 to 5.5 V				±500			±500	
I _I	Control inputs	V _{CC} = 5.5 V, V _I = V _{CC} or GND				±1			±1	µA
	A or B ports					±20			±20	
I _{OZH} [‡]	9A–11A	V _{CC} = 5.5 V, V _O = 2.7 V				10			10	µA
I _{OZL} [‡]	9A–11A	V _{CC} = 5.5 V, V _O = 0.5 V				–10			–10	µA
I _O	A port	V _{CC} = 5.5 V, V _O = 2.5 V		–50	–120	–180	–50		–180	mA
	B port			–25	–52	–90	–25		–90	
I _{off}		V _{CC} = 0, V _I or V _O ≤ 4.5 V, V _{CC} BIAS = 0				±100			±100	µA
I _{CC}	A or B ports	V _{CC} = 5.5 V, I _O = 0, V _I = V _{CC} or GND	Outputs high		28	36		28	36	mA
			Outputs low		38	48		38	48	
			Outputs disabled		20	32		20	32	
I _{CCD}	A or B ports	V _{CC} = 5 V, C _L = 50 pF	$\overline{\text{OE}}$ high		0.02			0.02		mA/ MHz
			$\overline{\text{OE}}$ low		0.33			0.33		
C _i	Control inputs	V _I = 2.5 V or 0.5 V			2.5	4		2.5	4	pF
C _{io}	I/O ports	V _O = 2.5 V or 0.5 V			4.5	8		4.5	8	pF

[†] All typical values are at V_{CC} = 5 V, T_A = 25°C.

[‡] The parameters I_{OZH} and I_{OZL} include the input leakage current.

SN54ABTE16246, SN74ABTE16246

11-BIT INCIDENT-WAVE SWITCHING BUS TRANSCEIVERS

WITH 3-STATE AND OPEN-COLLECTOR OUTPUTS

SCBS227F – JULY 1993 – REVISED JUNE 1999

live-insertion specifications over recommended operating free-air temperature range

PARAMETER		TEST CONDITIONS		SN54ABTE16246			SN74ABTE16246			UNIT
				MIN	TYP†	MAX	MIN	TYP†	MAX	
I _{CC} (V _{CCBIAS})		V _{CC} = 0 to 4.5 V, V _{CCBIAS} = 4.5 V to 5.5 V, I _O (DC) = 0		250 700			250 700			μA
		V _{CC} = 4.5 V to 5.5 V†, V _{CCBIAS} = 4.5 V to 5.5 V, I _O (DC) = 0		20			20			
V _O	A port	V _{CC} = 0	V _{CCBIAS} = 4.5 V to 5.5 V	1.1	1.5	1.9	1.1	1.5	1.9	V
			V _{CCBIAS} = 4.75 V to 5.25 V	1.3	1.5	1.7	1.3	1.5	1.7	
I _O	A port	V _{CC} = 0	V _O = 0, V _{CCBIAS} = 4.5 V	–20	–100		–20	–100		μA
			V _O = 3 V, V _{CCBIAS} = 4.5 V	20	100		20	100		

† All typical values are at $V_{CC} = 5$ V, $T_A = 25^\circ C$.

‡ $V_{CC} - 0.5$ V < V_{CCBIAS}

switching characteristics over recommended ranges of supply voltage and operating free-air temperature, $C_L = 50$ pF (unless otherwise noted) (see Figure 2)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 5$ V $T_A = 25^\circ C$			SN54ABTE16246		SN74ABTE16246		UNIT
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
t_{PLH}	A	B	1.5	3.1	4.2	1.5	5.4	1.5	5.2	ns
t_{PHL}			1.5	3.5	4.6	1.5	5.4	1.5	5.2	
t_{PLH}	9B–11B	9A–11A	1.5	3	3.8	1.5	4.7	1.5	4.5	ns
t_{PHL}			1.5	3.2	4	1.5	4.7	1.5	4.5	
t_{PLH}^S	1B–8B	1A–8A	1.5	3.2	4	1.5	4.7	1.5	4.5	ns
$t_{PLH}^{ }$			7.5	8.9	9.7	7.5	10.6	7.5	10.3	
t_{PHL}			1.5	3.2	4	1.5	4.7	1.5	4.5	
t_{PZH}	$\overline{OE}$	9A–11A	2	4.3	5.3	2	6.4	2	6.2	ns
t_{PZL}		1A–11A	2	4.4	5.4	2	7	2	6.8	
t_{PZH}	$\overline{OE}$	B	2	4.3	6	2	7.3	2	7.1	ns
t_{PZL}			2	4.5	6.4	2	7.5	2	7.3	
t_{PHZ}	$\overline{OE}$	9A–11A	2	4.2	5.9	2	7	2	6.7	ns
t_{PLZ}		1A–11A	2	3.5	4.6	2	5.4	2	5.1	
t_{PHZ}	$\overline{OE}$	B	2.5	4.3	6.2	2.5	7.2	2.5	7	ns
t_{PLZ}			2	3.6	5	2	5.8	2	5.5	

^S Measurement point is $V_{OL} + 0.3$ V.

^{||} Measurement point is $V_{OL} + 1.5$ V.

SN54ABTE16246, SN74ABTE16246
11-BIT INCIDENT-WAVE SWITCHING BUS TRANSCEIVERS
WITH 3-STATE AND OPEN-COLLECTOR OUTPUTS

SCBS227F – JULY 1993 – REVISED JUNE 1999

extended switching characteristics over recommended ranges of supply voltage and operating free-air temperature, $C_L = 50$ pF (unless otherwise noted) (see Figure 2)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	LOAD	$V_{CC} = 5$ V $T_A = 25^\circ\text{C}$			SN54ABTE16246		SN74ABTE16246		UNIT
				MIN	TYP	MAX	MIN	MAX	MIN	MAX	
t_{PLH}	9B–11B	9A–11A	$R_X = 13\ \Omega$	1.5	3.2	4	1.5	5	1.5	4.8	ns
t_{PHL}				1.5	3.8	4.7	1.5	5.8	1.5	5.6	
t_{PHL}	1B–8B	1A–8A	$R_X = 13\ \Omega$	1.5	3.3	4.2	1.5	5	1.5	4.8	ns
t_{PLH}	9B–11B	9A–11A	$R_X = 26\ \Omega$	1.5	3.1	4	1.5	4.8	1.5	4.6	ns
t_{PHL}				1.5	3.5	4.4	1.5	5.2	1.5	4.9	
t_{PHL}	1B–8B	1A–8A	$R_X = 26\ \Omega$	1.5	3.1	4	1.5	4.6	1.5	4.4	ns
t_{PLH}	9B–11B	1A–8A	$R_X = 56\ \Omega$	1.5	3	3.8	1.5	4.7	1.5	4.5	ns
t_{PHL}				1.5	3.3	4.2	1.5	5.1	1.5	4.7	
t_{PHL}	1B–8B	1A–8A	$R_X = 56\ \Omega$	1.5	3	4	1.5	4.6	1.5	4.4	ns
$t_{sk(p)}$	B	A	$R_X = \text{Open}$		0.1	0.6		2		2	ns
	A	B			0.4	0.8		2		2	
	B	A	$R_X = 26\ \Omega$		0.3	0.8		2		2	
$t_{sk(o)}$	B	A	$R_X = \text{Open}$		0.3	0.7		1.3		1.3	ns
	A	B			0.7	1.1		1.3		1.3	
	B	A	$R_X = 26\ \Omega$		0.5	1		1.3		1.3	
$t_t^\dagger$	B	A	$R_X = 26\ \Omega$	0.5	0.8	1.5	0.5	1.5	0.5	1.5	ns
$t_t^\ddagger$	A	B	Rise or fall time 10%–90%	3.5	5.5	7.3	3.5	8.1	3.5	7.9	ns

$^\dagger t_t$ is measured between 1 V and 2 V of the output waveform.

$^\ddagger t_t$ is measured between 10% and 90% of the output waveform.

extended output characteristics over recommended ranges of supply voltage and operating free-air temperature, $C_L = 50$ pF (see Figures 1 and 2)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	TEST CONDITIONS	LOAD	SN54ABTE16246		SN74ABTE16246		UNIT
					MIN	MAX	MIN	MAX	
$t_{sk(temp)}$	A	B	$V_{CC} = \text{constant},$ $\Delta T_A = 20^\circ\text{C}$			3		2.5	ns
	B	A		$R_X = 56\ \Omega$		4.5		4	
$t_{sk(load)}$	B	A	$V_{CC} = \text{constant},$ Temperature = constant	$R_X = 13, 26,$ or $56\ \Omega$		4.5		4	ns

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265


SN54ABTE16246, SN74ABTE16246

11-BIT INCIDENT-WAVE SWITCHING BUS TRANSCEIVERS

WITH 3-STATE AND OPEN-COLLECTOR OUTPUTS

SCBS227F – JULY 1993 – REVISED JUNE 1999

PARAMETER MEASUREMENT INFORMATION



- NOTES:
- A. Pulse skew, $t_{sk(p)}$, is defined as the difference in propagation delay times t_{PLH1} and t_{PHL1} on the same terminal at identical operating conditions.
 - B. Output skew, $t_{sk(o)}$, is defined as the difference in propagation delay of any two outputs of the same device switching in the same direction (e.g., $|t_{PLH1} - t_{PLH2}|$).
 - C. Temperature skew, $t_{sk(temp)}$, is the output skew of two devices, both having the same value of $V_{CC} \pm 1\%$ and with package temperature differences of 20°C .
 - D. Load skew, $t_{sk(load)}$, is measured with R_X in Figure 2 at $13\ \Omega$ for one unit and $56\ \Omega$ for the other unit.

Figure 1. Voltage Waveforms for Extended Characteristics


SN54ABTE16246, SN74ABTE16246

11-BIT INCIDENT-WAVE SWITCHING BUS TRANSCEIVERS

WITH 3-STATE AND OPEN-COLLECTOR OUTPUTS


SCBS227F – JULY 1993 – REVISED JUNE 1999

PARAMETER MEASUREMENT INFORMATION




$R_X = 13, 26, \text{ or } 56 \text{ } \Omega$

LOAD CIRCUIT



VOLTAGE WAVEFORMS
PROPAGATION DELAY TIMES



VOLTAGE WAVEFORMS
ENABLE AND DISABLE TIMES

- NOTES: A. C_L includes probe and jig capacitance.
- B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
- C. All input pulses are supplied by generators having the following characteristics: $PRR \leq 10 \text{ MHz}$, $Z_O = 50 \text{ } \Omega$, $t_r \leq 2.5 \text{ ns}$, $t_f \leq 2.5 \text{ ns}$.
- D. The outputs are measured one at a time with one transition per measurement.
- E. t_t is measured between 1 V and 2 V of the output waveform.
- F. t_t is measured between 10% and 90% of the output waveform.

Figure 2. Load Circuit and Voltage Waveforms

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.