

SN54HC09, SN74HC09 QUADRUPLE 2-INPUT POSITIVE-AND GATES WITH OPEN-DRAIN OUTPUTS

D2804, MARCH 1984 — REVISED SEPTEMBER 1987

- Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs
- Dependable Texas Instruments Quality and Reliability

description

These devices contain four independent 2-input AND gates. They perform the Boolean functions $Y = A \cdot B$ or $Y = \overline{A} + \overline{B}$ in positive logic. The open-drain outputs require pull-up resistors to perform correctly. They may be connected to other open-drain outputs to implement active-low wired-OR or active-high wired-AND functions.


The SN54HC09 is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74HC09 is characterized for operation from -40°C to 85°C .

FUNCTION TABLE (each gate)

INPUTS		OUTPUT
A	B	Y
H	H	H
L	X	L
X	L	L


**SN54HC09 . . . J PACKAGE
SN74HC09 . . . D OR N PACKAGE**

(TOP VIEW)



SN54HC09 . . . FK PACKAGE

(TOP VIEW)




NC — No internal connection

logic diagram (positive logic)



logic symbol[†]



[†]This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

Pin numbers shown are for D, J, and N packages.

SN54HC09, SN74HC09

QUADRUPLE 2-INPUT POSITIVE-AND GATES WITH OPEN-DRAIN OUTPUTS

absolute maximum ratings over operating free-air temperature range[†]

Supply voltage, V _{CC}	-0.5 V to 7 V
Input clamp current, I _{IK} (V _I < 0 or V _I > V _{CC})	±20 mA
Output clamp current, I _{OK} (V _O < 0 or V _O > V _{CC})	±20 mA
Continuous output current, I _O (V _O = 0 to V _{CC})	±25 mA
Continuous current through V _{CC} or GND pins	±50 mA
Lead temperature 1.6 mm (1/16 in) from case for 60 s: FK or J package	300°C
Lead temperature 1.6 mm (1/16 in) from case for 10 s: D or N package	260°C
Storage temperature range	-65°C to 150°C

[†]Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

recommended operating conditions

		SN54HC09			SN74HC09			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V _{CC}	Supply voltage	2	5	6	2	5	6	V
V _{IH}	High-level input voltage	V _{CC} = 2 V	1.5		1.5			
		V _{CC} = 4.5 V	3.15		3.15			
		V _{CC} = 6 V	4.2		4.2			
V _{IL}	Low-level input voltage	V _{CC} = 2 V	0	0.3	0	0.3		V
		V _{CC} = 4.5 V	0	0.9	0	0.9		
		V _{CC} = 6 V	0	1.2	0	1.2		
V _I	Input voltage		0	V _{CC}	0	V _{CC}		V
V _O	Output voltage		0	V _{CC}	0	V _{CC}		V
t _t	Input transition (rise and fall) times	V _{CC} = 2 V	0	1000	0	1000		
		V _{CC} = 4.5 V	0	500	0	500		
		V _{CC} = 6 V	0	400	0	400		ns
T _A	Operating free-air temperature		-55	125	-40	85		°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	V _{CC}	T _A = 25°C			SN54HC09		SN74HC09		UNIT
			MIN	Typ	MAX	MIN	MAX	MIN	MAX	
I _{OH}	V _I = V _{IH} or V _{IL} , V _O = V _{CC}	6 V	0.01	0.5		10		.5		μA
V _{OL}	V _I = V _{IH} or V _{IL} , I _{OL} = 20 μA	2 V	0.002	0.1		0.1		0.1		V
		4.5 V	0.001	0.1		0.1		0.1		
		6 V	0.001	0.1		0.1		0.1		
	V _I = V _{IH} or V _{IL} , I _{OL} = 4 mA	4.5 V	0.17	0.26		0.4		0.33		
	V _I = V _{IH} or V _{IL} , I _{OL} = 5.2 mA	6 V	0.15	0.26		0.4		0.33		
I _I	V _I = V _{CC} or 0	6 V	±0.1	±100		±1000		±1000		nA
I _{CC}	V _I = V _{CC} or 0, I _O = 0	6 V		2		40		20		μA
C _i		2 to 6 V	3	10		10		10		pF

SN54HC09, SN74HC09
QUADRUPLE 2-INPUT POSITIVE-AND GATES
WITH OPEN-DRAIN OUTPUTS

switching characteristics over recommended operating free-air temperature range (unless otherwise noted), $R_L = 1 \text{ k}\Omega$, $C_L = 50 \text{ pF}$ (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC}	T _A = 25°C			SN54HC09		SN74HC09		UNIT
				MIN	TYP	MAX	MIN	MAX	MIN	MAX	
t _{PLH}	A or B	Y	2 V	60	105	155			131		ns
			4.5 V	13	25	36			31		
			6 V	10	23	31			27		
t _{PHL}	A or B	Y	2 V	50	100	150			125		ns
			4.5 V	10	20	30			25		
			6 V	8	17	25			21		
t _f		Y	2 V	38	75	110			95		ns
			4.5 V	8	15	22			19		
			6 V	6	13	19			16		

C _{pd}	Power dissipation capacitance per gate	No load, T _A = 25°C	20 pF typ
-----------------	--	--------------------------------	-----------

NOTE 1: Load circuit and voltage waveforms are shown in Section 1.

2

HCMOS Devices