

54AC11623, 74AC11623

Octal Bus Transceivers with 3-State Outputs

These octal bus transceivers are designed for asynchronous two-way communication between data buses. The control function implementation allows for maximum flexibility in timing.

These devices allow data transmission from the A bus to the B bus, or from the B bus to the A bus, depending upon the logic levels at the enable inputs ($\bar{G}BA$ and GAB).

The enable inputs can be used to disable the device so that the buses are effectively isolated.

The dual-enable configuration gives these devices the capability to store data by simultaneous enabling of $\bar{G}BA$ and GAB . Each output reinforces its input in this transceiver configuration. Thus, when both control inputs are enabled and all other data sources to the two sets of bus lines are at high impedance, both sets of bus lines (16 in all) will remain at their last states. The 8-bit codes appearing on the two sets of buses will be identical for the AC11623.

The 54AC11623 is characterized for operation over the full military temperature range of -55°C to 125°C. The 74AC11623 is characterized for operation from -40°C to 85°C.

Rochester Electronics Manufactured Components

Rochester branded components are manufactured using either die/wafers purchased from the original suppliers or Rochester wafers recreated from the original IP. All re-creations are done with the approval of the Original Component Manufacturer (OCM).

Parts are tested using original factory test programs or Rochester developed test solutions to guarantee product meets or exceeds the OCM data sheet.

Quality Overview

- ISO-9001
- AS9120 certification
- Qualified Manufacturers List (QML) MIL-PRF-35835
 - Class Q Military
 - Class V Space Level
- Qualified Suppliers List of Distributors (QSLD)
 - Rochester is a critical supplier to DLA and meets all industry and DLA standards.

Rochester Electronics, LLC is committed to supplying products that satisfy customer expectations for quality and are equal to those originally supplied by industry manufacturers.

The original manufacturer's datasheet accompanying this document reflects the performance and specifications of the Rochester manufactured version of this device. Rochester Electronics guarantees the performance of its semiconductor products to the original OCM specifications. 'Typical' values are for reference purposes only. Certain minimum or maximum ratings may be based on product characterization, design, simulation, or sample testing.

FOR REFERENCE ONLY

54AC11623, 74AC11623 OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

TI0091—D2957, JULY 1987—REVISED MARCH 1990

- **Local Bus-Latch Capability**
- **Flow-Through Architecture to Optimize PCB Layout**
- **Center-Pin V_{CC} and GND Configurations to Minimize High-Speed Switching Noise**
- **EPIC™ (Enhanced-Performance Implanted CMOS) 1-μm Process**
- **500-mA Typical Latch-Up Immunity at 125°C**
- **Package Options Include Plastic "Small Outline" Packages, Ceramic Chip Carriers, and Standard Plastic and Ceramic 300-mil DIPs**

description

These octal bus transceivers are designed for asynchronous two-way communication between data buses. The control function implementation allows for maximum flexibility in timing.


These devices allow data transmission from the A bus to the B bus, or from the B bus to the A bus, depending upon the logic levels at the enable inputs ($\overline{\text{GBA}}$ and GAB).

The enable inputs can be used to disable the device so that the buses are effectively isolated.


The dual-enable configuration gives these devices the capability to store data by simultaneous enabling of $\overline{\text{GBA}}$ and GAB . Each output reinforces its input in this transceiver configuration. Thus, when both control inputs are enabled and all other data sources to the two sets of bus lines are at high impedance, both sets of bus lines (16 in all) will remain at their last states. The 8-bit codes appearing on the two sets of buses will be identical for the AC11623.

The 54AC11623 is characterized for operation over the full military temperature range of -55°C to 125°C. The 74AC11623 is characterized for operation from -40°C to 85°C.

54AC11623 ... JT PACKAGE
74AC11623 ... DW OR NT PACKAGE
(TOP VIEW)



54AC11623 ... FK PACKAGE
(TOP VIEW)



NC—No internal connection

FUNCTION TABLE

ENABLE INPUTS		OPERATION
$\overline{\text{GBA}}$	GAB	
L	L	B data to A bus
H	H	A data to B bus
H	L	Isolation
L	H	B data to A bus, A data to B bus

EPIC is a trademark of Texas Instruments Incorporated.

UNLESS OTHERWISE NOTED this document contains
PRODUCTION DATA information current as of publication date.
Products conform to specifications per the terms of Texas
Instruments standard warranty. Production processing does not
necessarily include testing of all parameters.

2-536


TEXAS
INSTRUMENTS
POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1990, Texas Instruments Incorporated


54AC11623, 74AC11623 OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

TI0091—D2957, JULY 1987—REVISED MARCH 1990

logic symbol†



logic diagram (positive logic)



† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

Pin numbers shown are for DW, JT, and NT packages.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)‡

Supply voltage range, V_{CC}	−0.5 V to 7 V
Input voltage range, V_I (see Note 1)	−0.5 V to $V_{CC} + 0.5$ V
Output voltage range, V_O (see Note 1)	−0.5 V to $V_{CC} + 0.5$ V
Input clamp current, I_{IK} ($V_I < 0$ or $V_I > V_{CC}$)	±20 mA
Output clamp current, I_{OK} ($V_O < 0$ or $V_O > V_{CC}$)	±50 mA
Continuous output current, I_O ($V_O = 0$ to V_{CC})	±50 mA
Continuous current through V_{CC} or GND pins	±200 mA
Storage temperature range	−65°C to 150°C

‡ Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: The input and output voltage ratings may be exceeded if the input and output current ratings are observed.

TEXAS
INSTRUMENTS

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

2-537

54AC11623, 74AC11623 OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

D2957, JULY 1987—REVISED MARCH 1990—TI0091

recommended operating conditions

			54AC11623			74AC11623			UNIT
			MIN	NOM	MAX	MIN	NOM	MAX	
V _{CC}	Supply voltage		3	5	5.5	3	5	5.5	V
V _{IH}	High-level input voltage	V _{CC} = 3 V	2.1			2.1			V
		V _{CC} = 4.5 V	3.15			3.15			
		V _{CC} = 5.5 V	3.85			3.85			
V _{IL}	Low-level input voltage	V _{CC} = 3 V		0.9			0.9		V
		V _{CC} = 4.5 V		1.35			1.35		
		V _{CC} = 5.5 V		1.65			1.65		
V _I	Input voltage		0	V _{CC}		0	V _{CC}		V
V _O	Output voltage		0	V _{CC}		0	V _{CC}		V
I _{OH}	High-level output current	V _{CC} = 3 V		-4			-4		mA
		V _{CC} = 4.5 V		24			24		
		V _{CC} = 5.5 V		-24			-24		
I _{OL}	Low-level output current	V _{CC} = 3 V		12			12		mA
		V _{CC} = 4.5 V		24			24		
		V _{CC} = 5.5 V		24			24		
Δt/Δv	Input transition rise or fall rate		0	10		0	10		ns/V
T _A	Operating free-air temperature		55	125		-40	85		°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS	V _{CC}	T _A = 25°C			54AC11623		74AC11623		UNIT
				MIN	TYP	MAX	MIN	MAX	MIN	MAX	
V _{OH}	I _{OH} = 50 μA		3 V	2.9			2.9		2.9		V
			4.5 V	4.4			4.4		4.4		
			5.5 V	5.4			5.4		5.4		
	I _{OH} = 4 mA		3 V	2.58			2.4		2.48		
			4.5 V	3.94			3.7		3.8		
			5.5 V	4.94			4.7		4.8		
V _{OL}	I _{OL} = 50 μA		3 V		0.1		0.1		0.1		V
			4.5 V		0.1		0.1		0.1		
			5.5 V		0.1		0.1		0.1		
	I _{OL} = 12 mA		3 V		0.36		0.5		0.44		
			4.5 V		0.36		0.5		0.44		
			5.5 V		0.36		0.5		0.44		
I _{OZ}	A or B ports†	V _O = V _{CC} or GND	3 V								μA
			4.5 V								
			5.5 V								
	G _{BA} or G _{AB}	V _I = V _{CC} or GND	3 V								
			4.5 V								
			5.5 V								
I _{CC}		V _I = V _{CC} or GND, I _O = 0	5.5 V		8		160		80		μA
C _i	G _{BA} or G _{AB}	V _I = V _{CC} or GND	5 V		4						pF
C _{io}	A or B ports	V _O = V _{CC} or GND	5 V		12						pF

† Not more than one output should be tested at a time, and the duration of the test should not exceed 10 ms.

‡ For I/O ports, the parameter I_{OZ} includes the input leakage current.

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.

2-538

**TEXAS
INSTRUMENTS**
POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

54AC11623, 74AC11623 OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

TI0091—D2957, JULY 1987—REVISED MARCH 1990

**switching characteristics over recommended operating free-air temperature range,
V_{CC} = 3.3 V ± 0.3 V (unless otherwise noted) (see Figure 1)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	T _A = 25°C			54AC11623		74AC11623		UNIT
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
t _{PLH}	A or B	B or A	1.5	6.8	9.2	1.5	11.4	1.5	10.5	ns
t _{PHL}			1.5	6.3	8.2	1.5	10.6	1.5	9.3	
t _{PZH}	$\overline{\text{G}}$ BA	A	1.5	8	10.6	1.5	13.3	1.5	12.2	ns
t _{PZL}			1.5	7.9	10.4	1.5	12.5	1.5	11.6	
t _{PHZ}	$\overline{\text{G}}$ BA	A	1.5	7	8.7	1.5	9.7	1.5	9.3	ns
t _{PLZ}			1.5	8	9.9	1.5	11.3	1.5	10.7	
t _{PZH}	GAB	B	1.5	8.2	10.4	1.5	13.2	1.5	12	ns
t _{PZL}			1.5	8.3	10.8	1.5	13.2	1.5	12.2	
t _{PHZ}	GAB	B	1.5	7	8.8	1.5	9.8	1.5	9.4	ns
t _{PLZ}			1.5	8	9.9	1.5	11.1	1.5	10.6	

**switching characteristics over recommended operating free-air temperature range,
V_{CC} = 5 V ± 0.5 V (unless otherwise noted) (see Figure 1)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	T _A = 25°C			54AC11623		74AC11623		UNIT
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
t _{PLH}	A or B	B or A	1.5	4.9	6.8	1.5	8.4	1.5	7.8	ns
t _{PHL}			1.5	4.6	6.4	1.5	7.7	1.5	7.1	
t _{PZH}	$\overline{\text{G}}$ BA	A	1.5	5.8	7.9	1.5	9.8	1.5	9	ns
t _{PZL}			1.5	5.9	8.1	1.5	9.9	1.5	9.1	
t _{PHZ}	$\overline{\text{G}}$ BA	A	1.5	6.1	7.7	1.5	8.6	1.5	8.3	ns
t _{PLZ}			1.5	6.6	8.2	1.5	9.3	1.5	8.8	
t _{PZH}	GAB	B	1.5	6.2	8	1.5	10	1.5	9.2	ns
t _{PZL}			1.5	6.1	8.3	1.5	10.2	1.5	9.4	
t _{PHZ}	GAB	B	1.5	6.2	7.8	1.5	8.7	1.5	8.3	ns
t _{PLZ}			1.5	6.5	8.1	1.5	9.2	1.5	8.8	

operating characteristics, V_{CC} = 5 V, T_A = 25°C

PARAMETER			TEST CONDITIONS		TYP	UNIT	
C _{pd}	Power dissipation capacitance per transceiver	Outputs enabled	C _L	50 pF, f	1 MHz	49	pF
		Outputs disabled				9	

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.

**TEXAS
INSTRUMENTS**


POST OFFICE BOX 655303 • DALLAS, TEXAS 75285

2-539

54AC11623, 74AC11623 OCTAL BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

D2957, JULY 1987—REVISED MARCH 1990—T10091

PARAMETER MEASUREMENT INFORMATION



- NOTES: A. C_L includes probe and jig capacitance.
 B. Input pulses are supplied by generators having the following characteristics: PRR $\leq 10 \text{ MHz}$, $Z_0 = 50 \Omega$, $t_r = 3 \text{ ns}$, $t_f = 3 \text{ ns}$.
 C. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
 D. The outputs are measured one at a time with one input transition per measurement.

FIGURE 1. LOAD CIRCUIT AND VOLTAGE WAVEFORMS