



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE74HC151 **Integrated Circuit** **TTL – High Speed CMOS,** **8–Channel Digital Multiplexer**

Description:

The NTE74HC151 is a high speed Digital multiplexer in a 16–Lead DIP type package that utilizes advanced silicon–gate CMOS technology. Along with high noise immunity and low power dissipation of standard CMOS integrated circuits, it possesses the ability to drive 10 LS–TTL loads. The NTE74HC151 selects one of the 8 data sources, depending on the address presented on the A, B, and C inputs. It features both true (Y) and complement (W) outputs. The STROBE input must be at a low logic level to enable the multiplexer. A high logic level at the STROBE forces the W output HIGH and the Y output LOW.

The 74HC logic family is functionally, as well as pinout compatible, with the standard 74LS logic family. All inputs are protected from damage due to static discharge by internal diode clamps to V_{CC} and GND.

Features:

- Typical Propagation Delay Data Select to Output Y: 26ns
- Wide Operatin Supply Voltage Range: 2V to 6V
- Low Input Current: 1 μ A (max)
- Low Quiescent Supply Current: 80 μ A (max)
- High Ooutput Drive Current: 4mA (max)

Absolute Maximum Ratings: (Note 1, Note 2)

Supply Voltage, V_{CC}	–0.5 to +7.0V
DC Input Voltage, V_{IN}	–1.5 to V_{CC} +1.5V
DC Output Voltage, V_{OUT}	–0.5 to V_{CC} + 0.5V
Clamp Diode Current, I_{IK} , I_{OK}	$\pm$ 20mA
DC Output Current (Per Pin), I_{OUT}	$\pm$ 25mA
DC V_{CC} or GND Current (Per Pin), I_{CC}	$\pm$ 50mA
Power Dissipation (Note 3), P_D	500mW
Storage Temperature Range, T_{stg}	–65°C to +150°C
Lead Temperature (During Soldering, 10sec), T_L	+260°C

Note 1. Absolute Maximum Ratings are those values beyond which damage to the device may occur.

Note 2. Unless otherwise specified, all voltages are referenced to GND.

Note 3. Power Dissipation temperature derating: 12mW/°C from +65°C to +85°C.

Recommended Operating Conditions:

Parameter	Symbol	Min	Typ	Max	Unit
Supply Voltage	V_{CC}	2.0	–	6.0	V
DC Input or Output Voltage	V_{IN}, V_{OUT}	0	–	V_{CC}	V
Operating Temperature Range	T_A	–40	–	+85	°C
Input Rise or Fall Times $V_{CC} = 2.0V$	t_r, t_f	–	–	1000	ns
$V_{CC} = 4.5V$		–	–	500	ns
$V_{CC} = 6.0V$		–	–	400	ns

DC Electrical Characteristics: ($V_{CC} = 5V \pm 10\%$ unless otherwise specified)

Parameter	Symbol	Test Conditions		V _{CC}	T _A = +25°C		T _A = −40° to +85°C		Unit
					Typ	Guaranteed Limits			
Minimum High Level Input Voltage	V _{IH}			2.0	–	1.5	1.5	V	
				4.5	–	3.15	3.15	V	
				6.0	–	4.2	4.2	V	
Maximum Low Level Input Voltage	V _{IL}			2.0	–	0.5	0.5	V	
				4.5	–	1.35	1.35	V	
				6.0	–	1.8	1.8	V	
Minimum High Level Output Voltage	V _{OH}	V _{IN} = V _{IH} or V _{IL} , I _{OUT} ≤ 20μA	2.0	2.0	1.9	1.9	V		
			4.5	4.5	4.4	4.4	V		
			6.0	6.0	5.9	5.9	V		
		V _{IN} = V _{IH} or V _{IL}	I _{OUT} ≤ 4.0mA		4.5	4.2	3.98	3.84	V
			I _{OUT} ≤ 5.2mA		6.0	5.7	5.48	5.34	V
Maximum Low Level Output Voltage	V _{OL}	V _{IN} = V _{IH} or V _{IL} , I _{OUT} ≤ 20μA	2.0	0	0.1	0.1	V		
			4.5	0	0.1	0.1	V		
			6.0	0	0.1	0.1	V		
		V _{IN} = V _{IH} or V _{IL}	I _{OUT} ≤ 4.0mA		4.5	0.2	0.26	0.33	V
			I _{OUT} ≤ 5.2mA		6.0	0.2	0.26	0.33	V
Maximum Input Current	I _{IN}	V _{IN} = V _{CC} or GND		6.0	–	±0.1	±1.0	μA	
Maximum Quiescent Supply Current	I _{CC}	V _{IN} = V _{CC} or GND, I _{OUT} = 0μA		6.0	–	8	80	μA	

AC Electrical Characteristics: ($V_{CC} = 5V, t_r = t_f = 6ns, C_L = 15pF, T_A = +25^\circ C$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Typ	Guaranteed Limits	Unit
Maximum Propagation Delay (A, B or C to Y)	t_{PHL}, t_{PLH}		26	35	ns
Maximum Propagation Delay (A, B or C to W)	t_{PHL}, t_{PLH}		27	35	ns
Maximum Propagation Delay (Any D to Y)	t_{PHL}, t_{PLH}		22	29	ns
Maximum Propagation Delay (Any D to W)	t_{PHL}, t_{PLH}		24	32	ns
Maximum Propagation Delay (Strobe to Y)	t_{PHL}, t_{PLH}		17	23	ns
Maximum Propagation Delay (Strobe to W)	t_{PHL}, t_{PLH}		16	21	ns

AC Electrical Characteristics: ($V_{CC} = 5V \pm 10\%$, $t_r = t_f = 6ns$, $C_L = 50pF$ unless otherwise specified)

Parameter	Symbol	Test Conditions	V _{CC}	T _A = +25°C		T _A = −40° to +85°C	Unit
				Typ	Guaranteed Limits		
Maximum Propagation Delay (A, B or C to Y)	t _{PHL} , t _{PLH}		2.0	90	205	256	ns
			4.5	31	41	51	ns
			6.0	26	35	44	ns
Maximum Propagation Delay (A, B or C to W)	t _{PHL} , t _{PLH}		2.0	95	205	256	ns
			4.5	32	41	51	ns
			6.0	27	35	44	ns
Maximum Propagation Delay (Any D to Y)	t _{PHL} , t _{PLH}		2.0	70	195	244	ns
			4.5	27	39	49	ns
			6.0	23	33	41	ns
Maximum Propagation Delay (Any D to W)	t _{PHL} , t _{PLH}		2.0	75	185	231	ns
			4.5	29	37	46	ns
			6.0	25	32	40	ns
Maximum Propagation Delay (Strobe to Y)	t _{PHL} , t _{PLH}		2.0	50	140	175	ns
			4.5	21	28	35	ns
			6.0	18	24	30	ns
Maximum Propagation Delay (Strobe to W)	t _{PHL} , t _{PLH}		2.0	45	127	159	ns
			4.5	20	25	32	ns
			6.0	17	22	28	ns
Maximum Output Rise and Fall Time	t _{TLH} , t _{THL}		2.0	30	75	95	ns
			4.5	8	15	19	ns
			6.0	7	13	16	ns
Power Dissipation Capacitance	C _{PD}	Per Package, Note 4	–	110	–	–	pF
Maximum Input Capacitance	C _{IN}		–	5	10	10	pF

Note 4. C_{PD} determines the no load dynamic power consumption, $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$, and the no load dynamic current consumption, $I_S = C_{PD} V_{CC} f + I_{CC}$.

Truth Table:

Inputs				Outputs	
Select			Strobe	Y	W
C	B	A	S		
X	X	X	H	L	H
L	L	L	L	D0	D0
L	L	H	L	D1	D1
L	H	L	L	D2	D2
L	H	H	L	D3	D3
H	L	L	L	D4	D4
H	L	H	L	D5	D5
H	H	L	L	D6	D6
H	H	H	L	D7	D7

H = HIGH Level

L = LOW Level

X = Don't Care

D0, D1 . . . D7 = the level of the respective D input

Pin Connection Diagram

Data Input 3	1	16	V _{CC}
Data Input 2	2	15	Data Input 4
Data Input 1	3	14	Data Input 5
Data Input 0	4	13	Data Input 6
Output Y	5	12	Data Input 7
Output W	6	11	Data Select A
Strobe	7	10	Data Select B
GND	8	9	Data Select C

