



FMS6400-1

Dual-Channel Video Driver with Integrated Filters and Composite Video Summer

Features

- 5.0 MHz 5th-Order Y, C filters with Composite Summer
- Selectable 0dB or 6dB Gain
- 50dB Stop-Band Attenuation at 27MHz on Y, C, and CV Outputs
- No External Frequency Selection Components or Clocks
- AC-Coupled Inputs
- AC-or DC-Coupled Outputs
- Continuous Time Low-Pass Filters
- 0.4% / 0.4° Differential Gain/Phase on Y, C, and CV Channels
- Integrated DC-Restore Circuitry with Low Tilt
- Lead (Pb) Free SOIC-8 Package

Description

The FMS6400-1 is a dual Y/C 5th-order Butterworth low-pass video filter optimized for minimum overshoot and flat group delay. The device contains a summing circuit to generate filtered composite video. In a typical application, the Y and C input signals from DACs are AC coupled into the filters. Both channels have DC-restore circuitry to clamp the DC input levels during video sync. The Y and C channels use separate feedback clamps. The clamp pulse is derived from the Y channel.

All outputs are capable of driving 2V_{PP}, AC or DC coupled, into either a single or dual video load. A single video load consists of a series-75Ω impedance-matching resistor connected to a terminated 75Ω line. This presents a total of 150Ω of loading to the part. A dual load is two of these in parallel, which presents a total of 75Ω to the part. The gain of the Y, C, and CV signals can be selected for 0dB or 6dB with 1V_{PP} input levels. All video channels are clamped during sync to establish the appropriate output voltage reference levels.

Applications

- Cable Set-Top Boxes
- Satellite Set-Top Boxes
- DVD Players
- Personal Video Recorders (PVR)
- Video On Demand (VOD)

Related Applications Notes

- [AN-6041 PCB Layout Considerations for Video Filter / Drivers](#)

Ordering Information

Part Number	Operating Temperature Range	 Eco Status	Package	Packing Method
FMS64001CS1X	0°C to +70°C	RoHS	8-Lead, Small-Outline Integrated Circuit (SOIC)	2500 Reel

 For Fairchild's definition of Eco Status, please visit: http://www.fairchildsemi.com/company/green/rohs_green.html.

Block Diagram




Figure 1. Block Diagram

Typical Application Diagram




Figure 2. AC-or DC-Coupled Application Diagram

Pin Configurations




Figure 3. FMS6400 SOIC-8

Pin Definitions

Pin #	Name	Type	Description
1	YIN	Input	Luminance (Luma) input. In a typical system, this pin is connected to the Luma or composite video output pin from the external video encoder.
2	ASEL	Input	Channel gain select. "0" = -0dB, "1" = 6dB.
3	GND	Input	Must be tied to ground.
4	CIN	Input	Chrominance (Chroma) input. In a typical system, this pin is connected to the Chroma output pin from the external video encoder.
5	COUT	Output	Filtered chrominance video output from the C _{IN} channel.
6	CVOUT	Output	Composite video output. This pin is the sum of Y _{OUT} and C _{OUT} .
7	VCC	Inputs	+5V Supply
8	YOUT	Output	Filtered luminance output from the Y _{IN} channel.

Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Symbol	Parameter	Min.	Max.	Unit
V_{CC}	DC Supply Voltage	-0.3	6.0	V
V_{IO}	Analog and Digital I/O	-0.3	$V_{CC} + 0.3$	V
I_{OUT}	Output Current Any One Channel, Do Not Exceed		40	mA

Recommended Operating Conditions

Symbol	Parameter	Min.	Typ.	Max.	Unit
T_A	Operating Temperature Range	0		+70	°C
V_{CC}	Supply Voltage Range	4.75	5.00	5.25	V

ESD Information

Symbol	Parameter	Value	Unit
ESD	Human Body Model, JESD22-A114	8	kV
	Charged Device Model, JESD22-C101	2	

Reliability Information

Symbol	Parameter	Min.	Typ.	Max.	Unit
T_J	Junction Temperature			+150	°C
T_{STG}	Storage Temperature Range	-65		+150	°C
T_L	Lead Temperature (Soldering, 10 seconds)			300	°C
Θ_{JA}	Thermal Resistance (JEDEC Standard Multi-Layer Test Boards, Still Air)		115		°C/W

DC Specifications

$T_A = 25^\circ\text{C}$, $V_{CC} = 5.0\text{V}$, $V_{IN} = 1V_{PP}$, $A_{SEL} = 1$ (6dB gain); all input is AC coupled with $0.1\mu\text{F}$; all output is AC coupled with $220\mu\text{F}$ into a 150Ω load; referenced to 400kHz, unless otherwise noted.

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_{CC}	Supply Current ⁽¹⁾	No Load		50	65	mA
V_{IN}	Input Voltage Maximum			1.4		V_{PP}
PSRR	Power Supply Rejection Ratio	All Channels DC		50		dB

Note:

- 100% tested at 25°C .

AC Electrical Specifications

$T_A = 25^\circ\text{C}$, $V_{CC} = 5.0\text{V}$, $V_{IN} = 1V_{PP}$, $A_{SEL} = 1$ (6dB gain); all input is AC coupled with $0.1\mu\text{F}$; all output is AC coupled with $220\mu\text{F}$ into a 150Ω load; referenced to 400kHz, unless otherwise noted.

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
AV_{0dB}	Channel Gain ⁽²⁾	All Channel, $A_{SEL} = 0$	-0.25	0	0.25	dB
AV_{6dB}	Channel Gain ⁽²⁾	All Channel, $A_{SEL} = 1$	5.75	6.00	6.25	dB
C_{SYNC}	C_{OUT} Output Level (During Sync) ⁽²⁾	Sync Present on Y_{IN} (after 6dB Gain)	0.80	1.00	1.30	V
Y_{SYNC}	Y_{OUT} Output Level (During Sync) ⁽²⁾		0.20	0.35	0.50	
CV_{SYNC}	CV_{OUT} Output Level (During Sync) ⁽²⁾		0.20	0.35	0.50	
t_{CLAMP}	Clamp Response Time (Y Channel)	Settled to within 10mV		10		ms
f_{Flat}	Gain Flatness to 2.4MHz	All Channels		-0.05		dB
f_C	-3dB Bandwidth ⁽²⁾	All Channels	4.1	5.1		MHz
f_{SB}	Stopband Attenuation ⁽²⁾	All Channels at 27MHz	37	52		dB
dG	Differential Gain	All Channels		0.4		%
dP	Differential Phase	All Channels		0.4		°
THD	Output Distortion	$V_{OUT} = 1.4V_{PP}$, 3.58MHz		0.3		%
X_{TALK}	Crosstalk	At 3.58MHz		-45		dB
SNR	Signal-to-Noise Ratio	Y, C Channel	NTC-7 weighting; 4.2MHz LP, 100kHz HP	75		dB
		CV Channel		70		
t_{pd}	Propagation Delay	All Channels		136		ns
GD	Group Delay Deviation	All Channels at 3.58MHz		10		ns
t_{SKEW}	Skew Between Y_{OUT} and C_{OUT}	At 1MHz		0		ns
t_{CLGCV}	Chroma-Luma Gain CV_{OUT} ⁽²⁾	$f = 3.58\text{MHz}$ (referenced to Y_{IN} at 400KHz)	94	100	104	%
t_{CLDCV}	Chroma-Luma Delay CV_{OUT}			10		ns

Note:

- 100% tested at 25°C ,

Application Information

Functional Description

This product is a two-channel monolithic, continuous-time, video filter designed for reconstructing the luminance and chrominance signals from an S-Video D/A source. Composite video output is generated by summing the Y and C outputs. The chip is designed to have AC-coupled inputs and works equally well with AC- or DC-coupled outputs.

The reconstruction filters provide a 5th-order Butterworth response with group delay equalization. This provides a maximally flat response in terms of delay and amplitude. Each of the three outputs is capable of driving 2V_{PP} into a 75Ω load.

All channels are clamped during the sync interval to set the appropriate minimum output DC level. With this operation, the effective input time constant is greatly reduced, which allows for the use of small low-cost coupling capacitors. The net effect is that the input settles to 10mV in 10ms for any DC shifts present in the input video signal.

In most applications, the input coupling capacitors are 0.1μF. The Y and C inputs typically sink 1μA of current during active video, which normally tilts a horizontal line by 2mV at the Y output. During sync, the clamp restores this leakage current by sourcing an average of 20μA over the clamp interval. Any change in the coupling capacitor values affects the amount of tilt per line. Any reduction in tilt comes with an increase in settling time.

Luminance (Y) I/O

The typical Luma input is driven by either a low-impedance source of 1V_{PP} or the output of a 75Ω-terminated line driven by the output of a current DAC. In either case, the input must be capacitively coupled to allow the sync detect and DC restore circuitry to operate properly.

All outputs are capable of driving 2V_{PP}, AC or DC coupled, into either a single or dual video load. A single video load consists of a series-75Ω, impedance-matching resistor connected to a terminated 75Ω line. This presents a total of 150Ω of loading to the part. A dual load is two of these in parallel, which presents a total of 75Ω to the part.

Channel gain of 0dB on all channels is selected by tying pin 2 to ground. Channel gain of 6dB on all channels is selected by tying pin 2 to V_{CC}. Both gain settings assume standard input video levels of 1V_{PP}.

Chrominance (C) I/O

The chrominance input can be driven in the same manner as the luminance input, but is typically only a 0.7V_{PP} signal. Since the chrominance signal doesn't contain any DC content, the output signal can be AC coupled using as small as a 0.1μF capacitor if DC coupling is not desired.

Composite Video (CV) Output

The composite video output driver is same as the other outputs.

Layout Considerations

General layout and supply bypassing play major roles in high-frequency performance and thermal characteristics. Fairchild offers a demonstration board, FMS6400DEMO, to use as a guide for layout and to aid in device testing and characterization. The FMS6400DEMO is a four-layer board with a full power and ground plane. For optimum results, follow the steps below as a basis for high frequency layout:

- Include 10μF and 0.1μF ceramic bypass capacitors.
- Place the 10μF capacitor within 0.75 inches of the power pin.
- Place the 0.1μF capacitor within 0.1 inches of the power pin.
- If using DC-coupled outputs, use a large ground plane to help dissipate heat.
- Minimize all trace lengths to reduce series inductances.

Output Considerations

The FMS6400-1 outputs are DC offset from the input by 150mV. Therefore, $V_{OUT} = 2 \cdot V_{IN} \text{ DC} + 150\text{mV}$. This offset is required to obtain optimal performance from the output driver and is held at the minimum value to decrease the standing DC current into the load. Since the FMS6400-1 has a 2x (6dB) gain, the output is typically connected via a 75Ω-series back-matching resistor, followed by the 75Ω video cable. Due to the inherent divide by two of this configuration, the blanking level at the load of the video signal is always less than 1V. When AC-coupling the output, ensure that the coupling capacitor of choice passes the lowest frequency content in the video signal and that line time distortion (video tilt) is kept as low as possible.

The selection of the coupling capacitor is a function of the subsequent circuit input impedance and the leakage current of the input being driven. To obtain the highest quality output video signal, the series termination resistor must be placed as close to the output pin as possible. This greatly reduces the parasitic capacitance and inductance effect on the output driver. The distance from the device pin to the series termination resistor should be no greater than 0.1 inches.




Figure 4. Distance from Device Pin to Series Termination Resistor

Physical Dimensions




Figure 5. 8- Lead Small Outline Integrated Circuit (SOIC) Package

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:
<http://www.fairchildsemi.com/packaging/>.



TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™
Auto-SPM™
Build it Now™
CorePLUS™
CorePOWER™
CROSSVOLT™
CTL™
Current Transfer Logic™
EcoSPARK®
EfficientMax™
EZSWITCH™
EZ™
DEUXPEED™
F®
Fairchild®
Fairchild Semiconductor®
FACT Quiet Series™
FACT®
FAST®
FastvCore™
FETBench™

FlashWriter®
FPS™
F-PFS™
FRFET®
Global Power Resource™
Green FPS™
Green FPS™ e-Series™
Gmax™
GTO™
IntelliMAX™
ISOPLANAR™
MegaBuck™
MICROCOUPLER™
MicroFET™
MicroPak™
MillerDrive™
MotionMax™
Motion-SPM™
OPTOLOGIC®
OPTOPLANAR®
PDP SPM™

Power-SPM™
PowerTrench®
PowerXS™
Programmable Active Droop™
QFET®
QS™
Quiet Series™
RapidConfigure™
Saving our world, 1mW/W/kW at a time™
SignalWise™
SmartMax™
SMART START™
SPM®
STEALTH™
SuperFET™
SuperSOT™.3
SuperSOT™.6
SuperSOT™.8
SupreMOS™
SyncFET™
Sync-Lock™

SYSTEM GENERAL®
The Power Franchise®
the power franchise
TinyBoost™
TinyBuck™
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TriFault Detect™
TRUECURRENT™
µSerDes™
SerDes®
UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
XS™

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. 143