

100314

Low Power Quint Differential Line Receiver

General Description

The 100314 is a monolithic quint differential line receiver with emitter-follower outputs. An internal reference supply (V_{BB}) is available for single-ended reception. When used in single-ended operation the apparent input threshold of the true inputs is 25 mV to 30 mV higher (positive) than the threshold of the complementary inputs. Unlike other F100K ECL devices, the inputs do not have input pull-down resistors.


Active current sources provide common-mode rejection of 1.0V in either the positive or negative direction. A defined output state exists if both inverting and non-inverting inputs are at the same potential between V_{EE} and V_{CC} . The defined state is logic HIGH on the $\bar{O}_a-\bar{O}_e$ outputs.

Features

- 35% power reduction of the 100114
- 2000V ESD protection
- Pin/function compatible with 100114
- Voltage compensated operating range = -4.2V to -5.7V
- Available to MIL-STD-883
- Available to industrial grade temperature range

Ordering Code:


Logic Symbol



Pin Names	Description
D_a-D_e	Data Inputs
$\bar{D}_a-\bar{D}_e$	Inverting Data Inputs
O_a-O_e	Data Outputs
$\bar{O}_a-\bar{O}_e$	Complementary Data Outputs


Connection Diagrams

24-Pin DIP/SOIC




DS010260-2

28-Pin PCC



DS010260-4

24-Pin Quad Cerpak



DS010260-3

Absolute Maximum Ratings (Note 1)

Above which the useful life may be impaired (Note 1)

Storage Temperature (T_{STG}) -65°C to $+150^{\circ}\text{C}$

Maximum Junction Temperature (T_J)

Ceramic $+175^{\circ}\text{C}$

Plastic $+150^{\circ}\text{C}$

Pin Potential to Ground Pin (V_{EE}) -7.0V to $+0.5\text{V}$

Input Voltage (DC) V_{EE} to $+0.5\text{V}$

Output Current (DC Output HIGH) -50 mA

ESD (Note 2) $\geq 2000\text{V}$

Recommended Operating Conditions

Case Temperature (T_C)

Commercial 0°C to $+85^{\circ}\text{C}$

Industrial -40°C to $+85^{\circ}\text{C}$

Military -55°C to $+125^{\circ}\text{C}$

Supply Voltage (V_{EE}) -5.7V to -4.2V

Note 1: Absolute maximum ratings are those values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: ESD testing conforms to MIL-STD-883, Method 3015.

Commercial Version DC Electrical Characteristics

$V_{EE} = -4.2\text{V}$ to -5.7V , $V_{CC} = V_{CCA} = \text{GND}$, $T_C = 0^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ (Note 3)

Symbol	Parameter	Min	Typ	Max	Units	Conditions
V_{OH}	Output HIGH Voltage	-1025	-955	-870	mV	$V_{IN} = V_{IH} (\text{Max})$ Loading with or $V_{IL} (\text{Min})$ 50Ω to -2.0V
V_{OL}	Output LOW Voltage	-1830	-1705	-1620	mV	$V_{IN} = V_{IH}$ Loading with or $V_{IL} (\text{Max})$ 50Ω to -2.0V
V_{OHC}	Output HIGH Voltage	-1035			mV	$V_{IN} = V_{IH}$ Loading with or $V_{IL} (\text{Max})$ 50Ω to -2.0V
V_{OLC}	Output LOW Voltage			-1610	mV	$V_{IN} = V_{IH}$ Loading with or $V_{IL} (\text{Max})$ 50Ω to -2.0V
V_{BB}	Output Reference Voltage	-1380	-1320	-1260	mV	$I_{V_{BB}} = -250\text{ }\mu\text{A}$
V_{DIFF}	Input Voltage Differential	150			mV	Required for Full Output Swing
V_{CM}	Common Mode Voltage	$V_{CC} - 2.0$		$V_{CC} - 0.5$	V	
V_{IH}	Single-Ended Input High Voltage	-1110		-870	mV	Guaranteed HIGH Signal for All Inputs (with one input tied to V_{BB}) $V_{BB} (\text{Max}) + V_{DIFF}$
V_{IL}	Single-Ended Input Low Voltage	-1830		-1530	mV	Guaranteed LOW Signal for All Inputs (with one input tied to V_{BB}) $V_{BB} (\text{Min}) - V_{DIFF}$
I_{IL}	Input LOW Current	0.50			μA	$V_{IN} = V_{IL} (\text{Min})$
I_{IH}	Input HIGH Current			240	μA	$V_{IN} = V_{IH} (\text{Max})$, $D_a - D_e = V_{BB}$, $\overline{D_a} - \overline{D_e} = V_{IL} (\text{Min})$
I_{CBO}	Input Leakage Current	-10			μA	$V_{IN} = V_{EE}$, $D_a - D_e = V_{BB}$, $\overline{D_a} - \overline{D_e} = V_{IL} (\text{Min})$
I_{EE}	Power Supply Current	-60		-30	mA	$D_a - D_e = V_{BB}$, $\overline{D_a} - \overline{D_e} = V_{IL} (\text{Min})$

Note 3: The specified limits represent the "worst case" value for the parameter. Since these values normally occur at the temperature extremes, additional noise immunity and guardbanding can be achieved by decreasing the allowable system operating ranges. Conditions for testing shown in the tables are chosen to guarantee operation under "worst case" conditions.

DIP AC Electrical Characteristics

$V_{EE} = -4.2V$ to $-5.7V$, $V_{CC} = V_{CCA} = GND$

Symbol	Parameter	$T_C = 0^\circ C$		$T_C = +25^\circ C$		$T_C = +85^\circ C$		Units	Conditions
		Min	Max	Min	Max	Min	Max		
f_{MAXFS}	Toggle Frequency (Full Swing)	250		250		250		MHz	(Note 2)
f_{MAXRS}	Toggle Frequency (Reduced Swing)	700		700		700		MHz	(Note 3)
t_{PLH} t_{PHL}	Propagation Delay Data to Output	0.65	1.90	0.65	2.00	0.70	2.00	ns	Figures 1, 2
t_{TLH} t_{THL}	Transition Time 20% to 80%, 80% to 20%	0.35	1.20	0.35	1.20	0.35	1.20	ns	

SOIC, PCC and Cerpak AC Electrical Characteristics

$V_{EE} = -4.2V$ to $-5.7V$, $V_{CC} = V_{CCA} = GND$

Symbol	Parameter	$T_C = 0^\circ C$		$T_C = +25^\circ C$		$T_C = +85^\circ C$		Units	Conditions
		Min	Max	Min	Max	Min	Max		
f_{MAXFS}	Toggle Frequency (Full Swing)	250		250		250		MHz	(Note 5)
f_{MAXRS}	Toggle Frequency (Reduced Swing)	700		700		700		MHz	(Note 6)
t_{PLH} t_{PHL}	Propagation Delay Data to Output	0.65	1.70	0.65	1.80	0.70	1.80	ns	Figures 1, 2
t_{TLH} t_{THL}	Transition Time 20% to 80%, 80% to 20%	0.35	1.10	0.35	1.10	0.35	1.10	ns	
t_{PLH} t_{PHL}	Propagation Delay Data to Output	0.70	1.50	0.80	1.60	0.90	1.80	ns	PCC only
t_{OSHL}	Maximum Skew Common Edge Output-to-Output Variation Data to Output Path		280		280		280	ps	PCC only (Notes 4, 7)
t_{OSLH}	Maximum Skew Common Edge Output-to-Output Variation Data to Output Path		330		330		330	ps	PCC only (Notes 4, 7)
t_{OST}	Maximum Skew Opposite Edge Output-to-Output Variation Data to Output Path		330		330		330	ps	PCC only (Notes 4, 7)
t_{PS}	Maximum Skew Pin (Signal) Transition Variation Data to Output Path		320		320		320	ps	PCC only (Notes 4, 7)

Note 4: Output-to-Output Skew is defined as the absolute value of the difference between the actual propagation delay for any outputs within the same packaged device. The specifications apply to any outputs switching in the same direction either HIGH to LOW (t_{OSHL}), or LOW to HIGH (t_{OSLH}), or in opposite directions both HL and LH (t_{OST}). Parameters t_{OST} and t_{PS} guaranteed by design.

Note 5: Maximum toggle frequency at which V_{OH} and V_{OL} DC specifications are maintained.

Note 6: Maximum toggle frequency at which outputs maintain 150 mV swing.

Note 7: All skews calculated using input crossing point to output crossing point propagation delays.

Industrial Version PCC DC Electrical Characteristics

$V_{EE} = -4.2V$ to $-5.7V$, $V_{CC} = V_{CCA} = GND$, $T_C = -40^\circ C$ to $+85^\circ C$ (Note 8)

Symbol	Parameter	$T_C = -40^\circ C$		$T_C = 0^\circ C$ to $+85^\circ C$		Units	Conditions	
		Min	Max	Min	Max			
V_{OH}	Output HIGH Voltage	-1085	-870	-1025	-870	mV	$V_{IN} = V_{IH}$ (Max)	Loading with 50Ω to $-2.0V$
V_{OL}	Output LOW Voltage	-1830	-1575	-1830	-1620	mV	or V_{IL} (Min)	
V_{OHC}	Output HIGH Voltage	-1095		-1035		mV	$V_{IN} = V_{IH}$	Loading with 50Ω to $-2.0V$
V_{OLC}	Output LOW Voltage		-1565		-1610	mV	or V_{IL} (Min)	
V_{BB}	Output Reference Voltage	-1395	-1255	-1380	-1260	mV	$I_{VBB} = -250 \mu A$	
V_{DIFF}	Input Voltage Differential	150		150		mV	Required for Full Output Swing	
V_{CM}	Common Mode Voltage	$V_{CC} - 2.0$	$V_{CC} - 0.5$	$V_{CC} - 2.0$	$V_{CC} - 0.5$	V		
V_{IH}	Single-Ended Input High Voltage	-1115	-870	-1110	-870	mV	Guaranteed HIGH Signal for All Inputs (with one input tied to V_{BB}) V_{BB} (Max) + V_{DIFF}	
V_{IL}	Single-Ended Input Low Voltage	-1830	-1535	-1830	-1530	mV	Guaranteed LOW Signal for All Inputs (with one input tied to V_{BB}) V_{BB} (Min) - V_{DIFF}	
I_{IL}	Input LOW Current	0.50		0.50		μA	$V_{IN} = V_{IL}$ (Min)	
I_{IH}	Input HIGH Current		240		240	μA	$V_{IN} = V_{IH}$ (Max), $D_a - D_e = V_{BB}$, $\overline{D_a} - \overline{D_e} = V_{IL}$ (Min)	
I_{CBO}	Input Leakage Current	-10		-10		μA	$V_{IN} = V_{EE}$, $D_a - D_e = V_{BB}$, $\overline{D_a} - \overline{D_e} = V_{IL}$ (Min)	
I_{EE}	Power Supply Current	-60	-30	-60	-30	mA	$D_a - D_e = V_{BB}$, $\overline{D_a} - \overline{D_e} = V_{IL}$ (Min)	

Note 8: The specified limits represent the "worst case" value for the parameter. Since these values normally occur at the temperature extremes, additional noise immunity and guardbanding can be achieved by decreasing the allowable system operating ranges. Conditions for testing shown in the tables are chosen to guarantee operation under "worst case" conditions.

PCC AC Electrical Characteristics

$V_{EE} = -4.2V$ to $-5.7V$, $V_{CC} = V_{CCA} = GND$

Symbol	Parameter	$T_C = -40^\circ C$		$T_C = +25^\circ C$		$T_C = +85^\circ C$		Units	Conditions
		Min	Max	Min	Max	Min	Max		
f_{MAXFS}	Toggle Frequency (Full Swing)	250		250		250		MHz	(Note 5)
f_{MAXRS}	Toggle Frequency (Reduced Swing)	700		700		700		MHz	(Note 6)
t_{PLH}	Propagation Delay Data to Output	0.65	1.70	0.65	1.80	0.70	1.80	ns	Figures 1, 2
t_{TLH}	Transition Time 20% to 80%, 80% to 20%	0.20	1.40	0.35	1.10	0.35	1.10	ns	
t_{THL}									

Military Version DC Electrical Characteristics

$V_{EE} = -4.2V$ to $-5.7V$, $V_{CC} = V_{CCA} = GND$, $T_C = -55^{\circ}C$ to $+125^{\circ}C$ (Note 11)

Symbol	Parameter	Min	Typ	Max	Units	T_C	Conditions	Notes
V_{OH}	Output HIGH Voltage	-1025		-870	mV	$0^{\circ}C$ to $+125^{\circ}C$	$V_{IN} = V_{IH} (Max)$ or $V_{IL} (Min)$ Loading with 50Ω to $-2.0V$	(Notes 9, 10, 11)
		-1085		-870	mV	$-55^{\circ}C$		
V_{OL}	Output LOW Voltage	-1830		-1620	mV	$0^{\circ}C$ to $+125^{\circ}C$	$V_{IN} = V_{IH} (Max)$ or $V_{IL} (Min)$ Loading with 50Ω to $-2.0V$	(Notes 9, 10, 11)
		-1830		-1555	mV	$-55^{\circ}C$		
V_{OHC}	Output HIGH Voltage	-1035			mV	$0^{\circ}C$ to $+125^{\circ}C$	$V_{IN} = V_{IH} (Max)$ or $V_{IL} (Min)$ Loading with 50Ω to $-2.0V$	(Notes 9, 10, 11)
		-1085			mV	$-55^{\circ}C$		
V_{OLC}	Output LOW Voltage			-1610	mV	$0^{\circ}C$ to $+125^{\circ}C$	$V_{IN} = V_{IH} (Max)$ or $V_{IL} (Min)$ Loading with 50Ω to $-2.0V$	(Notes 9, 10, 11)
				-1555	mV	$-55^{\circ}C$		
V_{BB}	Output Reference Voltage			-1260	mV	$0^{\circ}C$ to $+125^{\circ}C$	$I_{VBB} = 0 \mu A$, $V_{EE} = 4.2V$	(Notes 9, 10, 11)
		-1380		-1260	mV	$0^{\circ}C$ to $+125^{\circ}C$	$I_{VBB} = -250 \mu A$, $V_{EE} = -5.7V$	(Notes 9, 10, 11)
		-1396			mV	$-55^{\circ}C$	$I_{VBB} = -350 \mu A$, $V_{EE} = -5.7V$	(Notes 9, 10, 11)
V_{DIFF}	Input Voltage Differential	150			mV	$-55^{\circ}C$ to $+125^{\circ}C$	Required for Full Output Swing	(Notes 9, 10, 11)
V_{CM}	Common Mode Voltage	$V_{CC} - 2.0$		$V_{CC} - 0.5$	V	$-55^{\circ}C$ to $+125^{\circ}C$		(Notes 9, 10, 11)
V_{IH}	Single-Ended Input High Voltage	-1165		-870	mV	$-55^{\circ}C$ to $+125^{\circ}C$	Guaranteed HIGH Signal for All Inputs (with $\overline{D}_n$ tied to V_{BB})	(Notes 9, 10, 11, 12)
V_{IL}	Single-Ended Input Low Voltage	-1830		-1475	mV	$-55^{\circ}C$ to $+125^{\circ}C$	Guaranteed LOW Signal for All Inputs (with $\overline{D}_n$ tied to V_{BB})	(Notes 9, 10, 11, 12)
I_{IH}	Input HIGH Current			50	μA	$0^{\circ}C$ to $+125^{\circ}C$	$V_{IN} = V_{IH} (Max)$, $D_a - D_e = V_{BB}$, $\overline{D}_a - \overline{D}_e = V_{IL} (Min)$	(Notes 9, 10, 11)
				70	μA	$-55^{\circ}C$		
I_{CBO}	Input Leakage Current	-10			μA	$-55^{\circ}C$ to $+125^{\circ}C$	$V_{IN} = V_{EE}$, $D_a - D_e = V_{BB}$, $\overline{D}_a - \overline{D}_e = V_{IL} (Min)$	(Notes 9, 10, 11)
I_{EE}	Power Supply Current	-65		-25	mA	$-55^{\circ}C$ to $+125^{\circ}C$	$D_a - D_e = V_{BB}$, $\overline{D}_a - \overline{D}_e = V_{IL} (Min)$	(Notes 9, 10, 11)

Note 9: F100K 300 Series cold temperature testing is performed by temperature soaking (to guarantee junction temperature equals $-55^{\circ}C$), then testing immediately without allowing for the junction temperature to stabilize due to heat dissipation after power-up. This provides "cold start" specs which can be considered a worst case condition at cold temperatures.

Note 10: Screen tested 100% on each device at $-55^{\circ}C$, $+25^{\circ}C$, and $+125^{\circ}C$, Subgroups 1, 2, 3, 7, and 8.

Note 11: Sample tested (Method 5005, Table I) on each manufactured lot at $-55^{\circ}C$, $+25^{\circ}C$, and $+125^{\circ}C$, Subgroups A1, 2, 3, 7, and 8.

Note 12: Guaranteed by applying specified input condition and testing V_{OH}/V_{OL} .

AC Electrical Characteristics

$V_{EE} = -4.2V$ to $-5.7V$, $V_{CC} = V_{CCA} = GND$

Symbol	Parameter	$T_C = -55^\circ C$		$T_C = +25^\circ C$		$T_C = +125^\circ C$		Units	Conditions	Notes
		Min	Max	Min	Max	Min	Max			
t_{PLH}	Propagation Delay	0.40	2.30	0.60	2.20	0.60	2.70	ns	Figures 1, 2	(Notes 13, 14, 15)
t_{PHL}	Data to Output									
t_{TLH}	Transition Time	0.20	1.40	0.20	1.40	0.20	1.40	ns		(Note 16)
t_{THL}	20% to 80%, 80% to 20%									


Note 13: F100K 300 Series cold temperature testing is performed by temperature soaking (to guarantee junction temperature equals $-55^\circ C$), then testing immediately after power-up. This provides "cold start" specs which can be considered a worst case condition at cold temperatures.

Note 14: Screen tested 100% on each device at $+25^\circ C$ temperature only, Subgroup A9.

Note 15: Sample tested (Method 5005, Table I) on each manufactured lot at $+25^\circ C$, Subgroup A9, and at $+125^\circ C$ and $-55^\circ C$ temperatures, Subgroups A10 and A11.

Note 16: Not tested at $+25^\circ C$, $+125^\circ C$ and $-55^\circ C$ temperature (design characterization data).

Test Circuit




DS010260-5

Note: V_{CC} , $V_{CCA} = +2V$, $V_{EE} = -2.5V$
 $L1$ and $L2$ = equal length 50Ω impedance lines
 $R_T = 50\Omega$ terminator internal to scope
 Decoupling $0.1 \mu F$ from GND to V_{CC} and V_{EE}
 All unused outputs are loaded with 50Ω to GND
 C_L = Fixture and stray capacitance $\leq 3 pF$

FIGURE 1. AC Test Circuit

Switching Waveforms



DS010260-6


FIGURE 2. Propagation Delay and Transition Times

Ordering Information


The device number is used to form part of a simplified purchasing code where a package type and temperature range are defined as follows:

Device Type (Basic)	100314	D	C	QB	Special Variation
Package Code					QB = Military grade device with environmental and burn-in processing
D = Ceramic DIP					Temperature Range
F = Quad Cerpak					C = Commercial (0°C to +85°C)
Q = Plastic Leaded Chip Carrier (PCC)					I = Industrial (−40°C to +85°C) (PCC only)
P = Plastic DIP					M = Military (−55°C to +125°C)
S = Small Outline (SOIC)					

DS010260-7


Physical Dimensions inches (millimeters) unless otherwise noted

24-Lead Ceramic Dual-In-Line Package (0.400" Wide) (D)
Package Number J24E



24-Lead Molded Package (0.300") Wide (S)
Package Number M24B


Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



N24E (REV A)

24-Lead Plastic Dual-In-Line Package (P)
Package Number N24E


Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



**28-Lead Plastic Chip Carrier (Q)
Package Number V28A**

V28A (REV K)

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



W24B (REV D)

**24-Lead Quad Cerpak (F)
Package Number W24B**

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Fairchild Semiconductor Corporation Americas
Customer Response Center
Tel: 1-888-522-5372

Fairchild Semiconductor Europe
Fax: +49 (0) 1 80-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 8 141-35-0
English Tel: +44 (0) 1 793-85-68-56
Italy Tel: +39 (0) 2 57 5631

Fairchild Semiconductor Hong Kong Ltd.
13th Floor, Straight Block,
Ocean Centre, 5 Canton Rd.
Tsimshatsui, Kowloon
Hong Kong
Tel: +852 2737-7200
Fax: +852 2314-0061

National Semiconductor Japan Ltd.
Tel: 81-3-5620-6175
Fax: 81-3-5620-6179

www.fairchildsemi.com